

# MLH150BSL03B

t a Quote

### MLH150BSL03B Information

Heisener.com	Part Number	MLH150BSL03B
	Manufacturer	Honeywell Sensing and Productivity Solutions
	Category	Sensors, Transducers Pressure Sensors, Transducers
	Description	SENSOR SEALED GAUGE 0-150 PSI
	Package	Cylinder, Metal
		For the pricing/inventory/lead time, please contact
For Reference Only		us Wabaita: https://www.baisapar.com
		Website: https://www.heisener.com E-mail: salesdept@heisener.com

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## MLH150BSL03B Specifications

Manufacturer     Honeywell Sensing and Productivity Solutions       Category     Sensors, Transducers       Pressure Sensors, Transducers     Pressure Sensors, Transducers       Package     Cylinder, Metal       Series     MLH       Pressure Type     Sealed Gauge       Operating Pressure     Sealed Gauge       Output Type     Analog Current       Output Type     4 mA ~ 20 mA       Accuracy     ±0.25%       Voltage - Supply     9.5 V ~ 30 V       Port Size     Male - M14 x 1.5       Port Style     Threaded       Termination Style     Cable Im       Maximum Pressure     -       Operating Temperature     -       Operating Temperature     -       Package / Case     Cylinder, Metal		
CategorySensors, TransducersPackageCylinder, MetalPackageCylinder, MetalSeriesMLHPressure TypeSealed GaugeOperating Pressure2175.57 PSI (15000 kPa)Output TypeAnalog CurrentOutput Type4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply9.5 V ~ 30 VPort SizeMale - M14 x 1.5Port SiyleThreadedFeaturesAmplified Output, Temperature CompensatedCable 1m-Operating Temperature-Operating Temperature-Operating Temperature-Operating Temperature-Operating Temperature-Operating Temperature-Stakage / CaseCylinder, MetalSupplier Device Package-	Manufacturer Part Number	MLH150BSL03B
PackagePressure Sensors, TransducersPackageCylinder, MetalSeriesMLHPressure TypeSealed GaugeOperating Pressure2175.57 PSI (15000 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply9.5 V ~ 30 VPort SizeMale - M14 x 1.5Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedMaximum Pressure-Operating Temperature-40°C ~ 125°CPackage / Case-Supplier Device Package-	Manufacturer	Honeywell Sensing and Productivity Solutions
PackageCylinder, MetalSeriesMLHPressure TypeSealed GaugeOperating Pressure175.57 PSI (15000 kPa)Output TypeAnalog CurrentOutput Que4 mA ~ 20 mAAccuracy40.25%Voltage - Supply5.5 V ~ 30 VPort SizeMale - M14 x 1.5Port SyleFriendedFeaturesAmplified Output, Temperature CompensatedPort Syle-Port Size-Port Syle-Port Syle-Port SyleCable ImPort Syle-Port Syle-Port Syle-Synder Argen Compensated-Port Syle-Port Syle-Port Syle-Synder Argen Compensated-Port Syle-Port Syle-Synder Argen Compensated-Port Syle-Synder Argen Compensated-Port Syle-Port Syle- </td <td>Category</td> <td>Sensors, Transducers</td>	Category	Sensors, Transducers
SeriesMLHPressure TypeSealed GaugeOperating Pressure2175.57 PSI (15000 kPa)Output TypeAnalog CurrentOutput Queue4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply9.5 V ~ 30 VPort SizeMale - M14 x 1.5Port SyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination Style-Operating Temperature-40°C ~ 125°CPorksge / CaseCylinder, MetalSupplier Device Package-		Pressure Sensors, Transducers
Pressure TypeSealed GaugeOperating Pressure2175.57 PSI (15000 kPa)Output TypeAnalog CurrentOutput Quest4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply9.5 V ~ 30 VPort SizeMale - M14 x 1.5Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination Style-Operating Temperature-Operating Temperature-Supplier Device Package-Supplier Device Package-	Package	Cylinder, Metal
Operating Pressure2175.57 PSI (15000 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply9.5 V ~ 30 VPort SizeMale - M14 x 1.5Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination Style-Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-	Series	MLH
Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply9.5 V ~ 30 VPort SizeMale - M14 x 1.5Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination Style-Operating Temperature-Operating Temperature-40°C ~ 125°CPackage / Case-Supplier Device Package-	Pressure Type	Sealed Gauge
Output4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply9.5 V ~ 30 VPort SizeMale - M14 x 1.5Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleCable 1mMaximum Pressure-Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-	Operating Pressure	2175.57 PSI (15000 kPa)
Accuracy±0.25%Accuracy9.5 V ~ 30 VVoltage - Supply9.5 V ~ 30 VPort SizeMale - M14 x 1.5Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleCable 1mMaximum Pressure-Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-	Output Type	Analog Current
Yoltage - Supply9.5 V ~ 30 VPort SizeMale - M14 x 1.5Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleCable 1mMaximum Pressure-Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-	Output	4 mA ~ 20 mA
Port SizeMale - M14 x 1.5Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleCable 1mMaximum Pressure-Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-	Accuracy	±0.25%
Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleCable 1mMaximum Pressure-Operating Temperature40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-	Voltage - Supply	9.5 V ~ 30 V
FeaturesAmplified Output, Temperature CompensatedTermination StyleCable 1mMaximum Pressure-Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-	Port Size	Male - M14 x 1.5
Termination StyleCable 1mMaximum Pressure-Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-	Port Style	Threaded
Maximum Pressure-Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-	Features	Amplified Output, Temperature Compensated
Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-	Termination Style	Cable 1m
Package / Case Cylinder, Metal   Supplier Device Package -	Maximum Pressure	-
Supplier Device Package -	Operating Temperature	-40°C ~ 125°C
	Package / Case	Cylinder, Metal
Report errors?	Supplier Device Package	-
		Report errors?

#### MLH150BSL03B Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### MLH150BSL03B Payment Methods



### MLH150BSL03B Shipping Methods



If you have any question about MLH150BSL03B, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com