



MLH150PGL06B Information



For Reference Only

Part Number MLH150PGL06B

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

Description SENSOR AMP 150PSI 4-20MA OUT

Package Cylinder, Metal

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









		C 101 .1
MLH150PGI	L06B	Specifications

Manufacturer Part Number MLH150PGL06B Manufacturer Honeywell Sensing and Productivity Solutions Category Sensors, Transducers Package Cylinder, Metal Series MLH Pressure Type Vented Gauge Operating Pressure 150 PSI (1034.21 kPa) Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±0.25% Voltage - Supply 9.5 V ~ 30 V Port Size Male - 1/8" (3.18mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Cable 1m Maximum Pressure 450 PSI (3102.64 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package - Report errors?			
CategorySensors, TransducersPackageCylinder, MetalSeriesMLHPressure TypeVented GaugeOperating Pressure150 PSI (1034.21 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply9.5 V ~ 30 VPort SizeMale - 1/8" (3.18mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleCable 1mMaximum Pressure450 PSI (3102.64 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-	Manufacturer Part Number	MLH150PGL06B	
Package Cylinder, Metal Series MLH Pressure Type Vented Gauge Operating Pressure Operating Pressure Ottput Type Analog Current Output 4 mA ~ 20 mA Accuracy ±0.25% Voltage - Supply 9.5 V ~ 30 V Port Size Male - 1/8" (3.18mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Cable 1m Maximum Pressure 450 PSI (3102.64 kPa) Operating Temperature - 40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package	Manufacturer	Honeywell Sensing and Productivity Solutions	
PackageCylinder, MetalSeriesMLHPressure TypeVented GaugeOperating Pressure150 PSI (1034.21 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply9.5 V ~ 30 VPort SizeMale - 1/8" (3.18mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleCable 1 mMaximum Pressure450 PSI (3102.64 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-	Category	Sensors, Transducers	
SeriesMLHPressure TypeVented GaugeOperating Pressure150 PSI (1034.21 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply9.5 V ~ 30 VPort SizeMale - 1/8" (3.18mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleCable 1mMaximum Pressure450 PSI (3102.64 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-		Pressure Sensors, Transducers	
Pressure TypeVented GaugeOperating Pressure150 PSI (1034.21 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply9.5 V ~ 30 VPort SizeMale - 1/8" (3.18mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleCable 1mMaximum Pressure450 PSI (3102.64 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-	Package	Cylinder, Metal	
Operating Pressure 150 PSI (1034.21 kPa) Output Type Analog Current 4 mA ~ 20 mA Accuracy ±0.25% Voltage - Supply 9.5 V ~ 30 V Port Size Male - 1/8" (3.18mm) NPT Port Style Features Amplified Output, Temperature Compensated Termination Style Cable 1m Maximum Pressure 450 PSI (3102.64 kPa) Operating Temperature -40°C ~ 125°C Package / Case Supplier Device Package - 150 PSI (1034.21 kPa) Amalog Current 4 mA ~ 20 mA 4 malog Current -40°C ~ 30 V Supplier Operating Compensated -40°C ~ 125°C Cylinder, Metal Supplier Device Package	Series	MLH	
Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±0.25% Voltage - Supply 9.5 V ~ 30 V Port Size Male - 1/8" (3.18mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Cable 1m Maximum Pressure 450 PSI (3102.64 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package	Pressure Type	Vented Gauge	
Output $4 \text{ mA} \sim 20 \text{ mA}$ Accuracy $\pm 0.25\%$ Voltage - Supply $9.5 \text{ V} \sim 30 \text{ V}$ Port Size $\text{Male - 1/8" (3.18mm) NPT}$ Port Style Threaded Features $\text{Amplified Output, Temperature Compensated}$ Termination Style Cable 1m Maximum Pressure $450 \text{ PSI (3102.64 kPa)}$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case Cylinder, Metal Supplier Device Package $-$	Operating Pressure	150 PSI (1034.21 kPa)	
Accuracy $\pm 0.25\%$ Voltage - Supply 9.5 V ~ 30 V Port Size Male - 1/8" (3.18mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Cable 1m Maximum Pressure 450 PSI (3102.64 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package	Output Type	Analog Current	
Voltage - Supply 9.5 V ~ 30 V Port Size Male - 1/8" (3.18mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Cable 1m Maximum Pressure 450 PSI (3102.64 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Output	4 mA ~ 20 mA	
Port Size Male - 1/8" (3.18mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Cable 1m Maximum Pressure 450 PSI (3102.64 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Accuracy	±0.25%	
Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Cable 1m Maximum Pressure 450 PSI (3102.64 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Voltage - Supply	9.5 V ~ 30 V	
Features Amplified Output, Temperature Compensated Cable 1m Maximum Pressure 450 PSI (3102.64 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Port Size	Male - 1/8" (3.18mm) NPT	
Termination Style Cable 1m Maximum Pressure 450 PSI (3102.64 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Port Style	Threaded	
Maximum Pressure $450 \text{ PSI } (3102.64 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / CaseCylinder, MetalSupplier Device Package-	Features	Amplified Output, Temperature Compensated	
Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Termination Style	Cable 1m	
Package / Case Cylinder, Metal Supplier Device Package -	Maximum Pressure	450 PSI (3102.64 kPa)	
Supplier Device Package -	Operating Temperature	-40°C ~ 125°C	
	Package / Case	Cylinder, Metal	
Report errors?	Supplier Device Package	-	
		Report errors?	

MLH150PGL06B Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MLH150PGL06B Payment Methods



















MLH150PGL06B Shipping Methods













If you have any question about MLH150PGL06B, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com