



#### **MLH200PGB06A Information**

Heisener.com

Part Number MLH200PGB06A

Manufacturer Honeywell Sensing and Productivity Solutions

**Category** Sensors, Transducers

Pressure Sensors, Transducers

**Description** MLH ALL METAL PRESS SENSE -ATF

Package Cylinder, Metal

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **MLH200PGB06A Specifications**

Manufacturer Part Number       MLH200PGB06A         Manufacturer       Honeywell Sensing and Productivity Solutions         Category       Sensors, Transducers         Package       Cylinder, Metal         Series       MLH         Pressure Type       Vented Gauge         Operating Pressure       200 PSI (1378.95 kPa)         Output Type       Analog Voltage         Output       0.5 V ~ 4.5 V         Accuracy       ±0.25%         Voltage - Supply       5 V ~ 6 V         Port Size       Male - 1/8" (3.18mm) NPT         Port Style       Threaded         Features       Amplified Output, Temperature Compensated         Termination Style       -         Maximum Pressure       600 PSI (4136.85 kPa)         Operating Temperature       -40°C ~ 125°C         Package / Case       Cylinder, Metal         Supplier Device Package       -         Report errors?			
CategorySensors, TransducersPackageCylinder, MetalSeriesMLHPressure TypeVented GaugeOperating Pressure200 PSI (1378.95 kPa)Output TypeAnalog VoltageOutput0.5 V ~ 4.5 VAccuracy±0.25%Voltage - Supply5 V ~ 6 VPort SizeMale - 1/8" (3.18mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination Style-Maximum Pressure600 PSI (4136.85 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-	Manufacturer Part Number	MLH200PGB06A	
Package Cylinder, Metal  Series MLH  Pressure Type Vented Gauge  Operating Pressure  Output Type Analog Voltage  Output  Accuracy ±0.25%  Voltage - Supply 5 V ~ 6 V  Port Size Male - 1/8" (3.18mm) NPT  Port Style Threaded  Features Amplified Output, Temperature Compensated  Termination Style  Maximum Pressure  Output - 40°C ~ 125°C  Package / Case  Cylinder, Metal  Supplier Device Package  Cylinder, Metal	Manufacturer	Honeywell Sensing and Productivity Solutions	
PackageCylinder, MetalSeriesMLHPressure TypeVented GaugeOperating Pressure200 PSI (1378.95 kPa)Output TypeAnalog VoltageOutput0.5 V ~ 4.5 VAccuracy±0.25%Voltage - Supply5 V ~ 6 VPort SizeMale - 1/8" (3.18mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination Style-Maximum Pressure600 PSI (4136.85 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-	Category	Sensors, Transducers	
SeriesMLHPressure TypeVented GaugeOperating Pressure200 PSI (1378.95 kPa)Output TypeAnalog VoltageOutput0.5 V ~ 4.5 VAccuracy±0.25%Voltage - Supply5 V ~ 6 VPort SizeMale - 1/8" (3.18mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination Style-Maximum Pressure600 PSI (4136.85 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-		Pressure Sensors, Transducers	
Pressure TypeVented GaugeOperating Pressure200 PSI (1378.95 kPa)Output TypeAnalog VoltageOutput0.5 V ~ 4.5 VAccuracy±0.25%Voltage - Supply5 V ~ 6 VPort SizeMale - 1/8" (3.18mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination Style-Maximum Pressure600 PSI (4136.85 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-	Package	Cylinder, Metal	
Operating Pressure  200 PSI (1378.95 kPa)  Output Type  Analog Voltage  Output  0.5 V ~ 4.5 V  Accuracy  ±0.25%  Voltage - Supply  5 V ~ 6 V  Port Size  Male - 1/8" (3.18mm) NPT  Port Style  Threaded  Features  Amplified Output, Temperature Compensated  Termination Style	Series	MLH	
Output TypeAnalog VoltageOutput $0.5 \text{ V} \sim 4.5 \text{ V}$ Accuracy $\pm 0.25\%$ Voltage - Supply $5 \text{ V} \sim 6 \text{ V}$ Port SizeMale - $1/8$ " (3.18mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination Style-Maximum Pressure $600 \text{ PSI (4136.85 kPa)}$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / CaseCylinder, MetalSupplier Device Package-	Pressure Type	Vented Gauge	
Output $0.5 \text{ V} \sim 4.5 \text{ V}$ Accuracy $\pm 0.25\%$ Voltage - Supply $5 \text{ V} \sim 6 \text{ V}$ Port Size $\text{Male - 1/8" (3.18mm) NPT}$ Port Style $\text{Threaded}$ Features $\text{Amplified Output, Temperature Compensated}$ Termination Style $-$ Maximum Pressure $600 \text{ PSI (4136.85 kPa)}$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case $\text{Cylinder, Metal}$ Supplier Device Package $-$	Operating Pressure	200 PSI (1378.95 kPa)	
Accuracy ±0.25%  Voltage - Supply 5 V ~ 6 V  Port Size Male - 1/8" (3.18mm) NPT  Port Style Threaded  Features Amplified Output, Temperature Compensated  Termination Style -  Maximum Pressure 600 PSI (4136.85 kPa)  Operating Temperature -40°C ~ 125°C  Package / Case Cylinder, Metal  Supplier Device Package -	Output Type	Analog Voltage	
Voltage - Supply  5 V ~ 6 V  Port Size  Male - 1/8" (3.18mm) NPT  Port Style  Threaded  Features  Amplified Output, Temperature Compensated  Termination Style  -  Maximum Pressure  600 PSI (4136.85 kPa)  Operating Temperature  -40°C ~ 125°C  Package / Case  Cylinder, Metal  Supplier Device Package	Output	0.5 V ~ 4.5 V	
Port Size Male - 1/8" (3.18mm) NPT  Port Style Threaded  Features Amplified Output, Temperature Compensated  Termination Style -  Maximum Pressure 600 PSI (4136.85 kPa)  Operating Temperature -40°C ~ 125°C  Package / Case Cylinder, Metal  Supplier Device Package -	Accuracy	±0.25%	
Port Style Threaded Features Amplified Output, Temperature Compensated  Termination Style -  Maximum Pressure 600 PSI (4136.85 kPa)  Operating Temperature -40°C ~ 125°C  Package / Case Cylinder, Metal  Supplier Device Package -	Voltage - Supply	5 V ~ 6 V	
Features  Amplified Output, Temperature Compensated  Termination Style  - Maximum Pressure  600 PSI (4136.85 kPa)  Operating Temperature  -40°C ~ 125°C  Package / Case  Cylinder, Metal  Supplier Device Package  -	Port Size	Male - 1/8" (3.18mm) NPT	
Termination Style -  Maximum Pressure 600 PSI (4136.85 kPa)  Operating Temperature -40°C ~ 125°C  Package / Case Cylinder, Metal  Supplier Device Package -	Port Style	Threaded	
Maximum Pressure600 PSI (4136.85 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-	Features	Amplified Output, Temperature Compensated	
Operating Temperature -40°C ~ 125°C  Package / Case Cylinder, Metal  Supplier Device Package -	Termination Style	-	
Package / Case Cylinder, Metal Supplier Device Package -	Maximum Pressure	600 PSI (4136.85 kPa)	
Supplier Device Package -	Operating Temperature	-40°C ~ 125°C	
	Package / Case	Cylinder, Metal	
Report errors?	Supplier Device Package	-	
			Report errors?

#### MLH200PGB06A Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### MLH200PGB06A Payment Methods



















# MLH200PGB06A Shipping Methods













If you have any question about MLH200PGB06A, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com