



MLH250BSG17D Information

Heisener.com

Part Number MLH250BSG17D

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

Description MLH ALL METAL PRESS SENSE -ATF

Package Cylinder, Metal

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MLH250BSG17D Specifications

Manufacturer Part Number MLH250BSG17D Manufacturer Honeywell Sensing and Productivity Solutions Category Sensors, Transducers Package Cylinder, Metal Series MLH Pressure Type Sealed Gauge Operating Pressure 3625.94 PSI (25000 kPa) Output Type Analog Voltage Output 0.25 V ~ 10.25 V Accuracy ±0.25% Voltage - Supply 14 V ~ 30 V Port Size Male - 1/4" (6.35mm) BSP Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style - Maximum Pressure 7251.89 PSI (50000 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package - Report errors?		
CategorySensors, TransducersPackageCylinder, MetalSeriesMLHPressure TypeSealed GaugeOperating Pressure3625.94 PSI (25000 kPa)Output TypeAnalog VoltageOutput0.25 V ~ 10.25 VAccuracy±0.25%Voltage - Supply14 V ~ 30 VPort SizeMale - 1/4" (6.35mm) BSPPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination Style-Maximum Pressure7251.89 PSI (50000 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-	Manufacturer Part Number	MLH250BSG17D
Package Cylinder, Metal Series MLH Pressure Type Sealed Gauge Operating Pressure Onether Operating Pressure Operating Operating Operating Pressure Operating Pressure Operating Pressure Operating Pressure Operating Pressure Operating Pressure Operating Operating Pressure Operating Opera	Manufacturer	Honeywell Sensing and Productivity Solutions
PackageCylinder, MetalSeriesMLHPressure TypeSealed GaugeOperating Pressure3625.94 PSI (25000 kPa)Output TypeAnalog VoltageOutput0.25 V ~ 10.25 VAccuracy±0.25%Voltage - Supply14 V ~ 30 VPort SizeMale - 1/4" (6.35mm) BSPPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination Style-Maximum Pressure7251.89 PSI (50000 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-	Category	Sensors, Transducers
SeriesMLHPressure TypeSealed GaugeOperating Pressure3625.94 PSI (25000 kPa)Output TypeAnalog VoltageOutput0.25 V ~ 10.25 VAccuracy±0.25%Voltage - Supply14 V ~ 30 VPort SizeMale - 1/4" (6.35mm) BSPPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination Style-Maximum Pressure7251.89 PSI (50000 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-		Pressure Sensors, Transducers
Pressure Type Sealed Gauge Operating Pressure 3625.94 PSI (25000 kPa) Output Type Analog Voltage Output 0.25 V ~ 10.25 V Accuracy ±0.25% Voltage - Supply 14 V ~ 30 V Port Size Male - 1/4" (6.35mm) BSP Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style - Threaded Maximum Pressure 7251.89 PSI (50000 kPa) Operating Temperature - 40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package	Package	Cylinder, Metal
Operating Pressure Output Type Analog Voltage Output 0.25 V ~ 10.25 V Accuracy ±0.25% Voltage - Supply 14 V ~ 30 V Port Size Male - 1/4" (6.35mm) BSP Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Maximum Pressure 7251.89 PSI (50000 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Series	MLH
Output Type 0.25 V ~ 10.25 V Accuracy ±0.25% Voltage - Supply 14 V ~ 30 V Port Size Male - 1/4" (6.35mm) BSP Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style - T251.89 PSI (50000 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Pressure Type	Sealed Gauge
Output $0.25 \text{ V} \sim 10.25 \text{ V}$ Accuracy $\pm 0.25\%$ Voltage - Supply $14 \text{ V} \sim 30 \text{ V}$ Port Size $Male - 1/4$ " (6.35mm) BSP Port Style $Threaded$ Features $Amplified$ Output, Temperature Compensated Termination Style $-$ Maximum Pressure $7251.89 \text{ PSI} (50000 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case $Cylinder$, Metal Supplier Device Package $-$	Operating Pressure	3625.94 PSI (25000 kPa)
Accuracy ±0.25% Voltage - Supply 14 V ~ 30 V Port Size Male - 1/4" (6.35mm) BSP Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style - Maximum Pressure 7251.89 PSI (50000 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Output Type	Analog Voltage
Voltage - Supply Port Size Male - 1/4" (6.35mm) BSP Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style - Maximum Pressure 7251.89 PSI (50000 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package	Output	0.25 V ~ 10.25 V
Port Size Male - 1/4" (6.35mm) BSP Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style - Maximum Pressure 7251.89 PSI (50000 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Accuracy	$\pm 0.25\%$
Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style - Maximum Pressure 7251.89 PSI (50000 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Voltage - Supply	14 V ~ 30 V
Features Amplified Output, Temperature Compensated Termination Style - Maximum Pressure 7251.89 PSI (50000 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Port Size	Male - 1/4" (6.35mm) BSP
Termination Style - Maximum Pressure 7251.89 PSI (50000 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Port Style	Threaded
Maximum Pressure $7251.89 \text{ PSI } (50000 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / CaseCylinder, MetalSupplier Device Package-	Features	Amplified Output, Temperature Compensated
Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Termination Style	-
Package / Case Cylinder, Metal Supplier Device Package -	Maximum Pressure	7251.89 PSI (50000 kPa)
Supplier Device Package -	Operating Temperature	-40°C ~ 125°C
	Package / Case	Cylinder, Metal
Report errors?	Supplier Device Package	-
		Report errors?

MLH250BSG17D Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MLH250BSG17D Payment Methods



















MLH250BSG17D Shipping Methods













If you have any question about MLH250BSG17D, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com