



### **MLH350BSG14D Information**

Why specific com

For Reference Only

Part Number MLH350BSG14D

Manufacturer Honeywell Sensing and Productivity Solutions

**Category** Sensors, Transducers

Pressure Sensors, Transducers

**Description** SENSOR SEALED GAUGE 0-350 BAR

Package Cylinder, Metal

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **MLH350BSG14D Specifications**

Manufacturer Part Number       MLH350BSG14D         Manufacturer       Honeywell Sensing and Productivity Solutions         Category       Sensors, Transducers         Package       Cylinder, Metal         Series       MLH         Pressure Type       Sealed Gauge         Operating Pressure       5076.32 PSI (35000 kPa)         Output Type       Analog Voltage         Output       0.25 V ~ 10.25 V         Accuracy       ±0.25%         Voltage - Supply       14 V ~ 30 V         Port Size       Male - 1/4" (6.35mm) BSP         Port Style       Threaded         Features       Amplified Output, Temperature Compensated         Termination Style       DIN         Maximum Pressure       10152.64 PSI (70000 kPa)         Operating Temperature       -40°C ~ 125°C         Package / Case       Cylinder, Metal         Supplier Device Package       -         Report errors?		
CategorySensors, TransducersPackageCylinder, MetalSeriesMLHPressure TypeSealed GaugeOperating Pressure5076.32 PSI (35000 kPa)Output TypeAnalog VoltageOutput0.25 V ~ 10.25 VAccuracy±0.25%Voltage - Supply14 V ~ 30 VPort SizeMale - 1/4" (6.35mm) BSPPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleDINMaximum Pressure10152.64 PSI (70000 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-	Manufacturer Part Number	MLH350BSG14D
Package Cylinder, Metal Series MLH Pressure Type Sealed Gauge Operating Pressure Operating Pressure Output Type Analog Voltage Output O	Manufacturer	Honeywell Sensing and Productivity Solutions
PackageCylinder, MetalSeriesMLHPressure TypeSealed GaugeOperating Pressure5076.32 PSI (35000 kPa)Output TypeAnalog VoltageOutput0.25 V ~ 10.25 VAccuracy±0.25%Voltage - Supply14 V ~ 30 VPort SizeMale - 1/4" (6.35mm) BSPPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleDINMaximum Pressure10152.64 PSI (70000 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-	Category	Sensors, Transducers
SeriesMLHPressure TypeSealed GaugeOperating Pressure5076.32 PSI (35000 kPa)Output TypeAnalog VoltageOutput0.25 V ~ 10.25 VAccuracy±0.25%Voltage - Supply14 V ~ 30 VPort SizeMale - 1/4" (6.35mm) BSPPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleDINMaximum Pressure10152.64 PSI (70000 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-		Pressure Sensors, Transducers
Pressure TypeSealed GaugeOperating Pressure5076.32 PSI (35000 kPa)Output TypeAnalog VoltageOutput0.25 V ~ 10.25 VAccuracy±0.25%Voltage - Supply14 V ~ 30 VPort SizeMale - 1/4" (6.35mm) BSPPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleDINMaximum Pressure10152.64 PSI (70000 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-	Package	Cylinder, Metal
Operating Pressure $5076.32 \text{ PSI } (35000 \text{ kPa})$ Output TypeAnalog VoltageOutput $0.25 \text{ V} \sim 10.25 \text{ V}$ Accuracy $\pm 0.25\%$ Voltage - Supply $14 \text{ V} \sim 30 \text{ V}$ Port SizeMale - $1/4$ " ( $6.35\text{mm}$ ) BSPPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleDINMaximum Pressure $10152.64 \text{ PSI } (70000 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / CaseCylinder, MetalSupplier Device Package-	Series	MLH
Output TypeAnalog VoltageOutput $0.25 \text{ V} \sim 10.25 \text{ V}$ Accuracy $\pm 0.25\%$ Voltage - Supply $14 \text{ V} \sim 30 \text{ V}$ Port SizeMale - $1/4$ " ( $6.35 \text{mm}$ ) BSPPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleDINMaximum Pressure $10152.64 \text{ PSI } (70000 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / CaseCylinder, MetalSupplier Device Package-	Pressure Type	Sealed Gauge
Output $0.25 \text{ V} \sim 10.25 \text{ V}$ Accuracy $\pm 0.25\%$ Voltage - Supply $14 \text{ V} \sim 30 \text{ V}$ Port SizeMale - $1/4$ " ( $6.35\text{mm}$ ) BSPPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleDINMaximum Pressure $10152.64 \text{ PSI } (70000 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / CaseCylinder, MetalSupplier Device Package-	Operating Pressure	5076.32 PSI (35000 kPa)
Accuracy ±0.25%  Voltage - Supply 14 V ~ 30 V  Port Size Male - 1/4" (6.35mm) BSP  Port Style Threaded  Features Amplified Output, Temperature Compensated  Termination Style DIN  Maximum Pressure 10152.64 PSI (70000 kPa)  Operating Temperature -40°C ~ 125°C  Package / Case Cylinder, Metal  Supplier Device Package -	Output Type	Analog Voltage
Voltage - Supply  Port Size  Male - 1/4" (6.35mm) BSP  Port Style  Threaded  Features  Amplified Output, Temperature Compensated  Termination Style  DIN  Maximum Pressure  10152.64 PSI (70000 kPa)  Operating Temperature  -40°C ~ 125°C  Package / Case  Cylinder, Metal  Supplier Device Package	Output	0.25 V ~ 10.25 V
Port Size Male - 1/4" (6.35mm) BSP  Port Style Threaded  Features Amplified Output, Temperature Compensated  Termination Style DIN  Maximum Pressure 10152.64 PSI (70000 kPa)  Operating Temperature -40°C ~ 125°C  Package / Case Cylinder, Metal  Supplier Device Package -	Accuracy	±0.25%
Port Style Threaded  Features Amplified Output, Temperature Compensated  Termination Style DIN  Maximum Pressure 10152.64 PSI (70000 kPa)  Operating Temperature -40°C ~ 125°C  Package / Case Cylinder, Metal  Supplier Device Package -	Voltage - Supply	14 V ~ 30 V
Features Amplified Output, Temperature Compensated  Termination Style DIN  Maximum Pressure 10152.64 PSI (70000 kPa)  Operating Temperature -40°C ~ 125°C  Package / Case Cylinder, Metal  Supplier Device Package -	Port Size	Male - 1/4" (6.35mm) BSP
Termination Style DIN  Maximum Pressure 10152.64 PSI (70000 kPa)  Operating Temperature -40°C ~ 125°C  Package / Case Cylinder, Metal  Supplier Device Package -	Port Style	Threaded
Maximum Pressure10152.64 PSI (70000 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-	Features	Amplified Output, Temperature Compensated
Operating Temperature -40°C ~ 125°C  Package / Case Cylinder, Metal  Supplier Device Package -	Termination Style	DIN
Package / Case Cylinder, Metal Supplier Device Package -	Maximum Pressure	10152.64 PSI (70000 kPa)
Supplier Device Package -	Operating Temperature	-40°C ~ 125°C
	Package / Case	Cylinder, Metal
Report errors?	Supplier Device Package	-
		Report errors?

#### **MLH350BSG14D Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **MLH350BSG14D Payment Methods**



















### MLH350BSG14D Shipping Methods













If you have any question about MLH350BSG14D, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com