

MLP821M250EB0D

MLP821M250EB0D Information

Contraction the second	 MLP821M250EB0D Cornell Dubilier Electronics (CDE) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 820UF 20% 250V FLATPACK FlatPack, Tabbed For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MLP821M250EB0D Specifications

Manufacturer Part NumberMLP821M250EB0DManufacturerCornell Dubilier Electronics (CDE)CategoryCapacitorsAluminum Electrolytic CapacitorsPackageFlatPack, TabbedStriesMLPCapacitance820µFOlarace±20%Voltage - Rated50∨ESR (Equivalent Series Resistance)17 2mOhm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature90arApplicationsGeneral PurposeApple Current - High Frequency4.9A @ 20kHzImpedance.Lied Spacing3000" Lx 1.750" W (76.20mm x 44.45mm)Bighe Seated Must.500" (12.70mm)Surface Mount Land Size.Mounting TypeHadek, Tabbed		
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageFlatPack, TabbedSeriesMLPCapacitance\$20µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)172 mOhm @ 120HzDiperating Temperature-55°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency3.8A @ 120HzImpedance-Lead Spacing1.000" (25.40mm)Size / Dimension3.000" L x 1.750" W (76.20mm x 44.45mm)Height - Seated (Max)0.500" (12.70mm)Surface Mount Land Size-Polaring TypeChasis MountPackage / CaseFlatPack, Tabbed	Manufacturer Part Number	MLP821M250EB0D
Auminum Electrolytic CapacitorsPackageFlatPack, TabbedSeriesMLPCapacitance\$20µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)172 mOhm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature55°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency3.8A @ 120HzRipple Current - High Frequency4.9A @ 20kHzImpedance-Lead Spacing3.000° L x 1.750° W (76.20mm x 44.45mm)Size / Dimension0.500° (12.70mm)Surface Mount Land Size-Mounting TypeFlatPack, Tabbed	Manufacturer	Cornell Dubilier Electronics (CDE)
PackageFlatPack, TabbedSeriesMLPCapacitance820µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)172 mOhm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature2000 Hrs @ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency3.8A @ 120HzRipple Current - High Frequency1.000° (25.40mm)Size / Dimension3.000° L x 1.750° W (76.20mm x 44.45mm)Size / Dimension5.50° (12.70mm)Surface Mount Land Size-Mounting TypeFlatPack, Tabbed	Category	Capacitors
SeriesMLPCapacitance820µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)172 mOhm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-55°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.8A @ 120HzInpedance-Lead Spacing1.000° (25.40mm)Size / Dimension3.000° L x 1.750° W (76.20mm x 44.45mm)Surface Mount Land Size-Mounting TypeChasis MountPackage / CaseFalPack, Tabbed		Aluminum Electrolytic Capacitors
Capacitance820µFTolerance±20%Voltage Rated550VESR (Equivalent Series Resistance)172 mOhm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature>65°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency4.9A @ 20kHzImpedance.Lead Spacing1.000" (25.40mm)Size / Dimension3.000" L x 1.750" W (76.20mm x 44.45mm)Surface Mount Land Size.Mounting TypeChasis MountPackage / CaseFatPack, Tabbed	Package	FlatPack, Tabbed
Tolerance±0%Voltage - Rated250VESR (Equivalent Series Resistance)172 mOhm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-55°C ~ 85°CPolarzationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.8A @ 120HzImpedance-Lead Spacing1.000" (25.40mm)Size / Dimension0.500" (12.70mm) x 44.45mm)Height - Seated (Max)0.500" (12.70mm)Surface Mount Land Size-Mounting TypeChasis MountPackage / CaseFlatPack, Tabbed	Series	MLP
Voltage - Rated250VESR (Equivalent Series Resistance)172 mOhm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-55°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.8A @ 120HzRipple Current - High Frequency4.9A @ 20kHzImpedance-Lead Spacing1.000" (25.40mm)Size / Dimension0.500" (12.70mm) ¥ 44.45mm)Bight - Seated (Max)0.500" (12.70mm)Surface Mount Land Size-Mounting TypeChasis MountPackage / CaseFlatPack, Tabbed	Capacitance	820µF
ESR (Equivalent Series Resistance) 172 mOhm @ 120Hz ESR (Equivalent Series Resistance) 2000 Hrs @ 85°C Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -55°C ~ 85°C Polar Polar Applications General Purpose Ripple Current - Low Frequency 3.8A @ 120Hz Impedance - Lead Spacing 1.000" (25.40mm) Size / Dimension 3.000" L x 1.750" W (76.20mm x 44.45mm) Height - Seated (Max) 0.500" (12.70mm) Surface Mount Land Size - Mounting Type FlatPack, Tabbed	Tolerance	±20%
Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-55°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.8A @ 120HzMipedance-Lead Spacing1.000" (25.40mm)Size / Dimension3.000" L x 1.750" W (76.20mm x 44.45mm)Surface Mount Land Size-Mounting TypeChasis MountPackage / CaseFlatPack, Tabbed	Voltage - Rated	250V
Operating Temperature-55°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.8A @ 120HzRipple Current - High Frequency4.9A @ 20kHzImpedance-Lead Spacing1.000° (25.40mm)Size / Dimension3.000° L x 1.750° W (76.20mm x 44.45mm)Height - Seated (Max)0.500° (12.70mm)Surface Mount Land Size-Hounting TypeFlatPack, Tabbed	ESR (Equivalent Series Resistance)	172 mOhm @ 120Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.8A @ 120HzRipple Current - High Frequency4.9A @ 20kHzImpedance-Lead Spacing1.000" (25.40mm)Size / Dimension3.000" L x 1.750" W (76.20mm x 44.45mm)Height - Seated (Max)0.500" (12.70mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseFlatPack, Tabbed	Lifetime @ Temp.	2000 Hrs @ 85°C
Applications General Purpose Ripple Current - Low Frequency 3.8A @ 120Hz Ripple Current - High Frequency 4.9A @ 20kHz Impedance - Lead Spacing 1.000" (25.40mm) Size / Dimension 3.000" L x 1.750" W (76.20mm x 44.45mm) Height - Seated (Max) 0.500" (12.70mm) Surface Mount Land Size - Mounting Type Chasis Mount Package / Case FlatPack, Tabbed	Operating Temperature	-55°C ~ 85°C
Ripple Current - Low Frequency3.8A @ 120HzRipple Current - High Frequency4.9A @ 20kHzImpedance-Lead Spacing1.000" (25.40mm)Size / Dimension3.000" L x 1.750" W (76.20mm x 44.45mm)Height - Seated (Max)0.500" (12.70mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseFlatPack, Tabbed	Polarization	Polar
Ripple Current - High Frequency4.9A @ 20kHzImpedance-Lead Spacing1.000" (25.40mm)Size / Dimension3.000" L x 1.750" W (76.20mm x 44.45mm)Height - Seated (Max)0.500" (12.70mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseFlatPack, Tabbed	Applications	General Purpose
In reserveImpedance-Lead Spacing1.000" (25.40mm)Size / Dimension3.000" L x 1.750" W (76.20mm x 44.45mm)Height - Seated (Max)0.500" (12.70mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseFlatPack, Tabbed	Ripple Current - Low Frequency	3.8A @ 120Hz
Lead Spacing 1.000" (25.40mm) Size / Dimension 3.000" L x 1.750" W (76.20mm x 44.45mm) Height - Seated (Max) 0.500" (12.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case FlatPack, Tabbed	Ripple Current - High Frequency	4.9A @ 20kHz
Size / Dimension3.000" L x 1.750" W (76.20mm x 44.45mm)Height - Seated (Max)0.500" (12.70mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseFlatPack, Tabbed	Impedance	-
Height - Seated (Max)0.500" (12.70mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseFlatPack, Tabbed	Lead Spacing	1.000" (25.40mm)
Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseFlatPack, Tabbed	Size / Dimension	3.000" L x 1.750" W (76.20mm x 44.45mm)
Mounting TypeChassis MountPackage / CaseFlatPack, Tabbed	Height - Seated (Max)	0.500" (12.70mm)
Package / Case FlatPack, Tabbed	Surface Mount Land Size	-
	Mounting Type	Chassis Mount
Report errors?	Package / Case	FlatPack, Tabbed
		Report errors?

MLP821M250EB0D Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

MLP821M250EB0D Payment Methods



MLP821M250EB0D Shipping Methods



If you have any question about MLP821M250EB0D, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com