

# MLSG721M200EB1C

## MLSG721M200EB1C Information

Heisener.com	 MLSG721M200EB1C Cornell Dubilier Electronics (CDE) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 720UF 20% 200V FLATPACK FlatPack For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# MLSG721M200EB1C Specifications

Manufacturer   Cornell Dubilier Electronics (CDE)     Category   Capacitors     Aluminum Electrolytic Capacitors   Aluminum Electrolytic Capacitors     Package   FlatPack     Scries   MLSG Flatpack     Capacitance   720µF     Tolerance   ±20%     Voltage - Rated   200V     ESR (Equivalent Series Resistance)   -     Lifetime @ Temp.   5000 Hrs @ 125°C     Operating Temperature   -55°C ~ 125°C     Polarization   General Purpose     Applications   General Purpose     Ripple Current - Low Frequency   -     Impedance   -     Lead Spacing   1.000" (25.40mm)     Size / Dimension   3.000" L x 1.750" W (76.20mm x 44.45mm)     Height - Seated (Max)   0.500" (12.70mm)     Surface Mount Land Size   -     Mounting Type   Through Hole		
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageFlatPackPackageFlatPackSeriesMLSG FlatpackCapacitance720μFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 125°COperating Temperature-55°C ~ 125°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance-Lead Spacing1.000" (25.40mm)Size / Dimension3.000" L x 1.750" W (76.20mm x 44.45mm)Height - Seated (Max)0.500" (12.70mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseFlatPack	Manufacturer Part Number	MLSG721M200EB1C
Auminum Electrolytic CapacitorsPackageFlatPackSeriesMLSG FlatpackCapacitance720µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 125°COperating Temperature5000 Hrs @ 125°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency-Lingedance1.000° (25.40mm)Size / Dimension3.000° L x 1.750° W (76.20mm x 44.45mm)Size / Dimension0.500° (12.70mm)Surface Mount Land Size-Package / CaseFlatPack	Manufacturer	Cornell Dubilier Electronics (CDE)
PackageFlatPackSeriesMLSG FlatpackCapacitance720µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 125°COperating Temperature5000 Hrs @ 125°CPolarization6eneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance-Lided Spacing3.000° L x 1.750° W (76.20mm x 44.45mm)Size / Dimension0.500° (12.70mm)Straface Mount Land Size-Mounting TypeFlatPackPackage / CaseFlatPack	Category	Capacitors
Series   MLSG Flatpack     Capacitance   720µF     Tolerance   ±20%     Voltage - Rated   200V     ESR (Equivalent Series Resistance)   -     Lifetime @ Temp.   5000 Hrs @ 125°C     Operating Temperature   -55°C ~ 125°C     Polarization   Polar     Applications   General Purpose     Ripple Current - Low Frequency   -     Impedance   1.000° (25.40mm)     Size / Dimension   3.000° L x 1.750° W (76.20mm x 44.45mm)     Height - Seated (Max)   -     Surface Mount Land Size   -     Mounting Type   FlatPack     Package / Case   FlatPack		Aluminum Electrolytic Capacitors
Capacitance720µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 125°COperating Temperature-55°C ~ 125°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance-Lead Spacing1.000" (25.40mm)Size / Dimension3.000" L x 1.750" W (76.20mm x 44.45mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeFlatPackPackage / CaseFlatPack	Package	FlatPack
Tolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 125°COperating Temperature-55°C ~ 125°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low FrequencyImpedance-Lead Spacing1.000" (25.40mm)Size / Dimension0.500" L x 1.750" W (76.20mm x 44.45mm)Height - Seated (Max)0.500" (12.70mm)Surface Mount Land Size-Pokage / CaseFlatPackPokage / CaseFlatPack	Series	MLSG Flatpack
Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 125°COperating Temperature-55°C ~ 125°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency-Lead Spacing1.000" (25.40mm)Size / Dimension3.000" L x 1.750" W (76.20mm x 44.45mm)Size / Dimension0.500" (12.70mm)Height - Seated (Max)-Mounting TypeFlatPackPackage / CaseFlatPack	Capacitance	720µF
ESR   -     ESR (Equivalent Series Resistance)   -     ESR (Equivalent Series Resistance)   5000 Hrs @ 125°C     Doperating Temperature   -55°C ~ 125°C     Polar   Polar     Applications   General Purpose     Ripple Current - Low Frequency   -     Mippedance   -     Lead Spacing   1.000" (25.40mm)     Size / Dimension   3.000" L x 1.750" W (76.20mm x 44.45mm)     Height - Seated (Max)   0.500" (12.70mm)     Surface Mount Land Size   -     Mounting Type   FlatPack	Tolerance	±20%
Lifetime @ Temp.5000 Hrs @ 125°COperating Temperature-55°C ~ 125°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing1.000" (25.40mm)Size / Dimension3.000" L x 1.750" W (76.20mm x 44.45mm)Height - Seated (Max)0.500" (12.70mm)Surface Mount Land Size-Mounting TypeFlatPackPackage / CaseFlatPack	Voltage - Rated	200V
Operating Temperature-55°C ~ 125°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing1.000" (25.40mm)Size / Dimension3.000" L x 1.750" W (76.20mm x 44.45mm)Height - Seated (Max)0.500" (12.70mm)Surface Mount Land Size-Mounting TypeFlatPackPackage / CaseFlatPack	ESR (Equivalent Series Resistance)	-
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing1.000" (25.40mm)Size / Dimension3.000" L x 1.750" W (76.20mm x 44.45mm)Height - Seated (Max)0.500" (12.70mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseFlatPack	Lifetime @ Temp.	5000 Hrs @ 125°C
ApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing1.000" (25.40mm)Size / Dimension3.000" L x 1.750" W (76.20mm x 44.45mm)Height - Seated (Max)0.500" (12.70mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseFlatPack	Operating Temperature	-55°C ~ 125°C
Ripple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing1.000" (25.40mm)Size / Dimension3.000" L x 1.750" W (76.20mm x 44.45mm)Height - Seated (Max)0.500" (12.70mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseFlatPack	Polarization	Polar
Ripple Current - High Frequency -   Impedance -   Lead Spacing 1.000" (25.40mm)   Size / Dimension 3.000" L x 1.750" W (76.20mm x 44.45mm)   Height - Seated (Max) 0.500" (12.70mm)   Surface Mount Land Size -   Mounting Type Through Hole   Package / Case FlatPack	Applications	General Purpose
Impedance-Lead Spacing1.000" (25.40mm)Size / Dimension3.000" L x 1.750" W (76.20mm x 44.45mm)Height - Seated (Max)0.500" (12.70mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseFlatPack	Ripple Current - Low Frequency	-
Lead Spacing 1.000" (25.40mm)   Size / Dimension 3.000" L x 1.750" W (76.20mm x 44.45mm)   Height - Seated (Max) 0.500" (12.70mm)   Surface Mount Land Size -   Mounting Type Through Hole   Package / Case FlatPack	Ripple Current - High Frequency	-
Size / Dimension3.000" L x 1.750" W (76.20mm x 44.45mm)Height - Seated (Max)0.500" (12.70mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseFlatPack	Impedance	-
Height - Seated (Max)0.500" (12.70mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseFlatPack	Lead Spacing	1.000" (25.40mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseFlatPack	Size / Dimension	3.000" L x 1.750" W (76.20mm x 44.45mm)
Mounting TypeThrough HolePackage / CaseFlatPack	Height - Seated (Max)	0.500" (12.70mm)
Package / Case FlatPack	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	FlatPack
		Report errors?

### MLSG721M200EB1C Guarantees



**Quality Guarantees** 

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

### MLSG721M200EB1C Payment Methods





If you have any question about MLSG721M200EB1C, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com