



MM2 AC100/(110) Information

Heisener.com

Part Number MM2 AC100/(110)

Manufacturer Omron Automation and Safety

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPDT 15A 110V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com





Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MM2 AC100/(110) Specifications

Manufacturer Part Number MM2 AC100/(110) Manufacturer Omron Automation and Safety Category Relays Package - Series MM Relay Type General Purpose Coil Type Non Latching Coil Current 39mA Coil Voltage 110VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 15A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) 33 VAC Operate Time 25ms Release Time 30ms Features - Mounting Type Chassis Mount Termination Style Solder Lug		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesMMRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current39mACoil Voltage110VACContact FormDPDT (2 Form C)Contact Rating (Current)15ASwitching Voltage250VAC, 250VDC - MaxTurn On Voltage (Max)88 VACTurn Off Voltage (Min)33 VACOperate Time25msRelease Time30msFeatures-Mounting TypeChassis MountTermination StyleSolder Lug	Manufacturer Part Number	MM2 AC100/(110)
Package-SeriesMMRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current39mACoil Voltage110VACContact FormDPDT (2 Form C)Contact Rating (Current)15ASwitching Voltage250VAC, 250VDC - MaxTurn On Voltage (Max)88 VACTurn Off Voltage (Min)33 VACOperate Time25msRelease Time30msFeatures-Mounting TypeChassis MountTermination StyleSolder Lug	Manufacturer	Omron Automation and Safety
Package - Series MM Relay Type General Purpose Coil Type Non Latching Coil Current 39mA Coil Voltage 110VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 15A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) 33 VAC Operate Time 25ms Release Time 30ms Features - Mounting Type Chassis Mount Termination Style Solder Lug	Category	Relays
SeriesMMRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current39mACoil Voltage110VACContact FormDPDT (2 Form C)Contact Rating (Current)15ASwitching Voltage250VAC, 250VDC - MaxTurn On Voltage (Max)88 VACTurn Off Voltage (Min)33 VACOperate Time25msRelease Time30msFeatures-Mounting TypeChassis MountTermination StyleSolder Lug		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 39mA Coil Voltage 110VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 15A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) 33 VAC Operate Time 25ms Release Time 30ms Features - Mounting Type Chassis Mount Termination Style Solder Lug	Package	-
Coil TypeNon LatchingCoil Current39mACoil Voltage110VACContact FormDPDT (2 Form C)Contact Rating (Current)15ASwitching Voltage250VAC, 250VDC - MaxTurn On Voltage (Max)88 VACTurn Off Voltage (Min)33 VACOperate Time25msRelease Time30msFeatures-Mounting TypeChassis MountTermination StyleSolder Lug	Series	MM
Coil Current39mACoil Voltage110VACContact FormDPDT (2 Form C)Contact Rating (Current)15ASwitching Voltage250VAC, 250VDC - MaxTurn On Voltage (Max)88 VACTurn Off Voltage (Min)33 VACOperate Time25msRelease Time30msFeatures-Mounting TypeChassis MountTermination StyleSolder Lug	Relay Type	General Purpose
Coil Voltage 110VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 15A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) 33 VAC Operate Time 25ms Release Time 30ms Features - Mounting Type Chassis Mount Termination Style Solder Lug	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) 15A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) 33 VAC Operate Time 25ms Release Time 30ms Features - Mounting Type Chassis Mount Termination Style	Coil Current	39mA
Contact Rating (Current) Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) 33 VAC Operate Time 25ms Release Time 30ms Features - Mounting Type Chassis Mount Termination Style 15A 250VAC, 250VDC - Max 88 VAC - 100 100 100 100 100 100 100	Coil Voltage	110VAC
Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) 33 VAC Operate Time 25ms Release Time 30ms Features - Mounting Type Chassis Mount Termination Style Solder Lug	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 25ms Release Time 30ms Features - Mounting Type Chassis Mount Termination Style 88 VAC 33 VAC 25ms Chassis Mount Solder Lug	Contact Rating (Current)	15A
Turn Off Voltage (Min) Operate Time 25ms Release Time 30ms Features - Mounting Type Chassis Mount Termination Style Solder Lug	Switching Voltage	250VAC, 250VDC - Max
Operate Time 25ms Release Time 30ms Features - Mounting Type Chassis Mount Termination Style Solder Lug	Turn On Voltage (Max)	88 VAC
Release Time 30ms Features - Mounting Type Chassis Mount Termination Style Solder Lug	Turn Off Voltage (Min)	33 VAC
Features - Chassis Mount Termination Style Solder Lug	Operate Time	25ms
Mounting Type Chassis Mount Termination Style Solder Lug	Release Time	30ms
Termination Style Solder Lug	Features	-
	Mounting Type	Chassis Mount
Report errors?	Termination Style	Solder Lug
		Report errors?

MM2 AC100/(110) Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MM2 AC100/(110) Payment Methods





















MM2 AC100/(110) Shipping Methods













If you have any question about MM2 AC100/(110), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com