



MM2KB AC100/(110) Information

Heisener.com

Part Number MM2KB AC100/(110)

Manufacturer Omron Automation and Safety

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPDT 10A 110V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MM2KB AC100/(110) Specifications

Manufacturer Part NumberMM2KB AC100/(110)ManufacturerOmron Automation and SafetyCategoryRelaysPackage-SeriesMMKRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current39mACoil Voltage110VACContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 250VDC - MaxTurn On Voltage (Max)88 VACTurn Off Voltage (Min)-Operate Time30msRelease Time30msFeatures-Mounting TypeChassis Mount		
CategoryRelaysPackage-SeriesMMKRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current39mACoil Voltage110VACContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 250VDC - MaxTurn On Voltage (Max)88 VACTurn Off Voltage (Min)-Operate Time30msRelease Time30msFeatures-Mounting TypeChassis Mount	Manufacturer Part Number	MM2KB AC100/(110)
Package - Series MMK Relay Type General Purpose Coil Type Latching, Dual Coil Coil Current 39mA Coil Voltage 110VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) - Operate Time 30ms Release Time 30ms Features - Mounting Type Chassis Mount	Manufacturer	Omron Automation and Safety
Package-SeriesMMKRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current39mACoil Voltage110VACContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 250VDC - MaxTurn On Voltage (Max)88 VACTurn Off Voltage (Min)-Operate Time30msRelease Time30msFeatures-Mounting TypeChassis Mount	Category	Relays
SeriesMMKRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current39mACoil Voltage110VACContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 250VDC - MaxTurn On Voltage (Max)88 VACTurn Off Voltage (Min)-Operate Time30msRelease Time30msFeatures-Mounting TypeChassis Mount		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Latching, Dual Coil Coil Current 39mA Coil Voltage 110VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) - Operate Time 30ms Release Time 30ms Release Time 30ms Features - Mounting Type Chassis Mount	Package	-
Coil Type Latching, Dual Coil Coil Current 39mA Coil Voltage 110VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) - Operate Time 30ms Release Time 30ms Release Time 30ms Features - Mounting Type Chassis Mount	Series	MMK
Coil Current39mACoil Voltage110VACContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 250VDC - MaxTurn On Voltage (Max)88 VACTurn Off Voltage (Min)-Operate Time30msRelease Time30msFeatures-Mounting TypeChassis Mount	Relay Type	General Purpose
Coil Voltage 110VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) - Operate Time 30ms Release Time 30ms Features - Mounting Type Chassis Mount	Coil Type	Latching, Dual Coil
Contact Form C) Contact Rating (Current) Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) Operate Time 30ms Release Time 30ms Features - Mounting Type Chassis Mount	Coil Current	39mA
Contact Rating (Current) Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) Operate Time 30ms Release Time 30ms Features - Mounting Type Chassis Mount	Coil Voltage	110VAC
Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) - Operate Time 30ms Release Time 30ms Features - Mounting Type Chassis Mount	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 30ms Release Time 30ms Features - Mounting Type Chassis Mount	Contact Rating (Current)	10A
Turn Off Voltage (Min) Operate Time 30ms Release Time 30ms Features - Mounting Type Chassis Mount	Switching Voltage	250VAC, 250VDC - Max
Operate Time 30ms Release Time 30ms Features - Mounting Type Chassis Mount	Turn On Voltage (Max)	88 VAC
Release Time 30ms Features - Mounting Type Chassis Mount	Turn Off Voltage (Min)	-
Features - Chassis Mount Mounting Type Chassis Mount	Operate Time	30ms
Mounting Type Chassis Mount	Release Time	30ms
	Features	-
	Mounting Type	Chassis Mount
Termination Style Screw Terminal	Termination Style	Screw Terminal
Report errors?		Report errors?

MM2KB AC100/(110) Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MM2KB AC100/(110) Payment Methods



















MM2KB AC100/(110) Shipping Methods













If you have any question about MM2KB AC100/(110), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com