



### **MM4XP-JD DC125 Information**

Heisener.com

Part Number MM4XP-JD DC125

Manufacturer Omron Automation and Safety

Category Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE 4PDT 7A 125V

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **MM4XP-JD DC125 Specifications**

Manufacturer       MM4XP-JD DC125         Manufacturer       Omron Automation and Safety         Category       Relays         Power Relays, Over 2 Amps         Package       -         Series       MM         Relay Type       General Purpose         Coil Type       Non Latching         Coil Current       21.6mA         Coil Voltage       125VDC         Contact Form       4PDT (4 Form C)         Contact Rating (Current)       7A         Switching Voltage       250VAC, 250VDC - Max         Turn On Voltage (Max)       87.5 VDC         Turn Off Voltage (Min)       12.5 VDC         Operate Time       50ms         Release Time       30ms         Features       -         Mounting Type       Socketable         Termination Style       Plug In, 14 Pin		
Category Relays Power Relays, Over 2 Amps  Package - Series MM Relay Type General Purpose Coil Type Non Latching Coil Current 21.6mA Coil Voltage 125 VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 7A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) 12.5 VDC  Operate Time 50ms Release Time 30ms Features - Mounting Type Socketable Termination Style Plug In, 14 Pin	Manufacturer Part Number	MM4XP-JD DC125
Package-SeriesMMRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current21.6mACoil Voltage125VDCContact Form4PDT (4 Form C)Contact Rating (Current)7ASwitching Voltage250VAC, 250VDC - MaxTurn On Voltage (Max)87.5 VDCTurn Off Voltage (Min)12.5 VDCOperate Time50msRelease Time30msFeatures-Mounting TypeSocketableTermination StylePlug In, 14 Pin	Manufacturer	Omron Automation and Safety
Package         -           Series         MM           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         21.6mA           Coil Voltage         125VDC           Contact Form         4PDT (4 Form C)           Contact Rating (Current)         7A           Switching Voltage         250VAC, 250VDC - Max           Turn On Voltage (Max)         87.5 VDC           Turn Off Voltage (Min)         12.5 VDC           Operate Time         50ms           Release Time         30ms           Features         -           Mounting Type         Socketable           Termination Style         Plug In, 14 Pin	Category	Relays
SeriesMMRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current21.6mACoil Voltage125 VDCContact Form4PDT (4 Form C)Contact Rating (Current)7ASwitching Voltage250 VAC, 250 VDC - MaxTurn On Voltage (Max)87.5 VDCTurn Off Voltage (Min)12.5 VDCOperate Time50msRelease Time30msFeatures-Mounting TypeSocketableTermination StylePlug In, 14 Pin		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 21.6mA Coil Voltage 125VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 7A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 87.5 VDC Turn Off Voltage (Min) 12.5 VDC Operate Time 50ms Release Time 50ms Release Time 30ms Features - Mounting Type Socketable Termination Style Plug In, 14 Pin	Package	-
Coil TypeNon LatchingCoil Current21.6mACoil Voltage125VDCContact Form4PDT (4 Form C)Contact Rating (Current)7ASwitching Voltage250VAC, 250VDC - MaxTurn On Voltage (Max)87.5 VDCTurn Off Voltage (Min)12.5 VDCOperate Time50msRelease Time30msFeatures-Mounting TypeSocketableTermination StylePlug In, 14 Pin	Series	MM
Coil Current Coil Voltage 125VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 7A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 87.5 VDC Turn Off Voltage (Min) 12.5 VDC Operate Time 50ms Release Time 30ms Features - Mounting Type Socketable Termination Style Plug In, 14 Pin	Relay Type	General Purpose
Coil Voltage 125VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 7A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 87.5 VDC Turn Off Voltage (Min) 12.5 VDC Operate Time 50ms Release Time 30ms Features - Mounting Type Socketable Termination Style Plug In, 14 Pin	Coil Type	Non Latching
Contact Form 4PDT (4 Form C)  Contact Rating (Current) 7A  Switching Voltage 250VAC, 250VDC - Max  Turn On Voltage (Max) 87.5 VDC  Turn Off Voltage (Min) 12.5 VDC  Operate Time 50ms  Release Time 30ms  Features - Mounting Type Socketable  Termination Style Plug In, 14 Pin	Coil Current	21.6mA
Contact Rating (Current)  Switching Voltage  250VAC, 250VDC - Max  Turn On Voltage (Max)  87.5 VDC  Turn Off Voltage (Min)  12.5 VDC  Operate Time  50ms  Release Time  30ms  Features  -  Mounting Type  Socketable  Termination Style  Plug In, 14 Pin	Coil Voltage	125VDC
Switching Voltage 250VAC, 250VDC - Max  Turn On Voltage (Max) 87.5 VDC  Turn Off Voltage (Min) 12.5 VDC  Operate Time 50ms  Release Time 30ms  Features -  Mounting Type Socketable  Termination Style Plug In, 14 Pin	Contact Form	4PDT (4 Form C)
Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  50ms  Release Time  30ms  Features  - Mounting Type  Socketable  Termination Style  87.5 VDC  50ms  50ms  Found  Fou	Contact Rating (Current)	7A
Turn Off Voltage (Min)  Operate Time  50ms  Release Time  30ms  Features  - Mounting Type  Socketable  Termination Style  12.5 VDC  50ms  Soms  Features  Plug In, 14 Pin	Switching Voltage	250VAC, 250VDC - Max
Operate Time 50ms Release Time 30ms Features - Mounting Type Socketable Termination Style Plug In, 14 Pin	Turn On Voltage (Max)	87.5 VDC
Release Time 30ms  Features - Mounting Type Socketable  Termination Style Plug In, 14 Pin	Turn Off Voltage (Min)	12.5 VDC
Features - Mounting Type Socketable Termination Style Plug In, 14 Pin	Operate Time	50ms
Mounting Type Socketable Termination Style Plug In, 14 Pin	Release Time	30ms
Termination Style Plug In, 14 Pin	Features	-
	Mounting Type	Socketable
Poport arrors?	Termination Style	Plug In, 14 Pin
Report errors?		Report errors?

#### **MM4XP-JD DC125 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **MM4XP-JD DC125 Payment Methods**



















## MM4XP-JD DC125 Shipping Methods













If you have any question about MM4XP-JD DC125, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com