



Heisener.com

## MM4XPN AC200/(220) Information

Part Number MM4XPN AC200/(220)

Manufacturer Omron Automation and Safety

Category Relays

Power Relays, Over 2 Amps

RELAY GEN PURPOSE 4PDT 7A 220V **Description** 

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## MM4XPN AC200/(220) Specifications

Manufacturer Part Number  Manufacturer  Omron Automation and Safety  Relays  Power Relays, Over 2 Amps  Package  - Series  MM  Relay Type  General Purpose  Coil Type  Non Latching  Coil Current  25.5mA  Coil Voltage  220VAC  Contact Form  4PDT (4 Form C)  Contact Rating (Current)  7A  Switching Voltage  250VAC, 250VDC - Max  Turn On Voltage (Max)  Turn Off Voltage (Min)  66 VAC  Operate Time  25ms  Release Time  30ms  Features  Neon Indicator  Mounting Type  Socketable  Plug In, 14 Pin  Report errors?		
CategoryRelaysPackage-SeriesMMRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current25.5mACoil Voltage220VACContact Form4PDT (4 Form C)Contact Rating (Current)7ASwitching Voltage250VAC, 250VDC - MaxTurn On Voltage (Max)176 VACTurn Off Voltage (Min)66 VACOperate Time25msRelease Time30msFeaturesNeon IndicatorMounting TypeSocketableTermination StylePlug In, 14 Pin	Manufacturer Part Number	MM4XPN AC200/(220)
Package - Series MM Relay Type General Purpose Coil Type Non Latching Coil Current 25.5mA Coil Voltage 220VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 7A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 176 VAC Turn Off Voltage (Min) 66 VAC Operate Time 25ms Release Time 30ms Features Neon Indicator Mounting Type Socketable Termination Style Purpose	Manufacturer	Omron Automation and Safety
Package-SeriesMMRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current25.5mACoil Voltage220VACContact Form4PDT (4 Form C)Contact Rating (Current)7ASwitching Voltage250VAC, 250VDC - MaxTurn On Voltage (Max)176 VACTurn Off Voltage (Min)66 VACOperate Time25msRelease Time30msFeaturesNeon IndicatorMounting TypeSocketableTermination StylePlug In, 14 Pin	Category	Relays
SeriesMMRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current25.5mACoil Voltage220VACContact Form4PDT (4 Form C)Contact Rating (Current)7ASwitching Voltage250VAC, 250VDC - MaxTurn On Voltage (Max)176 VACTurn Off Voltage (Min)66 VACOperate Time25msRelease Time30msFeaturesNeon IndicatorMounting TypeSocketableTermination StylePlug In, 14 Pin		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 25.5mA Coil Voltage 220VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 7A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 176 VAC Turn Off Voltage (Min) 66 VAC Operate Time 25ms Release Time 30ms Features Neon Indicator Mounting Type Socketable Termination Style Plug In, 14 Pin	Package	-
Coil TypeNon LatchingCoil Current25.5mACoil Voltage220VACContact Form4PDT (4 Form C)Contact Rating (Current)7ASwitching Voltage250VAC, 250VDC - MaxTurn On Voltage (Max)176 VACTurn Off Voltage (Min)66 VACOperate Time25msRelease Time30msFeaturesNeon IndicatorMounting TypeSocketableTermination StylePlug In, 14 Pin	Series	MM
Coil Current         25.5mA           Coil Voltage         220VAC           Contact Form         4PDT (4 Form C)           Contact Rating (Current)         7A           Switching Voltage         250VAC, 250VDC - Max           Turn On Voltage (Max)         176 VAC           Turn Off Voltage (Min)         66 VAC           Operate Time         25ms           Release Time         30ms           Features         Neon Indicator           Mounting Type         Socketable           Termination Style         Plug In, 14 Pin	Relay Type	General Purpose
Coil Voltage 220VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 7A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 176 VAC Turn Off Voltage (Min) 66 VAC Operate Time 25ms Release Time 30ms Features Neon Indicator Mounting Type Socketable Termination Style Plug In, 14 Pin	Coil Type	Non Latching
Contact Form 4PDT (4 Form C)  Contact Rating (Current) 7A  Switching Voltage 250VAC, 250VDC - Max  Turn On Voltage (Max) 176 VAC  Turn Off Voltage (Min) 66 VAC  Operate Time 25ms  Release Time 30ms  Features Neon Indicator  Mounting Type Socketable  Termination Style Plug In, 14 Pin	Coil Current	25.5mA
Contact Rating (Current)  Switching Voltage  250VAC, 250VDC - Max  Turn On Voltage (Max)  176 VAC  Turn Off Voltage (Min)  66 VAC  Operate Time  25ms  Release Time  30ms  Features  Neon Indicator  Mounting Type  Socketable  Termination Style  Plug In, 14 Pin	Coil Voltage	220VAC
Switching Voltage 250VAC, 250VDC - Max  Turn On Voltage (Max) 176 VAC  Turn Off Voltage (Min) 66 VAC  Operate Time 25ms  Release Time 30ms  Features Neon Indicator  Mounting Type Socketable  Termination Style Plug In, 14 Pin	Contact Form	4PDT (4 Form C)
Turn On Voltage (Max)  176 VAC  Turn Off Voltage (Min)  66 VAC  Operate Time  25ms  Release Time  30ms  Features  Neon Indicator  Mounting Type  Socketable  Termination Style  176 VAC	Contact Rating (Current)	7A
Turn Off Voltage (Min)  Operate Time  25ms  Release Time  30ms  Features  Neon Indicator  Mounting Type  Socketable  Termination Style  Plug In, 14 Pin	Switching Voltage	250VAC, 250VDC - Max
Operate Time 25ms Release Time 30ms Features Neon Indicator Mounting Type Socketable Termination Style Plug In, 14 Pin	Turn On Voltage (Max)	176 VAC
Release Time 30ms Features Neon Indicator Mounting Type Socketable Termination Style Plug In, 14 Pin	Turn Off Voltage (Min)	66 VAC
Features Neon Indicator  Mounting Type Socketable  Termination Style Plug In, 14 Pin	Operate Time	25ms
Mounting Type Socketable Termination Style Plug In, 14 Pin	Release Time	30ms
Termination Style Plug In, 14 Pin	Features	Neon Indicator
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In, 14 Pin
		Report errors?

## MM4XPN AC200/(220) Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### MM4XPN AC200/(220) Payment Methods



















## MM4XPN AC200/(220) Shipping Methods













If you have any question about MM4XPN AC200/(220), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com