

MM74HC00MTCX

MM74HC00MTCX Information



For Reference Only

Part Number MM74HC00MTCX

Manufacturer Fairchild/ON Semiconductor

Category Integrated Circuits (ICs)
Logic - Gates and Inverters

Description IC GATE NAND 4CH 2-INP 14-TSSOP **Package** 14-TSSOP (0.173", 4.40mm Width)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MM74HC00MTCX Specifications

Manufacturer Part Number MM74HC00MTCX Manufacturer Fairchild/ON Semiconductor Category Integrated Circuits (ICs) Logic - Gates and Inverters Package 14-TSSOP (0.173", 4.40mm Width) Series 74HC Logic Type NAND Gate Number of Circuits 4 Number of Inputs 2 Features - Voltage - Supply 2 V ~ 6 V Current - Quiescent (Max) 2µA Current - Output High, Low 5.2mA, 5.2mA Logic Level - Low 0.5 V ~ 1.8 V Logic Level - High 1.5 V ~ 4.2 V Max Propagation Delay @ V, Max CL 15ns @ 6V, 50pF Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Supplier Device Package 14-TSSOP Package / Case 14-TSSOP (0.173", 4.40mm Width)		
Category Integrated Circuits (ICs) Logic - Gates and Inverters Package 14-TSSOP (0.173", 4.40mm Width) Series 74HC Logic Type NAND Gate Number of Circuits 4 Number of Inputs 2 Features - Voltage - Supply 2 V ~ 6 V Current - Quiescent (Max) 2μA Current - Output High, Low 5.2mA, 5.2mA Logic Level - Low 0.5 V ~ 1.8 V Logic Level - High 1.5 V ~ 4.2 V Max Propagation Delay @ V, Max CL 15ns @ 6V, 50pF Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Supplier Device Package 14-TSSOP Package / Case 14-TSSOP (0.173", 4.40mm Width)	Manufacturer Part Number	MM74HC00MTCX
Logic - Gates and InvertersPackage14-TSSOP (0.173", 4.40mm Width)Series74HCLogic TypeNAND GateNumber of Circuits4Number of Inputs2Features-Voltage - Supply2 V ~ 6 VCurrent - Quiescent (Max)2 μ ACurrent - Output High, Low5.2mA, 5.2mALogic Level - Low0.5 V ~ 1.8 VLogic Level - High1.5 V ~ 4.2 VMax Propagation Delay @ V, Max CL15ns @ 6V, 50pFOperating Temperature-40°C ~ 85°CMounting TypeSurface MountSupplier Device Package14-TSSOPPackage / Case14-TSSOP (0.173", 4.40mm Width)	Manufacturer	Fairchild/ON Semiconductor
Package 14-TSSOP (0.173", 4.40mm Width) Series 74HC Logic Type NAND Gate Number of Circuits 4 Number of Inputs 2 Features - Voltage - Supply 2 V ~ 6 V Current - Quiescent (Max) 2μA Current - Output High, Low 5.2mA, 5.2mA Logic Level - Low 0.5 V ~ 1.8 V Logic Level - High 1.5 V ~ 4.2 V Max Propagation Delay @ V, Max CL 15ns @ 6V, 50pF Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Supplier Device Package 14-TSSOP Package / Case 14-TSSOP (0.173", 4.40mm Width)	Category	Integrated Circuits (ICs)
Series $74HC$ Logic TypeNAND GateNumber of Circuits 4 Number of Inputs 2 Features $-$ Voltage - Supply $2 \text{ V} \sim 6 \text{ V}$ Current - Quiescent (Max) $2\mu A$ Current - Output High, Low $5.2\text{mA}, 5.2\text{mA}$ Logic Level - Low $0.5 \text{ V} \sim 1.8 \text{ V}$ Logic Level - High $1.5 \text{ V} \sim 4.2 \text{ V}$ Max Propagation Delay @ V, Max CL 15ns @ 6V , 50pF Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Mounting TypeSurface MountSupplier Device Package 14-TSSOP Package / Case 14-TSSOP (0.173° , 4.40mm Width)		Logic - Gates and Inverters
Logic TypeNAND GateNumber of Circuits4Number of Inputs2Features-Voltage - Supply2 V ~ 6 VCurrent - Quiescent (Max)2μACurrent - Output High, Low5.2mA, 5.2mALogic Level - Low0.5 V ~ 1.8 VLogic Level - High1.5 V ~ 4.2 VMax Propagation Delay @ V, Max CL15ns @ 6V, 50pFOperating Temperature-40°C ~ 85°CMounting TypeSurface MountSupplier Device Package14-TSSOPPackage / Case14-TSSOP (0.173", 4.40mm Width)	Package	14-TSSOP (0.173", 4.40mm Width)
Number of Circuits4Number of Inputs2Features-Voltage - Supply2 V ~ 6 VCurrent - Quiescent (Max)2μACurrent - Output High, Low5.2mA, 5.2mALogic Level - Low0.5 V ~ 1.8 VLogic Level - High1.5 V ~ 4.2 VMax Propagation Delay @ V, Max CL15ns @ 6V, 50pFOperating Temperature-40°C ~ 85°CMounting TypeSurface MountSupplier Device Package14-TSSOPPackage / Case14-TSSOP (0.173", 4.40mm Width)	Series	74HC
Number of Inputs2Features-Voltage - Supply2 V ~ 6 VCurrent - Quiescent (Max)2μACurrent - Output High, Low5.2mA, 5.2mALogic Level - Low0.5 V ~ 1.8 VLogic Level - High1.5 V ~ 4.2 VMax Propagation Delay @ V, Max CL15ns @ 6V, 50pFOperating Temperature-40°C ~ 85°CMounting TypeSurface MountSupplier Device Package14-TSSOPPackage / Case14-TSSOP (0.173", 4.40mm Width)	Logic Type	NAND Gate
Features-Voltage - Supply $2 \text{ V} \sim 6 \text{ V}$ Current - Quiescent (Max) $2\mu\text{A}$ Current - Output High, Low $5.2\text{mA}, 5.2\text{mA}$ Logic Level - Low $0.5 \text{ V} \sim 1.8 \text{ V}$ Logic Level - High $1.5 \text{ V} \sim 4.2 \text{ V}$ Max Propagation Delay @ V, Max CL 15ns @ 6V, 50pF Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Mounting TypeSurface MountSupplier Device Package 14-TSSOP Package / Case 14-TSSOP (0.173", 4.40mm Width)	Number of Circuits	4
Voltage - Supply	Number of Inputs	2
Current - Quiescent (Max) $2\mu A$ Current - Output High, Low $5.2mA, 5.2mA$ Logic Level - Low $0.5 \text{ V} \sim 1.8 \text{ V}$ Logic Level - High $1.5 \text{ V} \sim 4.2 \text{ V}$ Max Propagation Delay @ V, Max CL $15ns @ 6V, 50pF$ Operating Temperature $-40^{\circ}C \sim 85^{\circ}C$ Mounting Type $Surface Mount$ Supplier Device Package 14-TSSOP Package / Case $14\text{-TSSOP} (0.173'', 4.40mm \text{ Width})$	Features	-
Current - Output High, Low 5.2mA , 5.2mA Logic Level - Low $0.5 \text{ V} \sim 1.8 \text{ V}$ Logic Level - High $1.5 \text{ V} \sim 4.2 \text{ V}$ Max Propagation Delay @ V, Max CL 15ns @ 6V, 50pF Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Mounting TypeSurface MountSupplier Device Package 14-TSSOP Package / Case 14-TSSOP (0.173", 4.40mm Width)	Voltage - Supply	2 V ~ 6 V
Logic Level - Low $0.5 \text{ V} \sim 1.8 \text{ V}$ Logic Level - High $1.5 \text{ V} \sim 4.2 \text{ V}$ Max Propagation Delay @ V, Max CL 15ns @ 6V, 50pF Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Mounting TypeSurface MountSupplier Device Package 14-TSSOP Package / Case 14-TSSOP (0.173° , 4.40mm Width)	Current - Quiescent (Max)	2μΑ
Logic Level - High 1.5 V ~ 4.2 V Max Propagation Delay @ V, Max CL 15ns @ 6V, 50pF Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Supplier Device Package 14-TSSOP Package / Case 14-TSSOP (0.173", 4.40mm Width)	Current - Output High, Low	5.2mA, 5.2mA
Max Propagation Delay @ V, Max CL 15ns @ 6V, 50pF Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Supplier Device Package 14-TSSOP Package / Case 14-TSSOP (0.173", 4.40mm Width)	Logic Level - Low	0.5 V ~ 1.8 V
Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Supplier Device Package 14-TSSOP Package / Case 14-TSSOP (0.173", 4.40mm Width)	Logic Level - High	1.5 V ~ 4.2 V
Mounting Type Surface Mount Supplier Device Package 14-TSSOP Package / Case 14-TSSOP (0.173", 4.40mm Width)	Max Propagation Delay @ V, Max CL	15ns @ 6V, 50pF
Supplier Device Package 14-TSSOP Package / Case 14-TSSOP (0.173", 4.40mm Width)	Operating Temperature	-40°C ~ 85°C
Package / Case 14-TSSOP (0.173", 4.40mm Width)	Mounting Type	Surface Mount
	Supplier Device Package	14-TSSOP
	Package / Case	14-TSSOP (0.173", 4.40mm Width)
Report errors?		Report errors?

MM74HC00MTCX Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MM74HC00MTCX Payment Methods



















MM74HC00MTCX Shipping Methods













If you have any question about MM74HC00MTCX, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com