

MMS-123-02-L-DV Information



For Reference Only

Part Number MMS-123-02-L-DV

Manufacturer Samtec Inc.

Category Connectors, Interconnects

Rectangular Connectors - Headers, Receptacles,

Female Sockets

Description CONN RCPT 2MM 46POS DL VERT SMD

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MMS-123-02-L-DV Specifications

Manufacturer Part Number MMS-123-02-L-DV Manufacturer Samtec Inc. Category Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets Package - Series MMS Connector Type Receptacle Contact Type Female Socket Style Board to Board or Cable Number of Positions 46 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 2 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 10µin (0.25µm) Insulation Color Black Insulation Height 0.17" (4.50mm)		
Category Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets Package - Series MMS Connector Type Receptacle Contact Type Female Socket Style Board to Board or Cable Number of Positions 46 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 2 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Surface Mount Termination Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Insulation Color Black	Manufacturer Part Number	MMS-123-02-L-DV
Package-SeriesMMSConnector TypeReceptacleContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions46Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10μin (0.25μm)Insulation ColorBlack	Manufacturer	Samtec Inc.
Package-SeriesMMSConnector TypeReceptacleContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions46Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10μin (0.25μm)Insulation ColorBlack	Category	Connectors, Interconnects
SeriesMMSConnector TypeReceptacleContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions46Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10μin (0.25μm)Insulation ColorBlack		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector Type Receptacle Contact Type Female Socket Style Board to Board or Cable Number of Positions 46 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 2 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 10µin (0.25µm) Insulation Color	Package	-
Contact TypeFemale SocketStyleBoard to Board or CableNumber of Positions46Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10μin (0.25μm)Insulation ColorBlack	Series	MMS
Style Board to Board or Cable Number of Positions 46 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 2 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 10µin (0.25µm) Insulation Color Black	Connector Type	Receptacle
Number of Positions46Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10μin (0.25μm)Insulation ColorBlack	Contact Type	Female Socket
Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10μin (0.25μm)Insulation ColorBlack	Style	Board to Board or Cable
Pitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10μin (0.25μm)Insulation ColorBlack	Number of Positions	46
Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10μin (0.25μm)Insulation ColorBlack	Number of Positions Loaded	All
Row Spacing - Mating 0.079" (2.00mm) Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 10μin (0.25μm) Insulation Color Black	Pitch - Mating	0.079" (2.00mm)
Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 10μin (0.25μm) Insulation Color Black	Number of Rows	2
Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 10μin (0.25μm) Insulation Color Black	Row Spacing - Mating	0.079" (2.00mm)
Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 10μin (0.25μm) Insulation Color Black	Mounting Type	Surface Mount
Contact Finish - Mating Contact Finish Thickness - Mating Insulation Color Gold 10µin (0.25µm) Black	Termination	Solder
Contact Finish Thickness - Mating 10μin (0.25μm) Insulation Color Black	Fastening Type	Push-Pull
Insulation Color Black	Contact Finish - Mating	Gold
	Contact Finish Thickness - Mating	10μin (0.25μm)
Insulation Height 0.177" (4.50mm)	Insulation Color	Black
	Insulation Height	0.177" (4.50mm)
Contact Length - Post -	Contact Length - Post	-
Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Operating Temperature	-55°C ~ 125°C
Material Flammability Rating -	Material Flammability Rating	-

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?

MMS-123-02-L-DV Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MMS-123-02-L-DV Payment Methods



















MMS-123-02-L-DV Shipping Methods













If you have any question about MMS-123-02-L-DV, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com