



MOX-J-021004FE Information

Heisener.com

Part Number MOX-J-021004FE

Manufacturer Ohmite Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 1M OHM 1% 75W

Package Radial, Tubular

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MOX-J-021004FE Specifications

| Manufacturer Part Number MOX-J-021004FE Manufacturer Ohmite Category Resistors Package Radial, Tubular Series Power-Mox Resistance 1 MOhms Tolerance ±1% Power (Watts) 75W Composition Thick Film Temperature Coefficient 50ppm/°C Operating Temperature -65°C ~ 180°C Features High Voltage Coating, Housing Type Ceramic Mounting Feature Brackets Size / Dimension 0.770" Dia x 8.000" L (19.56mm x 203.20mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate - Report errors? | | |
|---|--------------------------|--|
| CategoryResistorsPackageRadial, TubularSeriesPower-MoxResistance1 MOhmsTolerance±1%Power (Watts)75WCompositionThick FilmTemperature Coefficient50ppm/°COperating Temperature-65°C ~ 180°CFeaturesHigh VoltageCoating, Housing TypeCeramicMounting FeatureBracketsSize / Dimension0.770" Dia x 8.000" L (19.56mm x 203.20mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate- | Manufacturer Part Number | MOX-J-021004FE |
| Chassis Mount Resistors Package Radial, Tubular Series Power-Mox Resistance 1 MOhms Tolerance ±1% Power (Watts) 75W Composition Thick Film Temperature Coefficient 50ppm/°C Operating Temperature -65°C ~ 180°C Features High Voltage Coating, Housing Type Ceramic Mounting Feature Brackets Size / Dimension 0.770" Dia x 8.000" L (19.56mm x 203.20mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate | Manufacturer | Ohmite |
| PackageRadial, TubularSeriesPower-MoxResistance1 MOhmsTolerance±1%Power (Watts)75WCompositionThick FilmTemperature Coefficient50ppm/°COperating Temperature-65°C ~ 180°CFeaturesHigh VoltageCoating, Housing TypeCeramicMounting FeatureBracketsSize / Dimension0.770" Dia x 8.000" L (19.56mm x 203.20mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate- | Category | Resistors |
| SeriesPower-MoxResistance1 MOhmsTolerance±1%Power (Watts)75WCompositionThick FilmTemperature Coefficient50ppm/°COperating Temperature-65°C ~ 180°CFeaturesHigh VoltageCoating, Housing TypeCeramicMounting FeatureBracketsSize / Dimension0.770" Dia x 8.000" L (19.56mm x 203.20mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate- | | Chassis Mount Resistors |
| Resistance1 MOhmsTolerance±1%Power (Watts)75WCompositionThick FilmTemperature Coefficient50ppm/°COperating Temperature-65°C ~ 180°CFeaturesHigh VoltageCoating, Housing TypeCeramicMounting FeatureBracketsSize / Dimension0.770" Dia x 8.000" L (19.56mm x 203.20mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate- | Package | Radial, Tubular |
| Tolerance ±1% Power (Watts) 75W Composition Thick Film Temperature Coefficient 50ppm/°C Operating Temperature -65°C ~ 180°C Features High Voltage Coating, Housing Type Ceramic Mounting Feature Brackets Size / Dimension 0.770" Dia x 8.000" L (19.56mm x 203.20mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate - | Series | Power-Mox |
| Power (Watts) Composition Thick Film Temperature Coefficient 50ppm/°C Operating Temperature -65°C ~ 180°C Features High Voltage Coating, Housing Type Ceramic Mounting Feature Brackets Size / Dimension 0.770" Dia x 8.000" L (19.56mm x 203.20mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate - | Resistance | 1 MOhms |
| CompositionThick FilmTemperature Coefficient50ppm/°COperating Temperature-65°C ~ 180°CFeaturesHigh VoltageCoating, Housing TypeCeramicMounting FeatureBracketsSize / Dimension0.770" Dia x 8.000" L (19.56mm x 203.20mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate- | Tolerance | ±1% |
| Temperature Coefficient 50ppm/°C Operating Temperature -65°C ~ 180°C Features High Voltage Coating, Housing Type Ceramic Mounting Feature Brackets Size / Dimension 0.770" Dia x 8.000" L (19.56mm x 203.20mm) Height - Seated (Max) Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate | Power (Watts) | 75W |
| Operating Temperature -65°C ~ 180°C Features High Voltage Coating, Housing Type Ceramic Mounting Feature Brackets Size / Dimension 0.770" Dia x 8.000" L (19.56mm x 203.20mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate - | Composition | Thick Film |
| Features High Voltage Coating, Housing Type Ceramic Mounting Feature Brackets Size / Dimension 0.770" Dia x 8.000" L (19.56mm x 203.20mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate - | Temperature Coefficient | 50ppm/°C |
| Coating, Housing Type Mounting Feature Brackets 0.770" Dia x 8.000" L (19.56mm x 203.20mm) Height - Seated (Max) Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate Ceramic Brackets 0.770" Dia x 8.000" L (19.56mm x 203.20mm) | Operating Temperature | -65°C ~ 180°C |
| Mounting Feature Brackets Size / Dimension 0.770" Dia x 8.000" L (19.56mm x 203.20mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate - | Features | High Voltage |
| Size / Dimension 0.770" Dia x 8.000" L (19.56mm x 203.20mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate - | Coating, Housing Type | Ceramic |
| Height - Seated (Max) Lead Style Package / Case Radial, Tubular Failure Rate - | Mounting Feature | Brackets |
| Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate- | Size / Dimension | 0.770" Dia x 8.000" L (19.56mm x 203.20mm) |
| Package / Case Radial, Tubular Failure Rate - | Height - Seated (Max) | - |
| Failure Rate - | Lead Style | Solder Lugs |
| | Package / Case | Radial, Tubular |
| Report errors? | Failure Rate | - |
| | | Report errors? |

MOX-J-021004FE Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MOX-J-021004FE Payment Methods



















MOX-J-021004FE Shipping Methods













If you have any question about MOX-J-021004FE, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com