



MP2015AGG-Z Information

Heisener.com

Part Number MP2015AGG-Z

Manufacturer Monolithic Power Systems Inc.

Category Integrated Circuits (ICs)

PMIC - Voltage Regulators - Linear

Description 24V, 150MA, LOW QUIESCENT CURREN

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com





Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









Manufacturer Part Number MP2015AGG-Z Manufacturer Monolithic Power Systems Inc. Category Integrated Circuits (ICs) Package - Series - Output Configuration Positive Output Type Adjustable Number of Regulators 1 Voltage - Input (Max) 24V Voltage - Output (Min/Fixed) 1.215V Voltage - Output (Max) 15V Voltage - Output (Max) 1.1V @ 150mA Current - Output 150mA Current - Supply (Max) 35μA ~ 50μA PSRR 55dB (100kHz) Control Features Enable Protection Features - Operating Temperature 40°C ~ 125°C (TJ) Mounting Type - Package / Case - Supplier Device Package - Epotterrors?	*	
Category Integrated Circuits (ICs) PMIC - Voltage Regulators - Linear Package - Series - Output Configuration Positive Output Type Adjustable Number of Regulators 1 Voltage - Input (Max) 24V Voltage - Output (Min/Fixed) 1.215V Voltage - Output (Max) 15V Voltage Dropout (Max) 1.1V @ 150mA Current - Output 150mA Current - Quiescent (Iq) - Current - Supply (Max) 35μA ~ 50μA PSRR 55dB (100kHz) Control Features Enable Protection Features - Operating Temperature -40°C ~ 125°C (TJ) Mounting Type - Package / Case - Supplier Device Package -	Manufacturer Part Number	MP2015AGG-Z
Package - Series - Output Configuration Positive Output Type Adjustable Number of Regulators 1 Voltage - Input (Max) 24V Voltage - Output (Min/Fixed) 1.215V Voltage - Output (Max) 15V Voltage Dropout (Max) 1.1V @ 150mA Current - Output 150mA Current - Quiescent (Iq) - Current - Supply (Max) 35μA ~ 50μA PSRR 55dB (100kHz) Control Features Enable Protection Features - Operating Temperature -40°C ~ 125°C (TJ) Mounting Type - Package / Case - Supplier Device Package -	Manufacturer	Monolithic Power Systems Inc.
Package - Series - Output Configuration Positive Output Type Adjustable Number of Regulators 1 Voltage - Input (Max) 24V Voltage - Output (Min/Fixed) 1.215V Voltage - Output (Max) 15V Voltage Dropout (Max) 1.1V @ 150mA Current - Output 150mA Current - Quiescent (Iq) - Current - Supply (Max) 35μA ~ 50μA PSRR 55dB (100kHz) Control Features - Operating Temperature -40°C ~ 125°C (TJ) Mounting Type - Package / Case - Supplier Device Package -	Category	Integrated Circuits (ICs)
Series - Output Configuration Positive Output Type Adjustable Number of Regulators 1 Voltage - Input (Max) 24V Voltage - Output (Min/Fixed) 1.215V Voltage - Output (Max) 15V Voltage Dropout (Max) 1.1V @ 150mA Current - Output 150mA Current - Quiescent (Iq) - Current - Supply (Max) 35µA ~ 50µA PSRR 55dB (100kHz) Control Features Enable Protection Features - 40°C ~ 125°C (TJ) Mounting Type - Package / Case Supplier Device Package		PMIC - Voltage Regulators - Linear
Output ConfigurationPositiveOutput TypeAdjustableNumber of Regulators1Voltage - Input (Max)24VVoltage - Output (Min/Fixed)1.215VVoltage - Output (Max)15VVoltage Dropout (Max)1.1V @ 150mACurrent - Output150mACurrent - Quiescent (Iq)-Current - Supply (Max)35μA ~ 50μAPSRR55dB (100kHz)Control FeaturesEnableProtection Features-Operating Temperature-40°C ~ 125°C (TJ)Mounting Type-Package / Case-Supplier Device Package-	Package	-
Output TypeAdjustableNumber of Regulators1Voltage - Input (Max)24VVoltage - Output (Min/Fixed)1.215VVoltage - Output (Max)15VVoltage Dropout (Max)1.1V @ 150mACurrent - Output150mACurrent - Quiescent (Iq)-Current - Supply (Max)35μA ~ 50μAPSRR55dB (100kHz)Control FeaturesEnableProtection Features-Operating Temperature-40°C ~ 125°C (TJ)Mounting Type-Package / Case-Supplier Device Package-	Series	-
Number of Regulators1Voltage - Input (Max)24VVoltage - Output (Min/Fixed)1.215VVoltage - Output (Max)15VVoltage Dropout (Max)1.1V @ 150mACurrent - Output150mACurrent - Quiescent (Iq)-Current - Supply (Max)35μA ~ 50μAPSRR55dB (100kHz)Control FeaturesEnableProtection Features-Operating Temperature-40°C ~ 125°C (TJ)Mounting Type-Package / Case-Supplier Device Package-	Output Configuration	Positive
Voltage - Input (Max)24VVoltage - Output (Min/Fixed)1.215VVoltage - Output (Max)15VVoltage Dropout (Max)1.1V @ 150mACurrent - Output150mACurrent - Quiescent (Iq)-Current - Supply (Max)35μA ~ 50μAPSRR55dB (100kHz)Control FeaturesEnableProtection Features-Operating Temperature-40°C ~ 125°C (TJ)Mounting Type-Package / Case-Supplier Device Package-	Output Type	Adjustable
Voltage - Output (Min/Fixed)1.215VVoltage - Output (Max)15VVoltage Dropout (Max)1.1V @ 150mACurrent - Output150mACurrent - Quiescent (Iq)-Current - Supply (Max)35μA ~ 50μAPSRR55dB (100kHz)Control FeaturesEnableProtection Features-Operating Temperature-40°C ~ 125°C (TJ)Mounting Type-Package / Case-Supplier Device Package-	Number of Regulators	1
Voltage - Output (Max) Voltage Dropout (Max) 1.1V @ 150mA Current - Output 150mA Current - Quiescent (Iq) - Current - Supply (Max) PSRR 55dB (100kHz) Control Features Enable Protection Features Operating Temperature -40°C ~ 125°C (TJ) Mounting Type - Package / Case Supplier Device Package - Supplier Device Package	Voltage - Input (Max)	24V
Voltage Dropout (Max) Current - Output 150mA Current - Quiescent (Iq) - Current - Supply (Max) PSRR 55dB (100kHz) Control Features Enable Protection Features Operating Temperature -40°C ~ 125°C (TJ) Mounting Type Package / Case Supplier Device Package - 150mA - 150mA	Voltage - Output (Min/Fixed)	1.215V
Current - Output 150mA Current - Quiescent (Iq) - Current - Supply (Max) 35 μ A ~ 50 μ A PSRR 55dB (100kHz) Control Features Enable Protection Features - Operating Temperature -40°C ~ 125°C (TJ) Mounting Type - Package / Case - Supplier Device Package -	Voltage - Output (Max)	15V
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$	Voltage Dropout (Max)	1.1V @ 150mA
Current - Supply (Max) PSRR 55dB (100kHz) Control Features Enable Protection Features -40°C ~ 125°C (TJ) Mounting Type - Package / Case Supplier Device Package - Supplier Device Package	Current - Output	150mA
PSRR 55dB (100kHz) Control Features Enable Protection Features -40°C ~ 125°C (TJ) Mounting Type - Package / Case - Supplier Device Package -	Current - Quiescent (Iq)	-
Control Features Enable Protection Features - Operating Temperature -40°C ~ 125°C (TJ) Mounting Type - Package / Case - Supplier Device Package -	Current - Supply (Max)	35μΑ ~ 50μΑ
Protection Features - Operating Temperature -40°C ~ 125°C (TJ) Mounting Type - Package / Case - Supplier Device Package -	PSRR	55dB (100kHz)
Operating Temperature -40°C ~ 125°C (TJ) Mounting Type - Package / Case - Supplier Device Package -	Control Features	Enable
Mounting Type - Package / Case - Supplier Device Package -	Protection Features	-
Package / Case - Supplier Device Package -	Operating Temperature	-40°C ~ 125°C (TJ)
Supplier Device Package -	Mounting Type	-
	Package / Case	-
Report errors?	Supplier Device Package	-
		Report errors?

MP2015AGG-Z Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MP2015AGG-Z Payment Methods





















MP2015AGG-Z Shipping Methods













If you have any question about MP2015AGG-Z, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com