



MP2015AGJE-P Information

Heisener.com

Part Number MP2015AGJE-P

Manufacturer Monolithic Power Systems Inc.

Category Integrated Circuits (ICs)

PMIC - Voltage Regulators - Linear

Description 24V, 150MA, LOW QUIESCENT CURREN

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MP2015AGJE-P Specifications

Manufacturer Part Number MP2015AGJE-P Manufacturer Monolithic Power Systems Inc. Category Integrated Circuits (ICs) Package - Series - Output Configuration Positive Output Type Adjustable Number of Regulators 1 Voltage - Input (Max) 24V Voltage - Output (Min/Fixed) 1.215V Voltage - Output (Max) 15V Voltage Dropout (Max) 1.1V @ 150mA Current - Output 150mA Current - Supply (Max) 35μA ~ 50μA PSRR 55dB (100kHz) Control Features Enable Protection Features - Operating Temperature 40°C ~ 125°C (TJ) Mounting Type - Package / Case - Supplier Device Package -		
Category Integrated Circuits (ICs) PMIC - Voltage Regulators - Linear Package - Series - Output Configuration Positive Output Type Adjustable Number of Regulators 1 Voltage - Input (Max) 24V Voltage - Output (Min/Fixed) 1.215V Voltage - Output (Max) 15V Voltage Dropout (Max) 1.1V @ 150mA Current - Output 150mA Current - Quiescent (Iq) - Current - Supply (Max) 35μA ~ 50μA PSRR 55dB (100kHz) Control Features Enable Protection Features - Operating Temperature -40°C ~ 125°C (TJ) Mounting Type - Package / Case - Supplier Device Package -	Manufacturer Part Number	MP2015AGJE-P
Package - Series - Output Configuration Positive Output Type Adjustable Number of Regulators 1 Voltage - Input (Max) 24V Voltage - Output (Min/Fixed) 1.215V Voltage - Output (Max) 15V Voltage Dropout (Max) 1.1V @ 150mA Current - Output 150mA Current - Quiescent (Iq) - Current - Supply (Max) 35μA ~ 50μA PSRR 55dB (100kHz) Control Features Enable Protection Features - Operating Temperature -40°C ~ 125°C (TJ) Mounting Type - Package / Case - Supplier Device Package -	Manufacturer	Monolithic Power Systems Inc.
Package - Series - Output Configuration Positive Output Type Adjustable Number of Regulators 1 Voltage - Input (Max) 24V Voltage - Output (Min/Fixed) 1.215V Voltage - Output (Max) 15V Voltage Dropout (Max) 1.1V @ 150mA Current - Output 150mA Current - Quiescent (Iq) - Current - Supply (Max) 35μA ~ 50μA PSRR 55dB (100kHz) Control Features - Protection Features - Operating Temperature -40°C ~ 125°C (TJ) Mounting Type - Package / Case - Supplier Device Package -	Category	Integrated Circuits (ICs)
Series - Output Configuration Positive Output Type Adjustable Number of Regulators 1 Voltage - Input (Max) 24V Voltage - Output (Min/Fixed) 1.215V Voltage - Output (Max) 15V Voltage Dropout (Max) 1.1V @ 150mA Current - Output 150mA Current - Quiescent (Iq) - Current - Supply (Max) 35μA ~ 50μA PSRR 55dB (100kHz) Control Features Enable Protection Features - Operating Temperature -40°C ~ 125°C (TJ) Mounting Type - Package / Case - Supplier Device Package -		PMIC - Voltage Regulators - Linear
Output ConfigurationPositiveOutput TypeAdjustableNumber of Regulators1Voltage - Input (Max)24VVoltage - Output (Min/Fixed)1.215VVoltage - Output (Max)15VVoltage Dropout (Max)1.1V @ 150mACurrent - Output150mACurrent - Quiescent (Iq)-Current - Supply (Max)35µA ~ 50µAPSRR55dB (100kHz)Control FeaturesEnableProtection Features-Operating Temperature-40°C ~ 125°C (TJ)Mounting Type-Package / Case-Supplier Device Package-	Package	-
Output TypeAdjustableNumber of Regulators1Voltage - Input (Max)24VVoltage - Output (Min/Fixed)1.215VVoltage - Output (Max)15VVoltage Dropout (Max)1.1V @ 150mACurrent - Output150mACurrent - Quiescent (Iq)-Current - Supply (Max)35μA ~ 50μAPSRR55dB (100kHz)Control FeaturesEnableProtection Features-Operating Temperature-40°C ~ 125°C (TJ)Mounting Type-Package / Case-Supplier Device Package-	Series	-
Number of Regulators1Voltage - Input (Max)24VVoltage - Output (Min/Fixed)1.215VVoltage - Output (Max)15VVoltage Dropout (Max)1.1V @ 150mACurrent - Output150mACurrent - Quiescent (Iq)-Current - Supply (Max)35μA ~ 50μAPSRR55dB (100kHz)Control FeaturesEnableProtection Features-Operating Temperature-40°C ~ 125°C (TJ)Mounting Type-Package / Case-Supplier Device Package-	Output Configuration	Positive
Voltage - Input (Max)24VVoltage - Output (Min/Fixed)1.215VVoltage - Output (Max)15VVoltage Dropout (Max)1.1V @ 150mACurrent - Output150mACurrent - Quiescent (Iq)-Current - Supply (Max)35μA ~ 50μAPSRR55dB (100kHz)Control FeaturesEnableProtection Features-Operating Temperature-40°C ~ 125°C (TJ)Mounting Type-Package / Case-Supplier Device Package-	Output Type	Adjustable
Voltage - Output (Min/Fixed)1.215VVoltage - Output (Max)15VVoltage Dropout (Max)1.1V @ 150mACurrent - Output150mACurrent - Quiescent (Iq)-Current - Supply (Max)35μA ~ 50μAPSRR55dB (100kHz)Control FeaturesEnableProtection Features-Operating Temperature-40°C ~ 125°C (TJ)Mounting Type-Package / Case-Supplier Device Package-	Number of Regulators	1
Voltage - Output (Max)15VVoltage Dropout (Max)1.1V @ 150mACurrent - Output150mACurrent - Quiescent (Iq)-Current - Supply (Max)35μA ~ 50μAPSRR55dB (100kHz)Control FeaturesEnableProtection Features-Operating Temperature-40°C ~ 125°C (TJ)Mounting Type-Package / Case-Supplier Device Package-	Voltage - Input (Max)	24V
Voltage Dropout (Max) 1.1V @ 150mA	Voltage - Output (Min/Fixed)	1.215V
Current - Output 150mA Current - Quiescent (Iq) Current - Supply (Max) 35 μ A ~ 50 μ A PSRR 55dB (100kHz) Control Features Enable Protection Features Operating Temperature -40°C ~ 125°C (TJ) Mounting Type Package / Case Supplier Device Package	Voltage - Output (Max)	15V
$\begin{tabular}{lllllllllllllllllllllllllllllllllll$	Voltage Dropout (Max)	1.1V @ 150mA
Current - Supply (Max) $35\mu A \sim 50\mu A$ PSRR $55dB (100kHz)$ Enable Protection Features - 40°C ~ 125°C (TJ) Mounting Type - Package / Case - Supplier Device Package	Current - Output	150mA
PSRR 55dB (100kHz) Control Features Enable Protection Features -40°C ~ 125°C (TJ) Mounting Type - Package / Case - Supplier Device Package -	Current - Quiescent (Iq)	-
Control Features Protection Features Operating Temperature -40°C ~ 125°C (TJ) Mounting Type - Package / Case Supplier Device Package Enable - Enable - 40°C ~ 125°C (TJ) - - - - - - - - - - - - -	Current - Supply (Max)	35μΑ ~ 50μΑ
Protection Features - Operating Temperature -40°C ~ 125°C (TJ) Mounting Type - Package / Case - Supplier Device Package -	PSRR	55dB (100kHz)
Operating Temperature -40°C ~ 125°C (TJ) Mounting Type - Package / Case - Supplier Device Package -	Control Features	Enable
Mounting Type - Package / Case - Supplier Device Package -	Protection Features	-
Package / Case - Supplier Device Package -	Operating Temperature	-40°C ~ 125°C (TJ)
Supplier Device Package -	Mounting Type	-
	Package / Case	-
Report errors?	Supplier Device Package	-
		Report errors?

MP2015AGJE-P Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MP2015AGJE-P Payment Methods



















MP2015AGJE-P Shipping Methods













If you have any question about MP2015AGJE-P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com