



MP62040DQFU-LF-Z Information



For Reference Only

Part Number MP62040DQFU-LF-Z

Manufacturer Monolithic Power Systems Inc.

Category Integrated Circuits (ICs)

PMIC - Power Distribution Switches, Load Drivers

DescriptionIC CURR LIMIT SWITCHPackage4-UFDFN Exposed Pad

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MP62040DQFU-LF-Z Specifications

Manufacturer Part Number MP62040DQFU-LF-Z Manufacturer Monolithic Power Systems Inc. Category Integrated Circuits (ICs) Package 4-UFDFN Exposed Pad Series - Switch Type General Purpose Number of Outputs 1 Ratio - Input:Output 1:1 Output Configuration High Side Output Type P-Channel Interface On/Off Voltage - Load 1.7 V ~ 5.5 V Voltage - Supply (Vcc/Vdd) Not Required Current - Output (Max) 2A Rds On (Typ) 85 mOhm Input Type - Features Slew Rate Controlled Fault Protection - Operating Temperature -40°C ~ 85°C (TA) Package / Case 4-UFDFN Exposed Pad Supplier Device Package 4-UTQFN (1.6x1.2)		
Category Integrated Circuits (ICs) PMIC - Power Distribution Switches, Load Drivers Package 4-UFDFN Exposed Pad Series - Switch Type General Purpose Number of Outputs 1 Ratio - Input:Output 1:1 Output Configuration High Side Output Type P-Channel Interface On/Off Voltage - Load 1.7 V ~ 5.5 V Voltage - Supply (Vcc/Vdd) Not Required Current - Output (Max) 2A Rds On (Typ) 85 mOhm Input Type - Features Slew Rate Controlled Fault Protection - Operating Temperature -40°C ~ 85°C (TA) Package / Case 4-UFDFN Exposed Pad Supplier Device Package 4-UTQFN (1.6x1.2)	Manufacturer Part Number	MP62040DQFU-LF-Z
Package 4-UFDFN Exposed Pad Series - Switch Type General Purpose Number of Outputs 1:1 Output Configuration High Side Output Type P-Channel Interface On/Off Voltage - Load 1.7 V ~ 5.5 V Voltage - Supply (Vcc/Vdd) Not Required Current - Output (Max) 2A Rds On (Typ) 85 mOhm Input Type - Features Slew Rate Controlled Fault Protection - Operating Temperature - 40°C ~ 85°C (TA) Package / Case 4-UTQFN (1.6x1.2)	Manufacturer	Monolithic Power Systems Inc.
Package 4-UFDFN Exposed Pad Series - Switch Type General Purpose Number of Outputs 1 Ratio - Input:Output 1:1 Output Configuration High Side Output Type P-Channel Interface On/Off Voltage - Load 1.7 V ~ 5.5 V Voltage - Supply (Vcc/Vdd) Not Required Current - Output (Max) 2A Rds On (Typ) 85 mOhm Input Type - Features Slew Rate Controlled Fault Protection - Operating Temperature -40°C ~ 85°C (TA) Package / Case 4-UFDFN Exposed Pad Supplier Device Package 4-UTQFN (1.6x1.2)	Category	Integrated Circuits (ICs)
Series - Switch Type General Purpose Number of Outputs 1 Ratio - Input:Output 1:1 Output Configuration High Side Output Type P-Channel Interface On/Off Voltage - Load 1.7 V ~ 5.5 V Voltage - Supply (Vcc/Vdd) Not Required Current - Output (Max) 2A Rds On (Typ) 85 mOhm Input Type - Features Slew Rate Controlled Fault Protection - Operating Temperature -40°C ~ 85°C (TA) Package / Case 4-UFDFN Exposed Pad Supplier Device Package 4-UTQFN (1.6x1.2)		PMIC - Power Distribution Switches, Load Drivers
Switch TypeGeneral PurposeNumber of Outputs1Ratio - Input:Output1:1Output ConfigurationHigh SideOutput TypeP-ChannelInterfaceOn/OffVoltage - Load1.7 V ~ 5.5 VVoltage - Supply (Vcc/Vdd)Not RequiredCurrent - Output (Max)2ARds On (Typ)85 mOhmInput Type-FeaturesSlew Rate ControlledFault Protection-Operating Temperature-40°C ~ 85°C (TA)Package / Case4-UFDFN Exposed PadSupplier Device Package4-UTQFN (1.6x1.2)	Package	4-UFDFN Exposed Pad
Number of Outputs Ratio - Input:Output 1:1 Output Configuration High Side Output Type P-Channel Interface On/Off Voltage - Load 1.7 V ~ 5.5 V Voltage - Supply (Vcc/Vdd) Not Required Current - Output (Max) 2A Rds On (Typ) 85 mOhm Input Type - Features Slew Rate Controlled Fault Protection Operating Temperature -40°C ~ 85°C (TA) Package / Case Supplier Device Package 4-UTQFN (1.6x1.2)	Series	-
Ratio - Input:Output Output Configuration High Side Output Type P-Channel Interface On/Off Voltage - Load 1.7 V ~ 5.5 V Voltage - Supply (Vcc/Vdd) Not Required Current - Output (Max) 2A Rds On (Typ) 85 mOhm Input Type - Features Slew Rate Controlled Fault Protection Operating Temperature -40°C ~ 85°C (TA) Package / Case Supplier Device Package 4-UTQFN (1.6x1.2)	Switch Type	General Purpose
Output Configuration High Side Output Type P-Channel Interface On/Off Voltage - Load 1.7 V ~ 5.5 V Voltage - Supply (Vcc/Vdd) Not Required Current - Output (Max) 2A Rds On (Typ) 85 mOhm Input Type - Features Slew Rate Controlled Fault Protection Operating Temperature -40°C ~ 85°C (TA) Package / Case 4-UFDFN Exposed Pad Supplier Device Package 4-UTQFN (1.6x1.2)	Number of Outputs	1
Output Type P-Channel Interface On/Off Voltage - Load 1.7 V ~ 5.5 V Voltage - Supply (Vcc/Vdd) Not Required Current - Output (Max) 2A Rds On (Typ) 85 mOhm Input Type - Features Slew Rate Controlled Fault Protection - Operating Temperature -40°C ~ 85°C (TA) Package / Case 4-UFDFN Exposed Pad Supplier Device Package 4-UTQFN (1.6x1.2)	Ratio - Input:Output	1:1
Interface On/Off Voltage - Load 1.7 V ~ 5.5 V Voltage - Supply (Vcc/Vdd) Not Required Current - Output (Max) 2A Rds On (Typ) 85 mOhm Input Type - Features Slew Rate Controlled Fault Protection - Operating Temperature -40°C ~ 85°C (TA) Package / Case 4-UTQFN (1.6x1.2)	Output Configuration	High Side
Voltage - Load 1.7 V ~ 5.5 V Voltage - Supply (Vcc/Vdd) Not Required Current - Output (Max) 2A Rds On (Typ) 85 mOhm Input Type - Features Slew Rate Controlled Fault Protection Operating Temperature -40°C ~ 85°C (TA) Package / Case 4-UTQFN (1.6x1.2)	Output Type	P-Channel
Voltage - Supply (Vcc/Vdd) Not Required Current - Output (Max) 2A Rds On (Typ) 85 mOhm Input Type - Features Slew Rate Controlled Fault Protection - Operating Temperature -40°C ~ 85°C (TA) Package / Case 4-UTQFN (1.6x1.2)	Interface	On/Off
Current - Output (Max) Rds On (Typ) 85 mOhm Input Type - Features Slew Rate Controlled Fault Protection Operating Temperature -40°C ~ 85°C (TA) Package / Case 4-UFDFN Exposed Pad Supplier Device Package 4-UTQFN (1.6x1.2)	Voltage - Load	1.7 V ~ 5.5 V
Rds On (Typ) 85 mOhm Input Type - Features Slew Rate Controlled Fault Protection Operating Temperature -40°C ~ 85°C (TA) Package / Case 4-UFDFN Exposed Pad Supplier Device Package 4-UTQFN (1.6x1.2)	Voltage - Supply (Vcc/Vdd)	Not Required
Input Type - Features Slew Rate Controlled Fault Protection - Operating Temperature -40°C ~ 85°C (TA) Package / Case 4-UFDFN Exposed Pad Supplier Device Package 4-UTQFN (1.6x1.2)	Current - Output (Max)	2A
Features Slew Rate Controlled Fault Protection - Operating Temperature -40°C ~ 85°C (TA) Package / Case 4-UFDFN Exposed Pad Supplier Device Package 4-UTQFN (1.6x1.2)	Rds On (Typ)	85 mOhm
Fault Protection - Operating Temperature -40°C ~ 85°C (TA) Package / Case 4-UFDFN Exposed Pad Supplier Device Package 4-UTQFN (1.6x1.2)	Input Type	-
Operating Temperature -40°C ~ 85°C (TA) Package / Case 4-UFDFN Exposed Pad Supplier Device Package 4-UTQFN (1.6x1.2)	Features	Slew Rate Controlled
Package / Case 4-UFDFN Exposed Pad Supplier Device Package 4-UTQFN (1.6x1.2)	Fault Protection	-
Supplier Device Package 4-UTQFN (1.6x1.2)	Operating Temperature	-40°C ~ 85°C (TA)
	Package / Case	4-UFDFN Exposed Pad
Report errors?	Supplier Device Package	4-UTQFN (1.6x1.2)
		Report errors?

MP62040DQFU-LF-Z Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MP62040DQFU-LF-Z Payment Methods



















MP62040DQFU-LF-Z Shipping Methods













If you have any question about MP62040DQFU-LF-Z, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com