

### MPB80-3300 Information



For Reference Only

Part Number MPB80-3300

Manufacturer Bel Power Solutions

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

**Description** AC/DC CONVERTER 3.3V 5V 12V 80W

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **MPB80-3300 Specifications**

Manufacturer Part Number         MPB80-3300           Manufacturer         Bel Power Solutions           Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         MPB80           Type         Open Frame           Number of Outputs         3           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         3.3V           Voltage - Output 2         5V           Voltage - Output 3         12V           Voltage - Output 4         -           Current - Output (Max)         7A, 3A, 400mA           Power (Watts)         80W           Applications         ITE (Commercial)           Voltage - Isolation         2.6kV (2600V)           Efficiency         73%           Operating Temperature         0°C ~ 70°C (With Derating)           Features         Adjustable Output, PFC, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.00" L x 3.00" W x 1.40" H (127.0mm x 76.2mm x 35.6mm)	•	
Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         MPB80           Type         Open Frame           Number of Outputs         3           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         3.3V           Voltage - Output 2         5V           Voltage - Output 3         12V           Voltage - Output 4         -           Current - Output (Max)         7A, 3A, 400mA           Power (Watts)         80W           Applications         ITE (Commercial)           Voltage - Isolation         2.6kV (2600V)           Efficiency         73%           Operating Temperature         0°C ~ 70°C (With Derating)           Features         Adjustable Output, PFC, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.00" L x 3.00" W x 1.40" H (127.0mm x 76.2mm x 35.6mm)	Manufacturer Part Number	MPB80-3300
Package         -           Series         MPB80           Type         Open Frame           Number of Outputs         3           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         3.3V           Voltage - Output 2         5V           Voltage - Output 3         12V           Voltage - Output 4         -           Current - Output (Max)         7A, 3A, 400mA           Power (Watts)         80W           Applications         ITE (Commercial)           Voltage - Isolation         2.6kV (2600V)           Efficiency         73%           Operating Temperature         0°C ~ 70°C (With Derating)           Features         Adjustable Output, PFC, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.00" L x 3.00" W x 1.40" H (127.0mm x 76.2mm x 35.6mm)	Manufacturer	Bel Power Solutions
Package         -           Series         MPB80           Type         Open Frame           Number of Outputs         3           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         3.3V           Voltage - Output 2         5V           Voltage - Output 3         12V           Voltage - Output 4         -           Current - Output (Max)         7A, 3A, 400mA           Power (Watts)         80W           Applications         ITE (Commercial)           Voltage - Isolation         2.6kV (2600V)           Efficiency         73%           Operating Temperature         0°C ~ 70°C (With Derating)           Features         Adjustable Output, PFC, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.00" L x 3.00" W x 1.40" H (127.0mm x 76.2mm x 35.6mm)	Category	Power Supplies - External/Internal (Off-Board)
Series         MPB80           Type         Open Frame           Number of Outputs         3           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         3.3V           Voltage - Output 2         5V           Voltage - Output 3         12V           Voltage - Output 4         -           Current - Output (Max)         7A, 3A, 400mA           Power (Watts)         80W           Applications         ITE (Commercial)           Voltage - Isolation         2.6kV (2600V)           Efficiency         73%           Operating Temperature         0°C ~ 70°C (With Derating)           Features         Adjustable Output, PFC, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.00" L x 3.00" W x 1.40" H (127.0mm x 76.2mm x 35.6mm)		AC DC Converters
Type         Open Frame           Number of Outputs         3           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         3.3V           Voltage - Output 2         5V           Voltage - Output 3         12V           Voltage - Output 4         -           Current - Output (Max)         7A, 3A, 400mA           Power (Watts)         80W           Applications         ITE (Commercial)           Voltage - Isolation         2.6kV (2600V)           Efficiency         73%           Operating Temperature         0°C ~ 70°C (With Derating)           Features         Adjustable Output, PFC, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.00" L x 3.00" W x 1.40" H (127.0mm x 76.2mm x 35.6mm)	Package	-
Number of Outputs3Voltage - Input $85 \sim 264 \text{ VAC}$ Voltage - Output 1 $3.3\text{V}$ Voltage - Output 2 $5\text{V}$ Voltage - Output 3 $12\text{V}$ Voltage - Output 4-Current - Output (Max) $7A$ , $3A$ , $400\text{mA}$ Power (Watts) $80\text{W}$ ApplicationsITE (Commercial)Voltage - Isolation $2.6\text{kV}$ ( $2600\text{V}$ )Efficiency $73\%$ Operating Temperature $0^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (With Derating)FeaturesAdjustable Output, PFC, Universal InputMounting TypeChassis MountSize / Dimension $5.00^{\circ}\text{L x } 3.00^{\circ}\text{W x } 1.40^{\circ}\text{H}$ ( $127.0\text{mm x } 76.2\text{mm x } 35.6\text{mm}$ )	Series	MPB80
Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         3.3V           Voltage - Output 2         5V           Voltage - Output 3         12V           Voltage - Output 4         -           Current - Output (Max)         7A, 3A, 400mA           Power (Watts)         80W           Applications         ITE (Commercial)           Voltage - Isolation         2.6kV (2600V)           Efficiency         73%           Operating Temperature         0°C ~ 70°C (With Derating)           Features         Adjustable Output, PFC, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.00" L x 3.00" W x 1.40" H (127.0mm x 76.2mm x 35.6mm)	Type	Open Frame
Voltage - Output 1  Voltage - Output 2  5V  Voltage - Output 3  12V  Voltage - Output 4  - Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  2.6kV (2600V)  Efficiency  Operating Temperature  O"C ~ 70°C (With Derating)  Features  Adjustable Output, PFC, Universal Input  Mounting Type  Size / Dimension  3.3V  3.3V  3.3V  3.3V  3.3V  3.3V  3.3V  4.40" H (127.0mm x 76.2mm x 35.6mm)	Number of Outputs	3
Voltage - Output 2  Voltage - Output 3  12V  Voltage - Output 4  - Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  2.6kV (2600V)  Efficiency  Operating Temperature  O°C ~ 70°C (With Derating)  Features  Adjustable Output, PFC, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  5.00" L x 3.00" W x 1.40" H (127.0mm x 76.2mm x 35.6mm)	Voltage - Input	85 ~ 264 VAC
Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  2.6kV (2600V)  Efficiency  Operating Temperature  O°C ~ 70°C (With Derating)  Features  Adjustable Output, PFC, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  12V  12V  12V  12V  12V  12V  12V  12	Voltage - Output 1	3.3V
Voltage - Output 4  Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  2.6kV (2600V)  Efficiency  73%  Operating Temperature  O°C ~ 70°C (With Derating)  Features  Adjustable Output, PFC, Universal Input  Mounting Type  Chassis Mount  Size / Dimension	Voltage - Output 2	5V
Current - Output (Max)  Power (Watts)  80W  Applications  ITE (Commercial)  Voltage - Isolation  2.6kV (2600V)  Efficiency  73%  Operating Temperature  0°C ~ 70°C (With Derating)  Features  Adjustable Output, PFC, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  7A, 3A, 400mA  80W  AU  AU  Commercial)  Commercial  Commercial  Au  Commercial  Commercial  Commercial  Commercial  Au  Commercial  Co	Voltage - Output 3	12V
Power (Watts)80WApplicationsITE (Commercial)Voltage - Isolation2.6kV (2600V)Efficiency73%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, PFC, Universal InputMounting TypeChassis MountSize / Dimension5.00" L x 3.00" W x 1.40" H (127.0mm x 76.2mm x 35.6mm)	Voltage - Output 4	-
Applications ITE (Commercial)  Voltage - Isolation 2.6kV (2600V)  Efficiency 73%  Operating Temperature 0°C ~ 70°C (With Derating)  Features Adjustable Output, PFC, Universal Input  Mounting Type Chassis Mount  Size / Dimension 5.00" L x 3.00" W x 1.40" H (127.0mm x 76.2mm x 35.6mm)	Current - Output (Max)	7A, 3A, 400mA
Voltage - Isolation  2.6kV (2600V)  Efficiency  73%  Operating Temperature  0°C ~ 70°C (With Derating)  Features  Adjustable Output, PFC, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  5.00" L x 3.00" W x 1.40" H (127.0mm x 76.2mm x 35.6mm)	Power (Watts)	80W
Efficiency 73%  Operating Temperature 0°C ~ 70°C (With Derating)  Features Adjustable Output, PFC, Universal Input  Mounting Type Chassis Mount  Size / Dimension 5.00" L x 3.00" W x 1.40" H (127.0mm x 76.2mm x 35.6mm)	Applications	ITE (Commercial)
Operating Temperature  0°C ~ 70°C (With Derating)  Adjustable Output, PFC, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  5.00" L x 3.00" W x 1.40" H (127.0mm x 76.2mm x 35.6mm)	Voltage - Isolation	2.6kV (2600V)
Features Adjustable Output, PFC, Universal Input  Mounting Type Chassis Mount  Size / Dimension 5.00" L x 3.00" W x 1.40" H (127.0mm x 76.2mm x 35.6mm)	Efficiency	73%
Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.40" H (127.0mm x 76.2mm x 35.6mm)	Operating Temperature	$0^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (With Derating)
Size / Dimension 5.00" L x 3.00" W x 1.40" H (127.0mm x 76.2mm x 35.6mm)	Features	Adjustable Output, PFC, Universal Input
	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	5.00" L x 3.00" W x 1.40" H (127.0mm x 76.2mm x 35.6mm)
		Report errors?

#### MPB80-3300 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### MPB80-3300 Payment Methods



















### **MPB80-3300 Shipping Methods**













If you have any question about MPB80-3300, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com