

MPC-X-12

MPC-X-12 Information

| Heisener.com | MPC-X-12 Signal Transformer Transformers Power Transformers XFRMR LAMINATED 10VA THRU HOLE - For the pricing/inventory/lead time, please contact | |
|--------------------|--|-----------------|
| For Reference Only | us Website: https://www.heisener.com E-mail: salesdept@heisener.com | Request a Quote |

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MPC-X-12 Specifications

| Manufacturer Part Number MPC-X-12 Manufacturer Signal Transformers Category Transformers Package - Package - Stries MPC Youge - Primary Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) Parallel 50V, Series 12V Current - Output (Max) Parallel 360mA, Series 60mA String Jual Conter Tap Voltage - Secondary Winding(s) Power - Max IOVA Mounting Type Primary Winding Series 60mA Store - Max IOVA Mounting Type Primary Winding Series 60mA Youge - Solation Prover - Max Mounting Type Dual Youge - Solation Prover - Max Mounting Type Prover - Max Youge - Isolation Prover - Max Woltage - Isolation SigoVrms Youge - Isolation SigoVrms | | |
|---|---------------------------------|-----------------------------|
| CategoryTansformersPackage-SeriesMPCTypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)Parallel 5V, Series 12VCurrent - Output (Max)Parallel 360mA, Series 60mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapYesPower - Max10 VAMounting TypePrinary Minding SingleSize / DimensionPC PinStard (Max)Stard (Max)Height - Seated (Max)41.00mmVoltage - Isolation1500VrmsWeightStard (Scolating) | Manufacturer Part Number | MPC-X-12 |
| Power TransformersPackage-SeriesMPCTypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)Parallel 5V, Series 12VCurrent - Output (Max)Parallel 360mA, Series 60mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapYesPower - Max10 VAMounting TypeThrough HoleSize / Dimension47.60mm Lx 36.50mm WHeight - Seated (Max)1500VrmsVoltage - Isolation1500Vrms | Manufacturer | Signal Transformer |
| Package-SeriesMPCTypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)Parallel 5V, Series 12VCurrent - Output (Max)Parallel 360mA, Series 60mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapYesPower - MaxInfough HoleMounting TypePrinaude ManagementSter / DimensionPC PinSter / Dimension47.60mm Lx 36.50mm WVoltage - Isolation150VrmsWeightSing VinsSter / Ser (Max)Sing VinsSter / DimensionSing VinsSter / Ser (Max)Sing VinsSte | Category | Transformers |
| SeriesMPCTypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)Parallel 5V, Series 12VCurrent - Output (Max)Parallel 360mA, Series 60mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapYesPower - Max10 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension47.60mm L x 36.50mm WHeight - Seated (Max)500VrmsWonght500Vrms | | Power Transformers |
| TypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)Parallel 5V, Series 12VCurrent - Output (Max)Parallel 360mA, Series 60mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapYesPower - MaxIn VAMounting TypePrinaugh HoleStez / DimensionPC PinSize / Dimension4.760mm L x 36.50mm WHeight - Seated (Max)1500VrmsWinght1500Vrms | Package | - |
| Voltage - PrimaryInformationVoltage - Secondary (Full Load)Parallel 5V, Series 12VCurrent - Output (Max)Parallel 360mA, Series 60mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapYesPower - Max10 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.70mm L x 36.50mm WHeight - Seated (Max)1500VrmsWoitght0.56 lb (254.01g) | Series | MPC |
| Voltage - Secondary (Full Load)Parallel 5V, Series 12VCurrent - Output (Max)Parallel 360mA, Series 60mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapYesPower - Max10 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.70mm WHeight - Seated (Max)1500VrmsVoltage - Isolation55 lb (254.01g) | Туре | Laminated Core |
| Current - Output (Max)Parallel 360mA, Series 60mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapYesPower - Max10 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.70mm L x 36.50mm WHeight - Seated (Max)1500VrmsVoltage - Isolation0.56 lb (254.01g) | Voltage - Primary | 115V |
| Primary Winding(s)SingleSecondary Winding(s)DualCenter TapYesPower - Max10 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension47.60mm L x 36.50mm WHeight - Seated (Max)1500VrmsVoltage - Isolation556 lb (254.01g) | Voltage - Secondary (Full Load) | Parallel 5V, Series 12V |
| Secondary Winding(s)DualCenter TapYesPower - Max10 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension47.60mm L x 36.50mm WHeight - Seated (Max)1500VrmsVoltage - Isolation1500VrmsWeight0.56 lb (254.01g) | Current - Output (Max) | Parallel 360mA, Series 60mA |
| Center TapYesPower - Max10 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension47.60mm L x 36.50mm WHeight - Seated (Max)41.70mmVoltage - Isolation1500VrmsWeight0.56 lb (254.01g) | Primary Winding(s) | Single |
| Power - Max10 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension47.60mm L x 36.50mm WHeight - Seated (Max)41.70mmVoltage - Isolation1500VrmsWeight0.56 lb (254.01g) | Secondary Winding(s) | Dual |
| Nounting TypeThrough HoleTermination StylePC PinSize / Dimension47.60mm L x 36.50mm WHeight - Seated (Max)41.70mmVoltage - Isolation1500VrmsWeight0.56 lb (254.01g) | Center Tap | Yes |
| Termination StylePC PinSize / Dimension47.60mm L x 36.50mm WHeight - Seated (Max)41.70mmVoltage - Isolation1500VrmsWeight0.56 lb (254.01g) | Power - Max | 10 VA |
| Size / Dimension 47.60mm L x 36.50mm W Height - Seated (Max) 41.70mm Voltage - Isolation 1500Vrms Weight 0.56 lb (254.01g) | Mounting Type | Through Hole |
| Height - Seated (Max)41.70mmVoltage - Isolation1500VrmsWeight0.56 lb (254.01g) | Termination Style | PC Pin |
| Voltage - Isolation1500VrmsWeight0.56 lb (254.01g) | Size / Dimension | 47.60mm L x 36.50mm W |
| Weight 0.56 lb (254.01g) | Height - Seated (Max) | 41.70mm |
| | Voltage - Isolation | 1500Vrms |
| Report errors? | Weight | 0.56 lb (254.01g) |
| | | Report errors? |

MPC-X-12 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about MPC-X-12, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com