



MPC5HDW4 Information

Heisener.com

Part Number MPC5HDW4 **Manufacturer** Bivar Inc.

Category Optoelectronics

Panel Indicators, Pilot Lights

Description LED ASSY PNL 5MM HER DIFF 635NM

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MPC5HDW4 Specifications

Manufacturer Part Number MPC5HDW4 Manufacturer Bivar Inc. Category Optoelectronics Panel Indicators, Pilot Lights Package - Series MPC5 Type LED Lamp Color Red Lens Color Red Lens Transparency Diffused Ratings Vf (Typ), If (Max) Voltage 2V Current 30mA Panel Cutout Shape Round Panel Cutout Dimensions 0.32" (8.13mm) Lens Style/Size Round with Domed Top, 5mm (T-1 3/4) Millicandela Rating 30mcd Wavelength - Peak 625nm Viewing Angle 45° Termination Style Wire Leads - 4" (101.60mm) Ingress Protection - Features - Report errors?	•		
Category Optoelectronics Panel Indicators, Pilot Lights Package - Series MPC5 Type LED Lamp Color Red Lens Color Red Lens Transparency Diffused Ratings Vf (Typ), If (Max) Voltage 2V Current 30mA Panel Cutout Shape Round Panel Cutout Dimensions 0.32" (8.13mm) Lens Style/Size Round with Domed Top, 5mm (T-1 3/4) Millicandela Rating 30mcd Wavelength - Peak 625mm Viewing Angle 45° Termination Style Wire Leads - 4" (101.60mm) Ingress Protection - Features -	Manufacturer Part Number	MPC5HDW4	
Package-SeriesMPC5TypeLEDLamp ColorRedLens TransparencyDiffusedRatingsVf (Typ), If (Max)Voltage2VCurrent30mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.32" (8.13mm)Lens Style/SizeRound with Domed Top, 5mm (T-1 3/4)Millicandela Rating30mcdWavelength - Peak625nmViewing Angle45°Termination StyleWire Leads - 4" (101.60mm)Ingress Protection-Features-	Manufacturer	Bivar Inc.	
Package - Series MPC5 Type LED Lamp Color Red Lens Color Red Lens Transparency Diffused Ratings Vf (Typ), If (Max) Voltage 2V Current 30mA Panel Cutout Shape Round Panel Cutout Dimensions 0.32" (8.13mm) Lens Style/Size Round with Domed Top, 5mm (T-1 3/4) Millicandela Rating 30mcd Wavelength - Peak 625nm Viewing Angle 45° Termination Style Wire Leads - 4" (101.60mm) Ingress Protection - Features -	Category	Optoelectronics	
SeriesMPC5TypeLEDLamp ColorRedLens ColorRedLens TransparencyDiffusedRatingsVf (Typ), If (Max)Voltage2VCurrent30mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.32" (8.13mm)Lens Style/SizeRound with Domed Top, 5mm (T-1 3/4)Millicandela Rating30mcdWavelength - Peak625nmViewing Angle45°Termination StyleWire Leads - 4" (101.60mm)Ingress Protection-Features-		Panel Indicators, Pilot Lights	
TypeLEDLamp ColorRedLens ColorRedLens TransparencyDiffusedRatingsVf (Typ), If (Max)Voltage2VCurrent30mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.32" (8.13mm)Lens Style/SizeRound with Domed Top, 5mm (T-1 3/4)Millicandela Rating30mcdWavelength - Peak625nmViewing Angle45°Termination StyleWire Leads - 4" (101.60mm)Ingress Protection-Features-	Package	-	
Lamp Color Lens Color Red Lens Transparency Diffused Ratings Vf (Typ), If (Max) Voltage 2V Current 30mA Panel Cutout Shape Round Panel Cutout Dimensions 0.32" (8.13mm) Lens Style/Size Round with Domed Top, 5mm (T-1 3/4) Millicandela Rating 30mcd Wavelength - Peak 625nm Viewing Angle 45° Termination Style Wire Leads - 4" (101.60mm) Ingress Protection - Features -	Series	MPC5	
Lens ColorRedLens TransparencyDiffusedRatingsVf (Typ), If (Max)Voltage2VCurrent30mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.32" (8.13mm)Lens Style/SizeRound with Domed Top, 5mm (T-1 3/4)Millicandela Rating30mcdWavelength - Peak625nmViewing Angle45°Termination StyleWire Leads - 4" (101.60mm)Ingress Protection-Features-	Туре	LED	
Lens TransparencyDiffusedRatingsVf (Typ), If (Max)Voltage2VCurrent30mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.32" (8.13mm)Lens Style/SizeRound with Domed Top, 5mm (T-1 3/4)Millicandela Rating30mcdWavelength - Peak625nmViewing Angle45°Termination StyleWire Leads - 4" (101.60mm)Ingress Protection-Features-	Lamp Color	Red	
Ratings Vf (Typ), If (Max) Voltage 2V Current 30mA Panel Cutout Shape Round Panel Cutout Dimensions 0.32" (8.13mm) Lens Style/Size Round with Domed Top, 5mm (T-1 3/4) Millicandela Rating 30mcd Wavelength - Peak 625nm Viewing Angle 45° Termination Style Wire Leads - 4" (101.60mm) Ingress Protection Features -	Lens Color	Red	
Voltage2VCurrent30mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.32" (8.13mm)Lens Style/SizeRound with Domed Top, 5mm (T-1 3/4)Millicandela Rating30mcdWavelength - Peak625nmViewing Angle45°Termination StyleWire Leads - 4" (101.60mm)Ingress Protection-Features-	Lens Transparency	Diffused	
Current 30mA Panel Cutout Shape Round Panel Cutout Dimensions 0.32" (8.13mm) Lens Style/Size Round with Domed Top, 5mm (T-1 3/4) Millicandela Rating 30mcd Wavelength - Peak 625nm Viewing Angle 45° Termination Style Wire Leads - 4" (101.60mm) Ingress Protection - Features -	Ratings	Vf (Typ), If (Max)	
Panel Cutout Dimensions 0.32" (8.13mm) Lens Style/Size Round with Domed Top, 5mm (T-1 3/4) Millicandela Rating 30mcd Wavelength - Peak 625nm Viewing Angle 45° Termination Style Wire Leads - 4" (101.60mm) Ingress Protection - Features -	Voltage	2V	
Panel Cutout Dimensions 0.32" (8.13mm) Lens Style/Size Round with Domed Top, 5mm (T-1 3/4) Millicandela Rating 30mcd Wavelength - Peak 625nm Viewing Angle 45° Termination Style Wire Leads - 4" (101.60mm) Ingress Protection - Features -	Current	30mA	
Lens Style/SizeRound with Domed Top, 5mm (T-1 3/4)Millicandela Rating30mcdWavelength - Peak625nmViewing Angle45°Termination StyleWire Leads - 4" (101.60mm)Ingress Protection-Features-	Panel Cutout Shape	Round	
Millicandela Rating Wavelength - Peak 625nm Viewing Angle 45° Termination Style Wire Leads - 4" (101.60mm) Ingress Protection Features -	Panel Cutout Dimensions	0.32" (8.13mm)	
Wavelength - Peak Viewing Angle 45° Termination Style Wire Leads - 4" (101.60mm) Ingress Protection Features -	Lens Style/Size	Round with Domed Top, 5mm (T-1 3/4)	
Viewing Angle45°Termination StyleWire Leads - 4" (101.60mm)Ingress Protection-Features-	Millicandela Rating	30mcd	
Termination Style Wire Leads - 4" (101.60mm) Ingress Protection - Features -	Wavelength - Peak	625nm	
Ingress Protection - Features -	Viewing Angle	45°	
Features -	Termination Style	Wire Leads - 4" (101.60mm)	
	Ingress Protection	-	
Report errors?	Features	-	
		Report e	rrors?

MPC5HDW4 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MPC5HDW4 Payment Methods





















MPC5HDW4 Shipping Methods













If you have any question about MPC5HDW4, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com