

MPI-250-230 Information

Heisener.com

For Reference Only

Part NumberMPI-250-230ManufacturerSignal TransformerCategoryTransformers

Power Transformers

Description XFRMR LAMINATED 250VA CHAS MOUNT

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MPI-250-230 Specifications

Manufacturer Part Number MPI-250-230 Manufacturer Signal Transformer Category Transformers Package - Series MPI Type Laminated Core Voltage - Primary 100V, 115V, 200V, 215V, 230V Voltage - Secondary (Full Load) Parallel 115V, Series 230V Current - Output (Max) Parallel 2.2A, Series 1.1A Primary Winding(s) Dual, Multiple Taps Secondary Winding(s) Dual Center Tap No Power - Max 250 VA Mounting Type Chassis Mount Termination Style Terminal Block Size / Dimension 104.80mm L x 104.90mm W Height - Seated (Max) 98.20mm Voltage - Isolation 4000Vrms Weight 6.8 lbs (3.1kg)		
CategoryTransformersPackage-SeriesMPITypeLaminated CoreVoltage - Primary100V, 115V, 200V, 215V, 230VVoltage - Secondary (Full Load)Parallel 115V, Series 230VCurrent - Output (Max)Parallel 2.2A, Series 1.1APrimary Winding(s)Dual, Multiple TapsSecondary Winding(s)DualCenter TapNoPower - Max250 VAMounting TypeChassis MountTermination StyleTerminal BlockSize / Dimension104.80mm L x 104.90mm WHeight - Seated (Max)98.20mmVoltage - Isolation4000VrmsWeight6.8 lbs (3.1kg)	Manufacturer Part Number	MPI-250-230
Package Series MPI Type Laminated Core Voltage - Primary Voltage - Secondary (Full Load) Parallel 115V, Series 230V Current - Output (Max) Parallel 2.2A, Series 1.1A Primary Winding(s) Dual, Multiple Taps Secondary Winding(s) Dual Center Tap No Power - Max 250 VA Mounting Type Chassis Mount Termination Style Size / Dimension 104.80mm L x 104.90mm W Height - Seated (Max) Voltage - Isolation Weight MPI Ampiration Style Laminated Core Laminated Core Dimension Power Tans MPI Ampirate Laminated Core L	Manufacturer	Signal Transformer
Package - Series MPI Type Laminated Core Voltage - Primary 100V, 115V, 200V, 215V, 230V Voltage - Secondary (Full Load) Parallel 115V, Series 230V Current - Output (Max) Parallel 2.2A, Series 1.1A Primary Winding(s) Dual, Multiple Taps Secondary Winding(s) Dual Center Tap No Power - Max 250 VA Mounting Type Chassis Mount Termination Style Terminal Block Size / Dimension 104.80mm L x 104.90mm W Height - Seated (Max) 98.20mm Voltage - Isolation 4000Vrms Weight 6.8 lbs (3.1kg)	Category	Transformers
SeriesMPITypeLaminated CoreVoltage - Primary100V, 115V, 200V, 215V, 230VVoltage - Secondary (Full Load)Parallel 115V, Series 230VCurrent - Output (Max)Parallel 2.2A, Series 1.1APrimary Winding(s)Dual, Multiple TapsSecondary Winding(s)DualCenter TapNoPower - Max250 VAMounting TypeChassis MountTermination StyleTerminal BlockSize / Dimension104.80mm L x 104.90mm WHeight - Seated (Max)98.20mmVoltage - Isolation4000VrmsWeight6.8 lbs (3.1kg)		Power Transformers
Type Laminated Core Voltage - Primary 100V, 115V, 200V, 215V, 230V Voltage - Secondary (Full Load) Parallel 115V, Series 230V Current - Output (Max) Parallel 2.2A, Series 1.1A Primary Winding(s) Dual, Multiple Taps Secondary Winding(s) Dual Center Tap No Power - Max 250 VA Mounting Type Chassis Mount Termination Style Terminal Block Size / Dimension 104.80mm L x 104.90mm W Height - Seated (Max) 98.20mm Voltage - Isolation 4000Vrms Weight 6.8 lbs (3.1kg)	Package	-
Voltage - Primary Voltage - Secondary (Full Load) Parallel 115V, 200V, 215V, 230V Current - Output (Max) Parallel 2.2A, Series 2.1A Primary Winding(s) Dual, Multiple Taps Secondary Winding(s) Dual Center Tap No Power - Max 250 VA Mounting Type Chassis Mount Termination Style Terminal Block Size / Dimension Height - Seated (Max) Voltage - Isolation Weight 100V, 115V, 200V, 215V, 230V Parallel 1.15V, Series 2.30V Current - Output (Max) Parallel 1.15V, Series 2.30V Parallel 1.15V, 200V, 215V, 230V Parallel 1.15V, 200V, 215V, 230V Parallel 1.15V, Series 2.30V Parallel 1.15V, 200V, 215V, 230V Parallel 1.15V, 200V Parallel 1.15V Parallel 1.15V	Series	MPI
Voltage - Secondary (Full Load) Current - Output (Max) Parallel 2.2A, Series 1.1A Primary Winding(s) Dual, Multiple Taps Secondary Winding(s) Dual Center Tap No Power - Max 250 VA Mounting Type Chassis Mount Termination Style Size / Dimension 104.80mm L x 104.90mm W Height - Seated (Max) Voltage - Isolation Weight Parallel 115V, Series 230V Parallel 2.2A, Series 1.1A Primary Winding(s) Dual No Chassis Mount Terminal Block 104.80mm L x 104.90mm W 4000Vrms 6.8 lbs (3.1kg)	Туре	Laminated Core
Current - Output (Max) Primary Winding(s) Dual, Multiple Taps Secondary Winding(s) Dual Center Tap No Power - Max 250 VA Mounting Type Chassis Mount Termination Style Size / Dimension 104.80mm L x 104.90mm W Height - Seated (Max) Voltage - Isolation Weight Parallel 2.2A, Series 1.1A Dual Paper Chassis Mount Terpination Style Terminal Block Terminal Block 104.80mm L x 104.90mm W 4000Vrms 4000Vrms 6.8 lbs (3.1kg)	Voltage - Primary	100V, 115V, 200V, 215V, 230V
Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max 250 VA Mounting Type Chassis Mount Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Weight Dual, Multiple Taps Dual No 1048 No 1048 104 1048 10	Voltage - Secondary (Full Load)	Parallel 115V, Series 230V
Secondary Winding(s)DualCenter TapNoPower - Max250 VAMounting TypeChassis MountTermination StyleTerminal BlockSize / Dimension104.80mm L x 104.90mm WHeight - Seated (Max)98.20mmVoltage - Isolation4000VrmsWeight6.8 lbs (3.1kg)	Current - Output (Max)	Parallel 2.2A, Series 1.1A
Center TapNoPower - Max250 VAMounting TypeChassis MountTermination StyleTerminal BlockSize / Dimension104.80mm L x 104.90mm WHeight - Seated (Max)98.20mmVoltage - Isolation4000VrmsWeight6.8 lbs (3.1kg)	Primary Winding(s)	Dual, Multiple Taps
Power - Max 250 VA Mounting Type Chassis Mount Termination Style Terminal Block Size / Dimension 104.80mm L x 104.90mm W Height - Seated (Max) 98.20mm Voltage - Isolation 4000Vrms Weight 6.8 lbs (3.1kg)	Secondary Winding(s)	Dual
Mounting Type Chassis Mount Termination Style Terminal Block Size / Dimension 104.80mm L x 104.90mm W Height - Seated (Max) 98.20mm Voltage - Isolation 4000Vrms Weight 6.8 lbs (3.1kg)	Center Tap	No
Termination Style Size / Dimension 104.80mm L x 104.90mm W Height - Seated (Max) 98.20mm Voltage - Isolation 4000Vrms Weight 6.8 lbs (3.1kg)	Power - Max	250 VA
Size / Dimension 104.80mm L x 104.90mm W Height - Seated (Max) 98.20mm Voltage - Isolation 4000Vrms Weight 6.8 lbs (3.1kg)	Mounting Type	Chassis Mount
Height - Seated (Max) Voltage - Isolation Weight 98.20mm 4000Vrms 6.8 lbs (3.1kg)	Termination Style	Terminal Block
Voltage - Isolation 4000Vrms Weight 6.8 lbs (3.1kg)	Size / Dimension	104.80mm L x 104.90mm W
Weight 6.8 lbs (3.1kg)	Height - Seated (Max)	98.20mm
	Voltage - Isolation	4000Vrms
Report errors?	Weight	6.8 lbs (3.1kg)
		Report errors?

MPI-250-230 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MPI-250-230 Payment Methods



















MPI-250-230 Shipping Methods













If you have any question about MPI-250-230, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com