

MPI-300-16 Information

Heisener.com

For Reference Only

Part Number MPI-300-16

Manufacturer Signal Transformer

Category

Transformers **Power Transformers**

Description

XFRMR LAMINATED 300VA CHAS MOUNT

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MPI-300-16 Specifications

Manufacturer Part NumberMPI-300-16ManufacturerSignal TransformerCategoryTransformersPackage-SeriesMPITypeLaminated CoreVoltage - Primary100V, 115V, 200V, 215V, 230VVoltage - Secondary (Full Load)Parallel 8V, Series 16VCurrent - Output (Max)Parallel 37.6A, Series 18.8APrimary Winding(s)Dual, Multiple TapsSecondary Winding(s)DualCenter TapNoPower - Max300 VAMounting TypeChassis MountTermination StyleTerminal BlockSize / Dimension104.80mm L x 113.10mm WHeight - Seated (Max)98.20mm		
CategoryTransformersPackage-SeriesMPITypeLaminated CoreVoltage - Primary100V, 115V, 200V, 215V, 230VVoltage - Secondary (Full Load)Parallel 8V, Series 16VCurrent - Output (Max)Parallel 37.6A, Series 18.8APrimary Winding(s)Dual, Multiple TapsSecondary Winding(s)DualCenter TapNoPower - Max300 VAMounting TypeChassis MountTermination StyleTerminal BlockSize / Dimension104.80mm L x 113.10mm W	Manufacturer Part Number	MPI-300-16
Package - Series MPI Type Laminated Core Voltage - Primary 100V, 115V, 200V, 215V, 230V Voltage - Secondary (Full Load) Parallel 8V, Series 16V Current - Output (Max) Parallel 37.6A, Series 18.8A Primary Winding(s) Dual, Multiple Taps Secondary Winding(s) Dual Center Tap No Power - Max 300 VA Mounting Type Chassis Mount Termination Style Terminal Block Size / Dimension 104.80mm L x 113.10mm W	Manufacturer	Signal Transformer
Package - MPI Type Laminated Core Voltage - Primary 100V, 115V, 200V, 215V, 230V Voltage - Secondary (Full Load) Parallel 8V, Series 16V Current - Output (Max) Parallel 37.6A, Series 18.8A Primary Winding(s) Dual, Multiple Taps Secondary Winding(s) Dual Center Tap No Power - Max 300 VA Mounting Type Chassis Mount Termination Style Terminal Block Size / Dimension 104.80mm L x 113.10mm W	Category	Transformers
Series MPI Type Laminated Core Voltage - Primary 100V, 115V, 200V, 215V, 230V Voltage - Secondary (Full Load) Parallel 8V, Series 16V Current - Output (Max) Parallel 37.6A, Series 18.8A Primary Winding(s) Dual, Multiple Taps Secondary Winding(s) Dual Center Tap No Power - Max 300 VA Mounting Type Chassis Mount Termination Style Terminal Block Size / Dimension 104.80mm L x 113.10mm W		Power Transformers
Type Laminated Core Voltage - Primary 100V, 115V, 200V, 215V, 230V Voltage - Secondary (Full Load) Parallel 8V, Series 16V Current - Output (Max) Parallel 37.6A, Series 18.8A Primary Winding(s) Dual, Multiple Taps Secondary Winding(s) Dual Center Tap No Power - Max 300 VA Mounting Type Chassis Mount Termination Style Terminal Block Size / Dimension 104.80mm L x 113.10mm W	Package	-
Voltage - Primary Voltage - Secondary (Full Load) Parallel 8V, Series 16V Current - Output (Max) Parallel 37.6A, Series 18.8A Primary Winding(s) Dual, Multiple Taps Secondary Winding(s) Dual Center Tap No Power - Max Mounting Type Chassis Mount Termination Style Size / Dimension 104.80mm L x 113.10mm W	Series	MPI
Voltage - Secondary (Full Load) Current - Output (Max) Parallel 8V, Series 16V Parallel 37.6A, Series 18.8A Primary Winding(s) Dual, Multiple Taps Secondary Winding(s) Dual Center Tap No Power - Max 300 VA Mounting Type Chassis Mount Termination Style Size / Dimension Parallel 8V, Series 16V Parallel 37.6A, Series 18.8A Pud, Series 18.	Type	Laminated Core
Current - Output (Max) Primary Winding(s) Dual, Multiple Taps Secondary Winding(s) Dual Center Tap No Power - Max Mounting Type Chassis Mount Termination Style Size / Dimension Parallel 37.6A, Series 18.8A Dual, Multiple Taps No Chassis Mount Termination Style Terminal Block 104.80mm L x 113.10mm W	Voltage - Primary	100V, 115V, 200V, 215V, 230V
Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max Mounting Type Chassis Mount Termination Style Size / Dimension Dual, Multiple Taps Dual No Powal No 104.80mm L x 113.10mm W	Voltage - Secondary (Full Load)	Parallel 8V, Series 16V
Secondary Winding(s)DualCenter TapNoPower - Max300 VAMounting TypeChassis MountTermination StyleTerminal BlockSize / Dimension104.80mm L x 113.10mm W	Current - Output (Max)	Parallel 37.6A, Series 18.8A
Center TapNoPower - Max300 VAMounting TypeChassis MountTermination StyleTerminal BlockSize / Dimension104.80mm L x 113.10mm W	Primary Winding(s)	Dual, Multiple Taps
Power - Max Mounting Type Chassis Mount Termination Style Terminal Block Size / Dimension 104.80mm L x 113.10mm W	Secondary Winding(s)	Dual
Mounting Type Chassis Mount Termination Style Terminal Block Size / Dimension 104.80mm L x 113.10mm W	Center Tap	No
Termination Style Terminal Block Size / Dimension 104.80mm L x 113.10mm W	Power - Max	300 VA
Size / Dimension 104.80mm L x 113.10mm W	Mounting Type	Chassis Mount
	Termination Style	Terminal Block
Height - Seated (Max) 98.20mm	Size / Dimension	104.80mm L x 113.10mm W
	Height - Seated (Max)	98.20mm
Voltage - Isolation 4000Vrms	Voltage - Isolation	4000Vrms
Weight 7.8 lbs (3.5kg)	Weight	7.8 lbs (3.5kg)
Report errors?		Report errors?

MPI-300-16 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MPI-300-16 Payment Methods





















MPI-300-16 Shipping Methods













If you have any question about MPI-300-16, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com