

MPI-400-10 Information

Heisener.com

For Reference Only

Part Number MPI-400-10

Manufacturer Signal Transformer

Category

Transformers **Power Transformers**

Description

XFRMR LAMINATED 400VA CHAS MOUNT

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MPI-400-10 Specifications

Manufacturer Part NumberMPI-400-10ManufacturerSignal TransformerCategoryTransformersPackage-SeriesMPITypeLaminated CoreVoltage - Primary100V, 115V, 200V, 215V, 230VVoltage - Secondary (Full Load)Parallel 5V, Series 10VCurrent - Output (Max)Parallel 80A, Series 40APrimary Winding(s)Dual, Multiple TapsSecondary Winding(s)DualCenter TapNoPower - Max400 VAMounting TypeChassis MountTermination StyleTerminal BlockSize / Dimension104.80mm L x 128.10mm WHeight - Seated (Max)98.20mmVoltage - Isolation4000VrmsWeight9.9 lbs (4.5kg)		
Category Transformers Power Transformers Package - Series MPI Type Laminated Core Voltage - Primary 100V, 115V, 200V, 215V, 230V Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 80A, Series 40A Primary Winding(s) Dual, Multiple Taps Secondary Winding(s) Dual Center Tap No Power - Max 400 VA Mounting Type Chassis Mount Termination Style Terminal Block Size / Dimension 104.80mm L x 128.10mm W Height - Seated (Max) 98.20mm Voltage - Isolation 4000Vrms	Manufacturer Part Number	MPI-400-10
Package Series MPI Type Laminated Core Voltage - Primary Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Primary Winding(s) Dual, Multiple Taps Secondary Winding(s) Dual Center Tap No Power - Max 400 VA Mounting Type Chassis Mount Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Power - Itanian Store Power - Max Autor Chassis Mount Termination Style Size / Dimension 104.80mm L x 128.10mm W Voltage - Isolation Power - Itanian Store Autor Chassis Mount Termination Style Size / Dimension Autor Chassis Mount Autor Chassis Autor Chassis Autor Chassis Autor Chassis Autor Chassis Autor	Manufacturer	Signal Transformer
Package - Series MPI Type Laminated Core Voltage - Primary 100V, 115V, 200V, 215V, 230V Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 80A, Series 40A Primary Winding(s) Dual, Multiple Taps Secondary Winding(s) Dual Center Tap No Power - Max 400 VA Mounting Type Chassis Mount Termination Style Terminal Block Size / Dimension 104.80mm L x 128.10mm W Height - Seated (Max) 98.20mm Voltage - Isolation 4000Vrms	Category	Transformers
Series MPI Type Laminated Core Voltage - Primary 100V, 115V, 200V, 215V, 230V Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 80A, Series 40A Primary Winding(s) Dual, Multiple Taps Secondary Winding(s) Dual Center Tap No Power - Max 400 VA Mounting Type Chassis Mount Termination Style Terminal Block Size / Dimension 104.80mm L x 128.10mm W Height - Seated (Max) 98.20mm Voltage - Isolation 4000Vrms		Power Transformers
Type Laminated Core Voltage - Primary 100V, 115V, 200V, 215V, 230V Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 80A, Series 40A Primary Winding(s) Dual, Multiple Taps Secondary Winding(s) Dual Center Tap No Power - Max 400 VA Mounting Type Chassis Mount Termination Style Terminal Block Size / Dimension 104.80mm L x 128.10mm W Height - Seated (Max) 98.20mm Voltage - Isolation 4000Vrms	Package	-
Voltage - Primary Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 80A, Series 40A Primary Winding(s) Dual, Multiple Taps Secondary Winding(s) Center Tap No Power - Max 400 VA Mounting Type Chassis Mount Termination Style Size / Dimension 104.80mm L x 128.10mm W Height - Seated (Max) Voltage - Isolation 100V, 115V, 200V, 215V, 230V Parallel 80A, Series 40A Parallel 80A, Series 40A Dual, Multiple Taps Chassis Mount Terminal Block 104.80mm L x 128.10mm W 4000Vrms	Series	MPI
Voltage - Secondary (Full Load) Current - Output (Max) Parallel 5V, Series 10V Parallel 80A, Series 40A Primary Winding(s) Dual, Multiple Taps Secondary Winding(s) Center Tap No Power - Max 400 VA Mounting Type Chassis Mount Termination Style Size / Dimension 104.80mm L x 128.10mm W Height - Seated (Max) Voltage - Isolation Parallel 5V, Series 10V Parallel 5V, Series 40A Publication 400 VA	Туре	Laminated Core
Current - Output (Max) Primary Winding(s) Dual, Multiple Taps Secondary Winding(s) Dual Center Tap No Power - Max 400 VA Mounting Type Chassis Mount Termination Style Terminal Block Size / Dimension Height - Seated (Max) Voltage - Isolation Parallel 80A, Series 40A Pual, Multiple Taps Dual Chassis Mount 104.80mm L x 128.10mm W 4000Vrms	Voltage - Primary	100V, 115V, 200V, 215V, 230V
Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max 400 VA Mounting Type Chassis Mount Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Dual, Multiple Taps Dual No 400 VA 400 VA 104.80mm L x 128.10mm W 98.20mm 4000Vrms	Voltage - Secondary (Full Load)	Parallel 5V, Series 10V
Secondary Winding(s) Center Tap No Power - Max 400 VA Mounting Type Chassis Mount Termination Style Terminal Block Size / Dimension 104.80mm L x 128.10mm W Height - Seated (Max) Voltage - Isolation Dual A00 VA 400 VA 400 VA Chassis Mount Terminal Block 104.80mm L x 128.10mm W 4000Vrms	Current - Output (Max)	Parallel 80A, Series 40A
Center Tap No Power - Max 400 VA Mounting Type Chassis Mount Termination Style Terminal Block Size / Dimension 104.80mm L x 128.10mm W Height - Seated (Max) 98.20mm Voltage - Isolation 4000Vrms	Primary Winding(s)	Dual, Multiple Taps
Power - Max Mounting Type Chassis Mount Termination Style Terminal Block Size / Dimension 104.80mm L x 128.10mm W Height - Seated (Max) 98.20mm Voltage - Isolation 4000Vrms	Secondary Winding(s)	Dual
Mounting Type Chassis Mount Termination Style Terminal Block Size / Dimension 104.80mm L x 128.10mm W Height - Seated (Max) 98.20mm Voltage - Isolation 4000Vrms	Center Tap	No
Termination Style Size / Dimension 104.80mm L x 128.10mm W Height - Seated (Max) 98.20mm Voltage - Isolation 4000Vrms	Power - Max	400 VA
Size / Dimension 104.80mm L x 128.10mm W Height - Seated (Max) 98.20mm Voltage - Isolation 4000Vrms	Mounting Type	Chassis Mount
Height - Seated (Max) Voltage - Isolation 98.20mm 4000Vrms	Termination Style	Terminal Block
Voltage - Isolation 4000Vrms	Size / Dimension	104.80mm L x 128.10mm W
	Height - Seated (Max)	98.20mm
Weight 9.9 lbs (4.5kg)	Voltage - Isolation	4000Vrms
\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	Weight	9.9 lbs (4.5kg)
Report errors?		Report errors?

MPI-400-10 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MPI-400-10 Payment Methods



















MPI-400-10 Shipping Methods













If you have any question about MPI-400-10, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com