

MPI-650-28

MPI-650-28 Information



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MPI-650-28 Specifications

ManufacturerSignal TransformerCategoryTransformersPower TransformersPower TransformersPackage-SeriesMPITypeLaminated CoreVoltage - Primary100V, 115V, 200V, 215V, 230VVoltage - Secondary (Full Load)Parallel 14V, Series 28VCurrent - Output (Max)Parallel 46.4A, Series 23.2APrimary Winding(s)Dual, Multiple TapsSecondary Winding(s)DualPower - MaxSo VAMounting TypeChassis MountTermination StyleTerminal BlockSize / Dimension113.30mm L x 119.40mm WHeight - Seated (Max)4000Vrms		
CategoryTransformers Power TransformersPackage-SeriesMPITypeLaminated CoreVoltage - Primary100V, 115V, 200V, 215V, 230VVoltage - Secondary (Full Load)Parallel 14V, Series 28VCurrent - Output (Max)Parallel 46.4A, Series 23.2APrimary Winding(s)Dual, Multiple TapsSecondary Winding(s)DualCenter TapNoPower - Max650 VAMounting TypeChassis MountTermination Style133.30mm L x 119.40mm WSize / Dimension117.80mmVoltage - Isolation4000VrmsWeight15 lbs (6.8kg)	Manufacturer Part Number	MPI-650-28
Power TransformersPackage-SeriesMPITypeLaminated CoreVoltage - Primary100V, 115V, 200V, 215V, 230VVoltage - Secondary (Full Load)Parallel 14V, Series 28VCurrent - Output (Max)Parallel 46.4A, Series 23.2APrimary Winding(s)Dual, Multiple TapsSecondary Winding(s)DualPower - Max650 VAMounting TypeChassis MountTermination StyleTerminal BlockSize / Dimension133.30mm L x 119.40mm WHeight - Seated (Max)4000VrmsWeight15 lbs (6.8kg)	Manufacturer	Signal Transformer
Package-SeriesMPITypeLaminated CoreVoltage - Primary100V, 115V, 200V, 215V, 230VVoltage - Secondary (Full Load)Parallel 14V, Series 28VCurrent - Output (Max)Parallel 46.4A, Series 23.2APrimary Winding(s)Dual, Multiple TapsSecondary Winding(s)DualPower - Max650 VAMounting TypeChassis MountTermination StyleTerminal BlockSize / Dimension133.30mm L x 119.40mm WHeight - Seated (Max)4000VrmsWeightSto Kassis	Category	Transformers
SeriesMPITypeLaminated CoreVoltage - Primary100V, 115V, 200V, 215V, 230VVoltage - Secondary (Full Load)Parallel 14V, Series 28VCurrent - Output (Max)Parallel 46.4A, Series 23.2APrimary Winding(s)Dual, Multiple TapsSecondary Winding(s)DualCenter TapNoPower - Max650 VAMounting TypeChassis MountTermination Style133.30mm L x 119.40mm WHeight - Seated (Max)117.80mmWotage - Isolation510 V/rmsWeight15 lbs (6.8kg)		Power Transformers
TypeLaminated CoreVoltage - Primary100V, 115V, 200V, 215V, 230VVoltage - Secondary (Full Load)Parallel 14V, Series 28VCurrent - Output (Max)Parallel 46.4A, Series 23.2APrimary Winding(s)Dual, Multiple TapsSecondary Winding(s)DualCenter TapNoPower - Max650 VAMounting TypeChassis MountTermination Style133.30mm L x 119.40mm WHeight - Seated (Max)117.80mmWotage - Isolation515 b(6.8kg)	Package	-
Voltage - Primary100V, 115V, 200V, 215V, 230VVoltage - Secondary (Full Load)Parallel 14V, Series 28VCurrent - Output (Max)Parallel 46.4A, Series 23.2APrimary Winding(s)Dual, Multiple TapsSecondary Winding(s)DualCenter TapNoPower - Max650 VAMounting TypeChassis MountTermination Style133.30mm L x 119.40mm WSize / Dimension117.80mmHeight - Seated (Max)15 lbs (6.8kg)	Series	MPI
Voltage - Secondary (Full Load)Parallel 14V, Series 28VCurrent - Output (Max)Parallel 46.4A, Series 23.2APrimary Winding(s)Dual, Multiple TapsSecondary Winding(s)DualCenter TapNoPower - Max650 VAMounting TypeChassis MountTermination StyleTerminal BlockSize / Dimension113.30mm L x 119.40mm WHeight - Seated (Max)4000VrmsWeight15 lbs (6.8kg)	Туре	Laminated Core
Current - Output (Max)Parallel 46.4A, Series 23.2APrimary Winding(s)Dual, Multiple TapsSecondary Winding(s)DualCenter TapNoPower - Max650 VAMounting TypeChassis MountTermination StyleTerminal BlockSize / Dimension133.30mm L x 119.40mm WHeight - Seated (Max)117.80mmVoltage - Isolation4000VrmsWeight15 lbs (6.8kg)	Voltage - Primary	100V, 115V, 200V, 215V, 230V
Primary Winding(s)Dual, Multiple TapsSecondary Winding(s)DualCenter TapNoPower - Max650 VAMounting TypeChassis MountTermination StyleTerminal BlockSize / Dimension133.30mm L x 119.40mm WHeight - Seated (Max)117.80mmVoltage - Isolation4000VrmsWeight15 lbs (6.8kg)	Voltage - Secondary (Full Load)	Parallel 14V, Series 28V
Secondary Winding(s)DualCenter TapNoPower - Max650 VAMounting TypeChassis MountTermination StyleTerminal BlockSize / Dimension133.30mm L x 119.40mm WHeight - Seated (Max)117.80mmVoltage - Isolation4000VrmsWeight15 lbs (6.8kg)	Current - Output (Max)	Parallel 46.4A, Series 23.2A
Center TapNoPower - Max650 VAMounting TypeChassis MountTermination StyleTerminal BlockSize / Dimension133.30mm L x 119.40mm WHeight - Seated (Max)117.80mmVoltage - Isolation4000VrmsWeight15 lbs (6.8kg)	Primary Winding(s)	Dual, Multiple Taps
Power - Max650 VAMounting TypeChassis MountTermination StyleTerminal BlockSize / Dimension133.30mm L x 119.40mm WHeight - Seated (Max)117.80mmVoltage - Isolation4000VrmsWeight15 lbs (6.8kg)	Secondary Winding(s)	Dual
Mounting TypeChassis MountTermination StyleTerminal BlockSize / Dimension133.30mm L x 119.40mm WHeight - Seated (Max)117.80mmVoltage - Isolation4000VrmsWeight15 lbs (6.8kg)	Center Tap	No
Termination StyleTerminal BlockSize / Dimension133.30mm L x 119.40mm WHeight - Seated (Max)117.80mmVoltage - Isolation4000VrmsWeight15 lbs (6.8kg)	Power - Max	650 VA
Size / Dimension 133.30mm L x 119.40mm W Height - Seated (Max) 117.80mm Voltage - Isolation 4000Vrms Weight 15 lbs (6.8kg)	Mounting Type	Chassis Mount
Height - Seated (Max)117.80mmVoltage - Isolation4000VrmsWeight15 lbs (6.8kg)	Termination Style	Terminal Block
Voltage - Isolation4000VrmsWeight15 lbs (6.8kg)	Size / Dimension	133.30mm L x 119.40mm W
Weight 15 lbs (6.8kg)	Height - Seated (Max)	117.80mm
	Voltage - Isolation	4000Vrms
Report errors?	Weight	15 lbs (6.8kg)
		Report errors?

MPI-650-28 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

MPI-650-28 Payment Methods WIRE PayPal WIRE ON ONE WIRE ON THE PAYPAL OF A CONTRACT ON THE ONE OF A CONTRACT ON THE ONE

If you have any question about MPI-650-28, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com