

MPMT10014001CT1

MPMT10014001CT1 Information



For Reference Only

Part Number MPMT10014001CT1
Manufacturer Vishay Thin Film

Category Resistors

Resistor Networks, Arrays

Description RES NTWRK 2 RES MULT OHM TO236-3

Package TO-236-3, SC-59, SOT-23-3

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MPMT10014001CT1 Specifications

Manufacturer Part Number MPMT10014001CT1 Manufacturer Vishay Thin Film Category Resistors Resistor Networks, Arrays Package TO-236-3, SC-59, SOT-23-3 Series MPM Circuit Type Voltage Divider Resistance (Ohms) 1k, 4k Tolerance ±0.25% Number of Resistors 2 Number of Pins 3 Power Per Element 100mW Temperature Coefficient ±25ppm/°C Operating Temperature -55°C ~ 125°C Applications Voltage Divider (TCR Matched) Mounting Type Surface Mount Package / Case TO-236-3, SC-59, SOT-23-3 Supplier Device Package SOT-23 Size / Dimension 0.113" L x 0.051" W (2.86mm x 1.30mm) Height - Seated (Max) 0.040" (1.02mm)		
Category Resistors Package TO-236-3, SC-59, SOT-23-3 Series MPM Circuit Type Voltage Divider Resistance (Ohms) 1k, 4k Tolerance ±0.25% Number of Resistors 2 Number of Pins 3 Power Per Element 100mW Temperature Coefficient ±25ppm/°C Operating Temperature -55°C ~ 125°C Applications Voltage Divider (TCR Matched) Mounting Type Surface Mount Package / Case TO-236-3, SC-59, SOT-23-3 Supplier Device Package SOT-23 Size / Dimension 0.113" L x 0.051" W (2.86mm x 1.30mm) Height - Seated (Max) 0.040" (1.02mm)	Manufacturer Part Number	MPMT10014001CT1
Resistor Networks, Arrays Package TO-236-3, SC-59, SOT-23-3 Series MPM Circuit Type Voltage Divider Resistance (Ohms) 1k, 4k Tolerance ±0.25% Number of Resistors 2 Number of Pins 3 Power Per Element 100mW Temperature Coefficient ±25ppm/°C Operating Temperature -55°C ~ 125°C Applications Voltage Divider (TCR Matched) Mounting Type Surface Mount Package / Case TO-236-3, SC-59, SOT-23-3 Supplier Device Package SOT-23 Size / Dimension 0.113" L x 0.051" W (2.86mm x 1.30mm) Height - Seated (Max) 0.040" (1.02mm)	Manufacturer	Vishay Thin Film
Package TO-236-3, SC-59, SOT-23-3 Series MPM Circuit Type Voltage Divider Resistance (Ohms) 1k, 4k Tolerance ±0.25% Number of Resistors 2 Number of Pins 3 Power Per Element 100mW Temperature Coefficient ±25ppm/°C Operating Temperature -55°C ~ 125°C Applications Voltage Divider (TCR Matched) Mounting Type Surface Mount Package / Case TO-236-3, SC-59, SOT-23-3 Supplier Device Package SOT-23 Size / Dimension 0.113" L x 0.051" W (2.86mm x 1.30mm) Height - Seated (Max) 0.040" (1.02mm)	Category	Resistors
SeriesMPMCircuit TypeVoltage DividerResistance (Ohms)1k, 4kTolerance±0.25%Number of Resistors2Number of Pins3Power Per Element100mWTemperature Coefficient±25ppm/°COperating Temperature-55°C ~ 125°CApplicationsVoltage Divider (TCR Matched)Mounting TypeSurface MountPackage / CaseTO-236-3, SC-59, SOT-23-3Supplier Device PackageSOT-23Size / Dimension0.113" L x 0.051" W (2.86mm x 1.30mm)Height - Seated (Max)0.040" (1.02mm)		Resistor Networks, Arrays
Circuit Type Voltage Divider Resistance (Ohms) 1k, 4k Tolerance ±0.25% Number of Resistors 2 Number of Pins 3 Power Per Element 100mW Temperature Coefficient ±25ppm/°C Operating Temperature -55°C ~ 125°C Applications Voltage Divider (TCR Matched) Mounting Type Surface Mount Package / Case TO-236-3, SC-59, SOT-23-3 Supplier Device Package SOT-23 Size / Dimension 0.113" L x 0.051" W (2.86mm x 1.30mm) Height - Seated (Max) 0.040" (1.02mm)	Package	TO-236-3, SC-59, SOT-23-3
Resistance (Ohms) 1k, 4k Tolerance ±0.25% Number of Resistors 2 Number of Pins 3 Power Per Element 100mW Temperature Coefficient ±25ppm/°C Operating Temperature -55°C ~ 125°C Applications Voltage Divider (TCR Matched) Mounting Type Surface Mount Package / Case TO-236-3, SC-59, SOT-23-3 Supplier Device Package SOT-23 Size / Dimension 0.113" L x 0.051" W (2.86mm x 1.30mm) Height - Seated (Max) 0.040" (1.02mm)	Series	MPM
Tolerance ±0.25% Number of Resistors 2 Number of Pins 3 Power Per Element 100mW Temperature Coefficient ±25ppm/°C Operating Temperature -55°C ~ 125°C Applications Voltage Divider (TCR Matched) Mounting Type Surface Mount Package / Case TO-236-3, SC-59, SOT-23-3 Supplier Device Package SOT-23 Size / Dimension 0.113" L x 0.051" W (2.86mm x 1.30mm) Height - Seated (Max) 0.040" (1.02mm)	Circuit Type	Voltage Divider
Number of Resistors2Number of Pins3Power Per Element100mWTemperature Coefficient±25ppm/°COperating Temperature-55°C ~ 125°CApplicationsVoltage Divider (TCR Matched)Mounting TypeSurface MountPackage / CaseTO-236-3, SC-59, SOT-23-3Supplier Device PackageSOT-23Size / Dimension0.113" L x 0.051" W (2.86mm x 1.30mm)Height - Seated (Max)0.040" (1.02mm)	Resistance (Ohms)	1k, 4k
Number of Pins Power Per Element 100mW Temperature Coefficient ±25ppm/°C Operating Temperature -55°C ~ 125°C Applications Voltage Divider (TCR Matched) Mounting Type Surface Mount Package / Case TO-236-3, SC-59, SOT-23-3 Supplier Device Package SOT-23 Size / Dimension 0.113" L x 0.051" W (2.86mm x 1.30mm) Height - Seated (Max) 0.040" (1.02mm)	Tolerance	±0.25%
Power Per Element Temperature Coefficient ±25ppm/°C Operating Temperature -55°C ~ 125°C Applications Voltage Divider (TCR Matched) Mounting Type Surface Mount Package / Case TO-236-3, SC-59, SOT-23-3 Supplier Device Package SOT-23 Size / Dimension 0.113" L x 0.051" W (2.86mm x 1.30mm) Height - Seated (Max) 0.040" (1.02mm)	Number of Resistors	2
Temperature Coefficient ±25ppm/°C Operating Temperature -55°C ~ 125°C Applications Voltage Divider (TCR Matched) Mounting Type Surface Mount Package / Case TO-236-3, SC-59, SOT-23-3 Supplier Device Package SOT-23 Size / Dimension 0.113" L x 0.051" W (2.86mm x 1.30mm) Height - Seated (Max) 0.040" (1.02mm)	Number of Pins	3
Operating Temperature -55°C ~ 125°C Applications Voltage Divider (TCR Matched) Mounting Type Surface Mount Package / Case TO-236-3, SC-59, SOT-23-3 Supplier Device Package SOT-23 Size / Dimension 0.113" L x 0.051" W (2.86mm x 1.30mm) Height - Seated (Max) 0.040" (1.02mm)	Power Per Element	100mW
Applications Voltage Divider (TCR Matched) Mounting Type Surface Mount Package / Case TO-236-3, SC-59, SOT-23-3 Supplier Device Package SOT-23 Size / Dimension 0.113" L x 0.051" W (2.86mm x 1.30mm) Height - Seated (Max) 0.040" (1.02mm)	Temperature Coefficient	±25ppm/°C
Mounting Type Surface Mount Package / Case TO-236-3, SC-59, SOT-23-3 Supplier Device Package SOT-23 Size / Dimension 0.113" L x 0.051" W (2.86mm x 1.30mm) Height - Seated (Max) 0.040" (1.02mm)	Operating Temperature	-55°C ~ 125°C
Package / Case TO-236-3, SC-59, SOT-23-3 Supplier Device Package SOT-23 Size / Dimension 0.113" L x 0.051" W (2.86mm x 1.30mm) Height - Seated (Max) 0.040" (1.02mm)	Applications	Voltage Divider (TCR Matched)
Supplier Device Package SOT-23 Size / Dimension 0.113" L x 0.051" W (2.86mm x 1.30mm) Height - Seated (Max) 0.040" (1.02mm)	Mounting Type	Surface Mount
Size / Dimension 0.113" L x 0.051" W (2.86mm x 1.30mm) Height - Seated (Max) 0.040" (1.02mm)	Package / Case	TO-236-3, SC-59, SOT-23-3
Height - Seated (Max) 0.040" (1.02mm)	Supplier Device Package	SOT-23
	Size / Dimension	0.113" L x 0.051" W (2.86mm x 1.30mm)
Report errors?	Height - Seated (Max)	0.040" (1.02mm)
		Report errors?

MPMT10014001CT1 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MPMT10014001CT1 Payment Methods



















MPMT10014001CT1 Shipping Methods













If you have any question about MPMT10014001CT1, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com