



MPR3SURC Information

Heisener.com

Part Number MPR3SURC Manufacturer Bivar Inc.

Category Optoelectronics

Panel Indicators, Pilot Lights **Description** IND METAL PNL 3MM ULT RD WTR CLR

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MPR3SURC Specifications

Manufacturer Part Number MPR3SURC Manufacturer Bivar Inc. Category Optoelectronics Panel Indicators, Pilot Lights Package - Series - Type LED Lamp Color Red Lens Color Colorless Lens Transparency Clear Ratings Vf (Typ), If (Max) Voltage 1.8V Current 20mA Panel Cutout Shape Round Panel Cutout Dimensions 0.24" (6.10mm) Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating 200mcd Wavelength - Peak 640nm Viewing Angle 20° Termination Style - Ingress Protection - Features -		
Category Optoelectronics Panel Indicators, Pilot Lights Package - Series - Type LED Lamp Color Red Lens Color Colorless Lens Transparency Clear Ratings Vf (Typ), If (Max) Voltage 1.8V Current 20mA Panel Cutout Shape Round Panel Cutout Dimensions 0.24" (6.10mm) Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating 200mcd Wavelength - Peak 640nm Viewing Angle 20° Termination Style - Ingress Protection - Features -	Manufacturer Part Number	MPR3SURC
Package Series Type LED Lamp Color Red Lens Color Colorless Lens Transparency Clear Ratings Vf (Typ), If (Max) Voltage 1.8V Current 20mA Panel Cutout Dimensions 0.24" (6.10mm) Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating 200mcd Wavelength - Peak 640nm Viewing Angle 20° Termination Style Ingress Protection Features Features Panel Cutous Lights Features Panel Indicators, Pilot Lights - Current Red Round -	Manufacturer	Bivar Inc.
Package - Series - Type LED Lamp Color Red Lens Color Colorless Lens Transparency Clear Ratings Vf (Typ), If (Max) Voltage 1.8V Current 20mA Panel Cutout Shape Round Panel Cutout Dimensions 0.24" (6.10mm) Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating 200mcd Wavelength - Peak 640nm Viewing Angle 20° Termination Style - Ingress Protection - Features -	Category	Optoelectronics
Series-TypeLEDLamp ColorRedLens ColorColorlessLens TransparencyClearRatingsVf (Typ), If (Max)Voltage1.8VCurrent20mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.24" (6.10mm)Lens Style/SizeRound with Domed Top, 3mm (T-1)Millicandela Rating200mcdWavelength - Peak640nmViewing Angle20°Termination Style-Ingress Protection-Features-		Panel Indicators, Pilot Lights
TypeLEDLamp ColorRedLens ColorColorlessLens TransparencyClearRatingsVf (Typ), If (Max)Voltage1.8VCurrent20mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.24" (6.10mm)Lens Style/SizeRound with Domed Top, 3mm (T-1)Millicandela Rating200mcdWavelength - Peak640nmViewing Angle20°Termination Style-Ingress Protection-Features-	Package	-
Lamp Color Lens Color Colorless Lens Transparency Clear Ratings Vf (Typ), If (Max) Voltage 1.8V Current 20mA Panel Cutout Shape Round Panel Cutout Dimensions 0.24" (6.10mm) Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating 200mcd Wavelength - Peak 640nm Viewing Angle 20° Termination Style Ingress Protection Features - Red Colorless Red And And And And And And And And And An	Series	-
Lens ColorColorlessLens TransparencyClearRatingsVf (Typ), If (Max)Voltage1.8VCurrent20mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.24" (6.10mm)Lens Style/SizeRound with Domed Top, 3mm (T-1)Millicandela Rating200mcdWavelength - Peak640nmViewing Angle20°Termination Style-Ingress Protection-Features-	Type	LED
Lens TransparencyClearRatingsVf (Typ), If (Max)Voltage1.8VCurrent20mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.24" (6.10mm)Lens Style/SizeRound with Domed Top, 3mm (T-1)Millicandela Rating200mcdWavelength - Peak640nmViewing Angle20°Termination Style-Ingress Protection-Features-	Lamp Color	Red
Ratings Voltage 1.8V Current 20mA Panel Cutout Shape Round Panel Cutout Dimensions 0.24" (6.10mm) Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating 200mcd Wavelength - Peak 640nm Viewing Angle 20° Termination Style Ingress Protection Features - - - - - - - - - - - - -	Lens Color	Colorless
Voltage 1.8V Current 20mA Panel Cutout Shape Round Panel Cutout Dimensions 0.24" (6.10mm) Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating 200mcd Wavelength - Peak 640nm Viewing Angle 20° Termination Style - Ingress Protection - Features -	Lens Transparency	Clear
Current 20mA Panel Cutout Shape Round Panel Cutout Dimensions 0.24" (6.10mm) Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating 200mcd Wavelength - Peak 640nm Viewing Angle 20° Termination Style - Ingress Protection - Features -	Ratings	Vf (Typ), If (Max)
Panel Cutout Dimensions 0.24" (6.10mm) Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating 200mcd Wavelength - Peak 640nm Viewing Angle 20° Termination Style - Ingress Protection - Features	Voltage	1.8V
Panel Cutout Dimensions O.24" (6.10mm) Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating 200mcd Wavelength - Peak 640nm Viewing Angle 20° Termination Style Ingress Protection Features	Current	20mA
Lens Style/SizeRound with Domed Top, 3mm (T-1)Millicandela Rating200mcdWavelength - Peak640nmViewing Angle20°Termination Style-Ingress Protection-Features-	Panel Cutout Shape	Round
Millicandela Rating200mcdWavelength - Peak640nmViewing Angle20°Termination Style-Ingress Protection-Features-	Panel Cutout Dimensions	0.24" (6.10mm)
Wavelength - Peak Viewing Angle 20° Termination Style Ingress Protection Features 640nm	Lens Style/Size	Round with Domed Top, 3mm (T-1)
Viewing Angle20°Termination Style-Ingress Protection-Features-	Millicandela Rating	200mcd
Termination Style - Ingress Protection - Features -	Wavelength - Peak	640nm
Ingress Protection	Viewing Angle	20°
Features -	Termination Style	-
	Ingress Protection	-
Report errors?	Features	-
		Report errors?

MPR3SURC Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MPR3SURC Payment Methods



















MPR3SURC Shipping Methods













If you have any question about MPR3SURC, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com