

MR041A471JAA

MR041A471JAA Information

For Reference Only	Manufacturer Category Description	MR041A471JAA AVX Corporation Capacitors Ceramic Capacitors CAP CER 470PF 100V NP0 RADIAL Padial	
	Package	Radial For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MR041A471JAA Specifications

AnufacturerAVX CorporationCapacitorsCeramic CapacitorsPackageRadialSeriesCeralam? MRCapacitance470pFColerance±5%Voltage - Rated100VPoperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CPackage / Case-Sailure Rated-August-August-August-Sailure Rated-August-August-Sailure Rate-August-August-August-August-Sailure Rate-August- <th></th> <th></th>		
Capacitors Capacitors Package Radial Capacitance Ceralam? MR Capacitance 470pF Colerance ±5% Voltage - Rated 100V Premperature Coefficient COG, NPO Capacitanos - Applications - Package / Case - Applications General Purpose Package / Case Radial Size / Dimension 0.100" L x 0.090" W (4.83mm x 2.28mm) Height - Seated (Max) - Chrones (Max) - Laberating -	Manufacturer Part Number	MR041A471JAA
Ceramic CapacitorsPackageRadialCapacitanceCeralam? MRCapacitance470pFFolerance±5%Voltage - Rated100VComperature CoefficientCOG, NP0Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Package / CaseRadialSize / Dimension0.190° L x 0.090° W (4.83mm x 2.28mm)Chickness (Max)-Lead Spacing0.100° (2.54mm)	Manufacturer	AVX Corporation
PackageRadialBackageCeralam? MRCapacitance470pFColerance±5%Voltage - Rated100VTemperature CoefficientCOG, NP0Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Failure Rate-Sailure Rate-General PurposeSize / DimensionGisze / Dimension0.190" L x 0.090" W (4.83mm x 2.28mm)Height - Seated (Max)-Chickness (Max)-Lead Spacing0.100" (2.54mm)	Category	Capacitors
Series Ceralam? MR Capacitance 470pF Folerance ±5% Voltage - Rated 100V Femperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Poperating Temperature -55°C ~ 125°C Series - Applications General Purpose Safurge Y Case Radial Avanting Type Through Hole Sakage / Case 0.100° L x 0.090° W (4.83mm x 2.28mm) Height - Seated (Max) - Chickness (Max) - Chickness (Max) 0.100° (2.54mm)		Ceramic Capacitors
Capacitance470pFColerance±5%Voltage - Rated100VComperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CPeatures-Ratings-ApplicationsGeneral PurposePailure Rate-Package / CaseRadialSize / Dimension0.190° L x 0.090° W (4.83mm x 2.28mm)Height - Seated (Max)-Chickness (Max)-Lead Spacing0.100° (2.54mm)	Package	Radial
Folerance±5%Voltage - Rated100VFemperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CSeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Package / CaseRadialSize / Dimension0.100" L x 0.090" W (4.83mm x 2.28mm)Height - Seated (Max)0.200" (5.08mm)Chickness (Max)0.100" (2.54mm)	Series	Ceralam? MR
Voltage - Rated100VFemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CSeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.190° L x 0.090° W (4.83mm x 2.28mm)Height - Seated (Max)-Chickness (Max)0.100° (5.08mm)Lead Spacing0.100° (2.54mm)	Capacitance	470pF
Femperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.190" L x 0.090" W (4.83mm x 2.28mm)Height - Seated (Max)-Chickness (Max)-Lead Spacing0.100" (2.54mm)	Tolerance	$\pm 5\%$
Derating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.190" L x 0.090" W (4.83mm x 2.28mm)Height - Seated (Max)-Chickness (Max)-Lead Spacing0.100" (2.54mm)	Voltage - Rated	100V
Features-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.190" L x 0.090" W (4.83mm x 2.28mm)Height - Seated (Max)-Chickness (Max)-Lead Spacing0.100" (2.54mm)	Temperature Coefficient	C0G, NP0
Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.190" L x 0.090" W (4.83mm x 2.28mm)Height - Seated (Max)-Chickness (Max)-Lead Spacing0.100" (2.54mm)	Operating Temperature	-55°C ~ 125°C
ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.190" L x 0.090" W (4.83mm x 2.28mm)Height - Seated (Max)0.200" (5.08mm)Chickness (Max)-Lead Spacing0.100" (2.54mm)	Features	-
Failure Rate-Mounting TypeThrough HolePackage / CaseRadialBize / Dimension0.190" L x 0.090" W (4.83mm x 2.28mm)Height - Seated (Max)0.200" (5.08mm)Chickness (Max)-Lead Spacing0.100" (2.54mm)	Ratings	-
Mounting TypeThrough HolePackage / CaseRadialPackage / Case0.190" L x 0.090" W (4.83mm x 2.28mm)Bize / Dimension0.200" (5.08mm)Height - Seated (Max)-Chickness (Max)-Lead Spacing0.100" (2.54mm)	Applications	General Purpose
Package / CaseRadialSize / Dimension0.190" L x 0.090" W (4.83mm x 2.28mm)Height - Seated (Max)0.200" (5.08mm)Thickness (Max)-Lead Spacing0.100" (2.54mm)	Failure Rate	-
Size / Dimension 0.190" L x 0.090" W (4.83mm x 2.28mm) Height - Seated (Max) 0.200" (5.08mm) Thickness (Max) - Lead Spacing 0.100" (2.54mm)	Mounting Type	Through Hole
Height - Seated (Max) 0.200" (5.08mm) Chickness (Max) - Lead Spacing 0.100" (2.54mm)	Package / Case	Radial
Chickness (Max) - Lead Spacing 0.100" (2.54mm)	Size / Dimension	0.190" L x 0.090" W (4.83mm x 2.28mm)
Lead Spacing 0.100" (2.54mm)	Height - Seated (Max)	0.200" (5.08mm)
	Thickness (Max)	-
ead Style Straight	Lead Spacing	0.100" (2.54mm)
•	Lead Style	Straight
Report erro		Report errors?

MR041A471JAA Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

MR041A471JAA Payment Methods



MR041A471JAA Shipping Methods



If you have any question about MR041A471JAA, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com