



MR042C471JAA Information



Part Number MR042C471JAA
Manufacturer AVX Corporation
Category Capacitors

Ceramic Capacitors

Description CAP CER 470PF 200V X7R RADIAL

Package Radia

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MR042C471JAA Specifications

Manufacturer Part Number MR042C471JAA Manufacturer AVX Corporation Category Capacitors Package Radial Series Ceralam? MR Capacitance 470pF Tolerance ±5% Voltage - Rated 200V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.190" L x 0.090" W (4.83mm x 2.28mm) Height - Seated (Max) 0.200" (5.08mm) Thickness (Max) - Lead Spacing 0.100" (2.54mm) Lead Style Straight		
Category Capacitors Package Radial Series Ceralam? MR Capacitance 470pF Tolerance ±5% Voltage - Rated 200V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.190" L x 0.090" W (4.83mm x 2.28mm) Height - Seated (Max) 0.200" (5.08mm) Thickness (Max) - Lead Spacing 0.100" (2.54mm) Lead Style Straight	Manufacturer Part Number	MR042C471JAA
Package Radial Series Ceralam? MR Capacitance 470pF Tolerance ±5% Voltage - Rated 200V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.190" L x 0.090" W (4.83mm x 2.28mm) Height - Seated (Max) 0.200" (5.08mm) Thickness (Max) - Lead Spacing 0.100" (2.54mm) Lead Style Straight	Manufacturer	AVX Corporation
Package Radial Series Ceralam? MR Capacitance 470pF Tolerance ±5% Voltage - Rated 200V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.190" L x 0.090" W (4.83mm x 2.28mm) Height - Seated (Max) 0.200" (5.08mm) Thickness (Max) - Lead Spacing 0.100" (2.54mm) Lead Style Straight	Category	Capacitors
Series Ceralam? MR Capacitance 470pF Tolerance ±5% Voltage - Rated 200V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.190" L x 0.090" W (4.83mm x 2.28mm) Height - Seated (Max) 0.200" (5.08mm) Thickness (Max) - Lead Spacing 0.100" (2.54mm) Lead Style Straight		Ceramic Capacitors
Capacitance 470pF Tolerance ±5% Voltage - Rated 200V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.190" L x 0.090" W (4.83mm x 2.28mm) Height - Seated (Max) 0.200" (5.08mm) Thickness (Max) - Lead Spacing 0.100" (2.54mm) Lead Style Straight	Package	Radial
Tolerance ±5% Voltage - Rated 200V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features Ratings Applications General Purpose Failure Rate Mounting Type Through Hole Package / Case Radial Size / Dimension 0.190" L x 0.090" W (4.83mm x 2.28mm) Height - Seated (Max) 0.200" (5.08mm) Thickness (Max) Lead Spacing 0.100" (2.54mm) Lead Style Size / Dimension 0.100" (2.54mm)	Series	Ceralam? MR
Voltage - Rated200VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.190" L x 0.090" W (4.83mm x 2.28mm)Height - Seated (Max)0.200" (5.08mm)Thickness (Max)-Lead Spacing0.100" (2.54mm)Lead StyleStraight	Capacitance	470pF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension Height - Seated (Max) Thickness (Max) - Lead Spacing Lead Style Straight X7R A7R A7R A7R A7R A7R A7R A7R	Tolerance	±5%
Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.190" L x 0.090" W (4.83mm x 2.28mm)Height - Seated (Max)0.200" (5.08mm)Thickness (Max)-Lead Spacing0.100" (2.54mm)Lead StyleStraight	Voltage - Rated	200V
Features Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style Straight	Temperature Coefficient	X7R
Ratings - General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.190" L x 0.090" W (4.83mm x 2.28mm) Height - Seated (Max) 0.200" (5.08mm) Thickness (Max) - Lead Spacing 0.100" (2.54mm) Lead Style Straight	Operating Temperature	-55°C ~ 125°C
Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.190" L x 0.090" W (4.83mm x 2.28mm) Height - Seated (Max) 0.200" (5.08mm) Thickness (Max) - Lead Spacing 0.100" (2.54mm) Lead Style Straight	Features	-
Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.190" L x 0.090" W (4.83mm x 2.28mm) Height - Seated (Max) 0.200" (5.08mm) Thickness (Max) - Lead Spacing 0.100" (2.54mm) Lead Style Straight	Ratings	-
Mounting Type Through Hole Package / Case Radial Size / Dimension 0.190" L x 0.090" W (4.83mm x 2.28mm) Height - Seated (Max) 0.200" (5.08mm) Thickness (Max) - Lead Spacing 0.100" (2.54mm) Lead Style Straight	Applications	General Purpose
Package / Case Radial Size / Dimension 0.190" L x 0.090" W (4.83mm x 2.28mm) Height - Seated (Max) 0.200" (5.08mm) Thickness (Max) - Lead Spacing 0.100" (2.54mm) Lead Style Straight	Failure Rate	-
Size / Dimension 0.190" L x 0.090" W (4.83mm x 2.28mm) Height - Seated (Max) 0.200" (5.08mm) Thickness (Max) - Lead Spacing 0.100" (2.54mm) Lead Style Straight	Mounting Type	Through Hole
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style 0.200" (5.08mm) - Under Control of the seated (Max) Straight	Package / Case	Radial
Thickness (Max) Lead Spacing 0.100" (2.54mm) Lead Style Straight	Size / Dimension	0.190" L x 0.090" W (4.83mm x 2.28mm)
Lead Spacing 0.100" (2.54mm) Lead Style Straight	Height - Seated (Max)	0.200" (5.08mm)
Lead Style Straight	Thickness (Max)	-
	Lead Spacing	0.100" (2.54mm)
	Lead Style	Straight
Report errors?		Report errors?

MR042C471JAA Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MR042C471JAA Payment Methods





















MR042C471JAA Shipping Methods













If you have any question about MR042C471JAA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com