

MR045C103MAA

MR045C103MAA Information

	Part Number	MR045C103MAA	
For Reference Only	Manufacturer	AVX Corporation	
	Category	Capacitors Ceramic Capacitors	1227
	Description	CAP CER 10000PF 50V X7R RADIAL	19667-73
	Package	Radial	一合行力的
		For the pricing/inventory/lead time, please contact us	
		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MR045C103MAA Specifications

ManufacturerAVX CorporationCapacitorsCaranic CapacitorsPackageRadialSeriesCeralam? MRCapacitance10000pFTolerance±20%Voltage - Rated50VTomperature Coefficient50°C ~ 125°C ~ 125°CPactangs-Ratings-ApplicationsGeneral PurposeFailure Rate-ApplicationsGeneral PurposeFailure Rate-Mounting TypeNicoly HolePackage / CaseRadialSize / Dimension0.100" (5.08mm)Height - Seated (Max)0.200" (5.08mm)Thickness (Max)0.100" (2.54mm)		
CapacitorsPackageRadialPackageRadialSeriesCeralm? MRCapacitors10000pFCapacitance±20%Tolerance±20%Voltage - Rated50VOperating Temperature CoefficientX7ROperating Temperature-55°C ~ 125°CPatters-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.100" (L x 0.090" W (4.83mm x 2.28mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.100" (2.54mm)Lead StyleStraight	Manufacturer Part Number	MR045C103MAA
Ceramic CapacitorsPackageRadialSeriesCeralam? MRCapacitance10000pFTolerance±20%Voltage - Rated50VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.100" (L x 0.090" W (4.83mm x 2.28mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.100" (2.54mm)Lead StyleStraight	Manufacturer	AVX Corporation
PackageRadialSeriesCeralam? MRCapacitance10000pFTolerance±20%Voltage - Rated50VTomperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / Case.190° L x 0.090° W (4.83mm x 2.28mm)Size / Dimension0.100° (5.08mm)Height - Seated (Max)-Lead SpacingStraight	Category	Capacitors
Series Ceralam? MR Capacitance 10000pF Tolerance ±20% Voltage - Rated 50V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Size / Dimension 0.190° L x 0.090° W (4.83mm x 2.28mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing 0.100° (2.54mm) Lead Style Straight		Ceramic Capacitors
Capacitance10000pFTolerance±20%Voltage - Rated50VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CPeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeRadialSize / Dimension0.100" L x 0.009" W (4.83mm x 2.28mm)Height - Seated (Max)0.200" (5.08mm)Thickness (Max)0.100" (2.54mm)Lead SpacingSriaght	Package	Radial
Tolerance±20%Voltage - Rated50VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.100" (± x 0.090" W (4.83mm x 2.28mm)Height - Seated (Max)-Thickness (Max)-Lead StyleStraight	Series	Ceralam? MR
Voltage - Rated50VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.100" L x 0.090" W (4.83mm x 2.28mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.100" (2.54mm)Lead StyleStraight	Capacitance	10000pF
Temperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.190" L x 0.090" W (4.83mm x 2.28mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.100" (2.54mm)Lead StyleStraight	Tolerance	$\pm 20\%$
Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.190" L x 0.090" W (4.83mm x 2.28mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.100" (2.54mm)Lead StyleStraight	Voltage - Rated	50V
Features-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.190" L x 0.090" W (4.83mm x 2.28mm)Height - Seated (Max)0.200" (5.08mm)Thickness (Max)-Lead Spacing0.100" (2.54mm)Kead StyleStraight	Temperature Coefficient	X7R
Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.190" L x 0.090" W (4.83mm x 2.28mm)Height - Seated (Max)0.200" (5.08mm)Thickness (Max)-Lead Spacing0.100" (2.54mm)Kead StyleStraight	Operating Temperature	-55°C ~ 125°C
ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.190" L x 0.090" W (4.83mm x 2.28mm)Height - Seated (Max)0.200" (5.08mm)Thickness (Max)-Lead Spacing0.100" (2.54mm)Lead StyleStraight	Features	-
Failure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.190" L x 0.090" W (4.83mm x 2.28mm)Height - Seated (Max)0.200" (5.08mm)Thickness (Max)-Lead Spacing0.100" (2.54mm)Lead StyleStraight	Ratings	-
Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.190" L x 0.090" W (4.83mm x 2.28mm)Height - Seated (Max)0.200" (5.08mm)Thickness (Max)-Lead Spacing0.100" (2.54mm)Lead StyleStraight	Applications	General Purpose
Package / CaseRadialSize / Dimension0.190" L x 0.090" W (4.83mm x 2.28mm)Height - Seated (Max)0.200" (5.08mm)Thickness (Max)-Lead Spacing0.100" (2.54mm)Lead StyleStraight	Failure Rate	-
Size / Dimension 0.190" L x 0.090" W (4.83mm x 2.28mm) Height - Seated (Max) 0.200" (5.08mm) Thickness (Max) - Lead Spacing 0.100" (2.54mm) Lead Style Straight	Mounting Type	Through Hole
Height - Seated (Max)0.200" (5.08mm)Thickness (Max)-Lead Spacing0.100" (2.54mm)Lead StyleStraight	Package / Case	Radial
Thickness (Max)-Lead Spacing0.100" (2.54mm)Lead StyleStraight	Size / Dimension	0.190" L x 0.090" W (4.83mm x 2.28mm)
Lead Spacing0.100" (2.54mm)Lead StyleStraight	Height - Seated (Max)	0.200" (5.08mm)
Lead Style Straight	Thickness (Max)	-
	Lead Spacing	0.100" (2.54mm)
Report errors?	Lead Style	Straight
		Report errors?

MR045C103MAA Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

MR045C103MAA Payment Methods



MR045C103MAA Shipping Methods



If you have any question about MR045C103MAA, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com