

MR2520LX

MR2520LX Information

www.Cener.com	Part Number Manufacturer Category Description Package	MR2520LX ON Semiconductor Circuit Protection TVS - Diodes TVS DIODE 23VWM AXIAL Button, Axial For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MR2520LX Specifications

ManufacturerON SemiconductorCategoryCircuit Protection TVS - DiodesPackageButton, AxialPackageButton, AxialSeries-TypeZenerUndirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)24V (Max)Voltage - Breakdown (Min)-Voltage - Clamping (Max) @ Ipp-Current - Peak Pulse (10/1000µs)-Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-Power Quest @ Frequency-Appleace @ Frequency-Appleace @ Frequency-Appleace @ Frequency-Mounting Type-Package / CaseButton, AxialSupplier Device PackageMicrode Button, Axial	-	
CategoryCircuit ProtectionTVS - DiodesPackageButton, AxialSeries-TypeZenerUndirectional Channels1Bidirectional Channels-Soriege - Reverse Standoff (Typ)23V (Max)Voltage - Reverse Standoff (Typ)24VVoltage - Clamping (Max) @ Ipp-Current - Peak Pulse (10/100µs)-Power Line ProtectionNoApplicationsS00W (2.5kW)Capacitance @ Frequency-Capacitance @ Frequency-Operating Temperature-Package / CaseButton, AxialSupplier Device PackageButton, Axial	Manufacturer Part Number	MR2520LX
TVS - DiodesPackageButton, AxialSeries-TypeZenerUnidirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)23V (Max)Voltage - Breakdown (Min)24VVoltage - Clamping (Max) @ Ipp-Current - Peak Pulse (10/1000µs)-Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-65°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseButton, AxialSupplier Device PackageMicrode Button	Manufacturer	ON Semiconductor
PackageButton, AxialSeries-TypeZenerUnidirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)23V (Max)Voltage - Breakdown (Min)24VVoltage - Clamping (Max) @ Ipp-Current - Peak Pulse (10/1000µs)-Power - Peak Pulse2500W (2.5kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-65°C ~ 175°C (TJ)Mounting TypeButton, AxialPackage / CaseButton, AxialSupplier Device PackageMicrode Button	Category	Circuit Protection
Series-TypeZenerUnidirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)23V (Max)Voltage - Breakdown (Min)24VVoltage - Clamping (Max) @ Ipp-Current - Peak Pulse (10/1000µs)-Power - Peak Pulse2500W (2.5kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Type-Package / CaseButton, AxialSupplier Device PackageMicrode Button		TVS - Diodes
TypeZenerUnidirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)23V (Max)Voltage - Breakdown (Min)24VVoltage - Clamping (Max) @ Ipp-Voltage - Clamping (Max) @ Ipp-Power - Peak Pulse (10/1000µs)-Power - Peak Pulse2500W (2.5kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-65°C ~ 175°C (TJ)Mounting TypeButton, AxialPackage / CaseButton, AxialSupplier Device PackageMicrode Button	Package	Button, Axial
PrePreUnidirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)23V (Max)Voltage - Breakdown (Min)24VVoltage - Clamping (Max) @ Ipp-Current - Peak Pulse (10/1000µs)-Power - Peak Pulse (10/100µs)S00W (2.5kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-5°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseButton, AxialSupplier Device PackageMicrode Button	Series	_
Bidirectional Channels-Woltage - Reverse Standoff (Typ)23V (Max)Voltage - Breakdown (Min)24VVoltage - Clamping (Max) @ Ipp-Current - Peak Pulse (10/1000µs)-Power - Peak Pulse (10/1000µs)2500W (2.5kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-65°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseButton, AxialSupplier Device PackageMicrode Button	Туре	Zener
Voltage - Reverse Standoff (Typ)23V (Max)Voltage - Breakdown (Min)24VVoltage - Clamping (Max) @ Ipp-Current - Peak Pulse (10/1000µs)-Power - Peak Pulse (10/1000µs)2500W (2.5kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-65°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseButton, AxialSupplier Device PackageMicrode Button	Unidirectional Channels	1
Voltage - Breakdown (Min)24VVoltage - Clamping (Max) @ Ipp-Current - Peak Pulse (10/1000µs)-Power - Peak Pulse (10/1000µs)2500W (2.5kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-65°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseButton, AxialSupplier Device PackageMicrode Button	Bidirectional Channels	-
Voltage - Clamping (Max) @ Ipp-Current - Peak Pulse (10/1000µs)-Power - Peak Pulse2500W (2.5kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-65°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseButton, AxialSupplier Device PackageMicrode Button	Voltage - Reverse Standoff (Typ)	23V (Max)
Current - Peak Pulse (10/1000µs)-Power - Peak Pulse2500W (2.5kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-65°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseButton, AxialSupplier Device PackageMicrode Button	Voltage - Breakdown (Min)	24V
Power - Peak Pulse2500W (2.5kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-65°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseButton, AxialSupplier Device PackageMicrode Button	Voltage - Clamping (Max) @ Ipp	-
Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-65°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseButton, AxialSupplier Device PackageMicrode Button	Current - Peak Pulse (10/1000µs)	-
ApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-65°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseButton, AxialSupplier Device PackageMicrode Button	Power - Peak Pulse	2500W (2.5kW)
Capacitance @ Frequency-Operating Temperature-65°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseButton, AxialSupplier Device PackageMicrode Button	Power Line Protection	No
Operating Temperature-65°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseButton, AxialSupplier Device PackageMicrode Button	Applications	General Purpose
Mounting TypeThrough HolePackage / CaseButton, AxialSupplier Device PackageMicrode Button	Capacitance @ Frequency	-
Package / CaseButton, AxialSupplier Device PackageMicrode Button	Operating Temperature	-65°C ~ 175°C (TJ)
Supplier Device Package Microde Button	Mounting Type	Through Hole
	Package / Case	Button, Axial
Report errors?	Supplier Device Package	Microde Button
		Report errors?

MR2520LX Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

MR2520LX Payment Methods WIRE transfer PayPal Methods MR2520LX Shipping Methods MR2520LX Shipping Methods MR2520LX Shipping Methods

If you have any question about MR2520LX, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com