



MRT 2.5AMMO Information



For Reference Only

Part NumberMRT 2.5AMMOManufacturerBel Fuse Inc.CategoryCircuit Protection

Fuses

Description FUSE BOARD MOUNT 2.5A 250VAC RAD

Package Radial, Can, Vertical

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MRT 2.5AMMO Specifications

| Manufacturer Part NumberMRT 2.5AMMOManufacturerBel Fuse Inc.CategoryCircuit ProtectionFusesPackagePackageRadial, Can, VerticalSeriesMRTFuse TypeBoard Mount (Cartridge Style Excluded)Current Rating2.5AVoltage Rating - AC250VVoltage Rating - DC-Response TimeSlowPackage / CaseRadial, Can, VerticalMounting TypeThrough HoleBreaking Capacity @ Rated Voltage35AMelting 12t37ApprovalsCCC, CE, CSA, cURus, SEMKO, VDEOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.329" Dia x 0.303" H (8.35mm x 7.70mm) | • | |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------|-----------------------------------------|
| Category Circuit Protection Fuses Package Radial, Can, Vertical MRT Fuse Type Board Mount (Cartridge Style Excluded) Current Rating 2.5A Voltage Rating - AC Voltage Rating - DC Response Time Slow Package / Case Radial, Can, Vertical Mounting Type Through Hole Breaking Capacity @ Rated Voltage Breaking Capacity @ Rated Voltage Melting I2t Approvals CCC, CE, CSA, cURus, SEMKO, VDE Operating Temperature -55°C ~ 125°C Color - Size / Dimension Circuit Protection Indicates Radial, Can, Vertical Aprovals CCC, CE, CSA, cURus, SEMKO, VDE | Manufacturer Part Number | MRT 2.5AMMO |
| Fuses Package Radial, Can, Vertical Series MRT Fuse Type Board Mount (Cartridge Style Excluded) Current Rating 2.5A Voltage Rating - AC Voltage Rating - DC - Response Time Slow Package / Case Radial, Can, Vertical Mounting Type Through Hole Breaking Capacity @ Rated Voltage Breaking Capacity @ Rated Voltage CCC, CE, CSA, cURus, SEMKO, VDE Operating Temperature -55°C ~ 125°C Color - Size / Dimension Radial, Can, Vertical -55°C ~ 125°C | Manufacturer | Bel Fuse Inc. |
| Package Radial, Can, Vertical Series MRT Fuse Type Board Mount (Cartridge Style Excluded) Current Rating 2.5A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Slow Package / Case Radial, Can, Vertical Mounting Type Through Hole Breaking Capacity @ Rated Voltage 35A Melting I2t 37 Approvals CCC, CE, CSA, cURus, SEMKO, VDE Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.329" Dia x 0.303" H (8.35mm x 7.70mm) | Category | Circuit Protection |
| Series MRT Fuse Type Board Mount (Cartridge Style Excluded) Current Rating 2.5A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Slow Package / Case Radial, Can, Vertical Mounting Type Through Hole Breaking Capacity @ Rated Voltage 35A Melting 12t 37 Approvals CCC, CE, CSA, cURus, SEMKO, VDE Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.329" Dia x 0.303" H (8.35mm x 7.70mm) | | Fuses |
| Fuse Type Current Rating 2.5A Voltage Rating - AC Voltage Rating - DC Response Time Slow Package / Case Radial, Can, Vertical Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting I2t Approvals Operating Temperature CCC, CE, CSA, cURus, SEMKO, VDE Operating Temperature -55°C ~ 125°C Color Size / Dimension Board Mount (Cartridge Style Excluded) 2.5A Solw Apologous Accordance -50°C 250V Color Color -35°C ~ 125°C -329" Dia x 0.303" H (8.35mm x 7.70mm) | Package | Radial, Can, Vertical |
| Current Rating Voltage Rating - AC 250V Voltage Rating - DC Response Time Slow Package / Case Radial, Can, Vertical Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting I2t Approvals CCC, CE, CSA, cURus, SEMKO, VDE Operating Temperature -55°C ~ 125°C Color Size / Dimension 2.5A 250V Color 250V Color 250V Color 250V Color 250V Color 250V Color 2500 2500 2500 2500 2500 Color | Series | MRT |
| Voltage Rating - AC Voltage Rating - DC Response Time Slow Package / Case Radial, Can, Vertical Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting 12t Approvals CCC, CE, CSA, cURus, SEMKO, VDE Operating Temperature -55°C ~ 125°C Color Size / Dimension 250V A provide Capacity 250V Color - Size / Dimension 250V Addition 12t Control 12t Cont | Fuse Type | Board Mount (Cartridge Style Excluded) |
| Voltage Rating - DC Response Time Slow Package / Case Radial, Can, Vertical Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting I2t Approvals CCC, CE, CSA, cURus, SEMKO, VDE Operating Temperature Color -Size / Dimension -Size / Dimension Slow Radial, Can, Vertical Can, Vertical Can, Vertical CTC, CE, CSA, CURUS Sian Approvals CCC, CE, CSA, cURUS COC, CE, CSA, CURUS | Current Rating | 2.5A |
| Response Time Package / Case Radial, Can, Vertical Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting I2t Approvals CCC, CE, CSA, cURus, SEMKO, VDE Operating Temperature -55°C ~ 125°C Color Size / Dimension Slow Radial, Can, Vertical Characteristics Radial, Can, Vertical Through Hole 35A CCC, CE, CSA, cURus, SEMKO, VDE -55°C ~ 125°C - 125°C | Voltage Rating - AC | 250V |
| Package / Case Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting I2t Approvals CCC, CE, CSA, cURus, SEMKO, VDE Operating Temperature Color Size / Dimension Radial, Can, Vertical 85A 95A CCC, CE, CSA, cURus, SEMKO, VDE -55°C ~ 125°C 0.329" Dia x 0.303" H (8.35mm x 7.70mm) | Voltage Rating - DC | - |
| Mounting Type Breaking Capacity @ Rated Voltage 35A Melting I2t 37 Approvals CCC, CE, CSA, cURus, SEMKO, VDE Operating Temperature -55°C ~ 125°C Color Size / Dimension CNA 0.329" Dia x 0.303" H (8.35mm x 7.70mm) | Response Time | Slow |
| Breaking Capacity @ Rated Voltage Melting I2t Approvals CCC, CE, CSA, cURus, SEMKO, VDE Operating Temperature -55°C ~ 125°C Color Size / Dimension 0.329" Dia x 0.303" H (8.35mm x 7.70mm) | Package / Case | Radial, Can, Vertical |
| Melting I2t37ApprovalsCCC, CE, CSA, cURus, SEMKO, VDEOperating Temperature -55° C $\sim 125^{\circ}$ CColor-Size / Dimension 0.329° Dia x 0.303° H (8.35 mm x 7.70 mm) | Mounting Type | Through Hole |
| Approvals CCC, CE, CSA, cURus, SEMKO, VDE Operating Temperature -55°C ~ 125°C Color Size / Dimension 0.329" Dia x 0.303" H (8.35mm x 7.70mm) | Breaking Capacity @ Rated Voltage | 35A |
| Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.329" Dia x 0.303" H (8.35mm x 7.70mm) | Melting I2t | 37 |
| Color - Color | Approvals | CCC, CE, CSA, cURus, SEMKO, VDE |
| Size / Dimension 0.329" Dia x 0.303" H (8.35mm x 7.70mm) | Operating Temperature | -55°C ~ 125°C |
| | Color | - |
| Report errors? | Size / Dimension | 0.329" Dia x 0.303" H (8.35mm x 7.70mm) |
| | | Report errors? |

MRT 2.5AMMO Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MRT 2.5AMMO Payment Methods



















MRT 2.5AMMO Shipping Methods













If you have any question about MRT 2.5AMMO, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com