



MS17347R24C22P Information

Heisener.com

Part Number MS17347R24C22P

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 4POS JAM NUT PIN

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MS17347R24C22P Specifications

Manufacturer Part Number MS17347R24C22P Manufacturer Amphenol Industrial Operations Category Connectors, Interconnects Package - Series Military, MIL-DTL-22992 Connector Type Receptacle, Male Pins Number of Positions 4 Shell Size - Insert 24-22 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Conductive Cadmium Plated Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating - Report errors?		
CategoryConnectors, InterconnectsPackage-SeriesMilitary, MIL-DTL-22992Connector TypeReceptacle, Male PinsNumber of Positions4Shell Size - Insert24-22Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Conductive Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Manufacturer Part Number	MS17347R24C22P
Package-SeriesMilitary, MIL-DTL-22992Connector TypeReceptacle, Male PinsNumber of Positions4Shell Size - Insert24-22Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Conductive Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Manufacturer	Amphenol Industrial Operations
Package-SeriesMilitary, MIL-DTL-22992Connector TypeReceptacle, Male PinsNumber of Positions4Shell Size - Insert24-22Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Conductive Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Category	Connectors, Interconnects
Series Military, MIL-DTL-22992 Connector Type Receptacle, Male Pins Number of Positions 4 Shell Size - Insert 24-22 Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Conductive Cadmium Plated Contact Finish Silver Features Voltage - Rated 900VAC, 1250VDC Current Rating		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions4Shell Size - Insert24-22Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Conductive Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Package	-
Number of Positions Shell Size - Insert 24-22 Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Conductive Cadmium Plated Contact Finish Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Series	Military, MIL-DTL-22992
Shell Size - Insert 24-22 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Conductive Cadmium Plated Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Connector Type	Receptacle, Male Pins
Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Conductive Cadmium Plated Contact Finish Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Number of Positions	4
Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Conductive Cadmium Plated Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Shell Size - Insert	24-22
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Conductive Cadmium Plated Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Shell Size, MIL	-
Fastening Type Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating Threaded N (Normal) Aluminum, Conductive Cadmium Plated Silver - - - - - - - - - - - - -	Mounting Type	Panel Mount, Bulkhead - Front Side Nut
Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Conductive Cadmium Plated Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Termination	Solder Cup
Ingress Protection Waterproof Shell Material, Finish Aluminum, Conductive Cadmium Plated Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Fastening Type	Threaded
Shell Material, Finish Contact Finish Silver Features - Voltage - Rated Current Rating Aluminum, Conductive Cadmium Plated Silver - - - - - - - - - - - - -	Orientation	N (Normal)
Contact Finish Features - Voltage - Rated Current Rating Silver - Current Rating	Ingress Protection	Waterproof
Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Shell Material, Finish	Aluminum, Conductive Cadmium Plated
Voltage - Rated 900VAC, 1250VDC Current Rating -	Contact Finish	Silver
Current Rating -	Features	-
	Voltage - Rated	900VAC, 1250VDC
Report errors?	Current Rating	-
		Report errors?

MS17347R24C22P Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MS17347R24C22P Payment Methods



















MS17347R24C22P Shipping Methods













If you have any question about MS17347R24C22P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com