



#### MS17347R24C22S Information

Heisener.com

Part Number MS17347R24C22S

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

Circular Connectors

**Description** CONN RCPT 4POS JAM NUT SKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **MS17347R24C22S Specifications**

Manufacturer Part Number       MS17347R24C22S         Manufacturer       Amphenol Industrial Operations         Category       Connectors, Interconnects         Package       -         Series       Military, MIL-DTL-22992         Connector Type       Receptacle, Female Sockets         Number of Positions       4         Shell Size - Insert       24-22         Shell Size, MIL       -         Mounting Type       Panel Mount, Bulkhead - Front Side Nut         Termination       Solder Cup         Fastening Type       Threaded         Orientation       N (Normal)         Ingress Protection       Waterproof         Shell Material, Finish       Aluminum, Conductive Cadmium Plated         Contact Finish       Silver         Features       -         Voltage - Rated       900VAC, 1250VDC         Current Rating       -		
CategoryConnectors, InterconnectsPackage-SeriesMilitary, MIL-DTL-22992Connector TypeReceptacle, Female SocketsNumber of Positions4Shell Size - Insert24-22Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Conductive Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Manufacturer Part Number	MS17347R24C22S
Package-SeriesMilitary, MIL-DTL-22992Connector TypeReceptacle, Female SocketsNumber of Positions4Shell Size - Insert24-22Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Conductive Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Manufacturer	Amphenol Industrial Operations
Package - Military, MIL-DTL-22992 Connector Type Receptacle, Female Sockets Number of Positions 4 Shell Size - Insert 24-22 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Conductive Cadmium Plated Contact Finish Silver Features - Woltage - Rated Outent Rating - OnoWAC, 1250VDC Current Rating - Onower Administration Silver	Category	Connectors, Interconnects
Series Military, MIL-DTL-22992 Connector Type Receptacle, Female Sockets Number of Positions 4 Shell Size - Insert 24-22 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Conductive Cadmium Plated Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating -		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions4Shell Size - Insert24-22Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Conductive Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Package	-
Number of Positions  Shell Size - Insert  24-22  Shell Size, MIL  Mounting Type  Panel Mount, Bulkhead - Front Side Nut  Termination  Solder Cup  Fastening Type  Threaded  Orientation  N (Normal)  Ingress Protection  Waterproof  Shell Material, Finish  Aluminum, Conductive Cadmium Plated  Contact Finish  Silver  Features  -  Voltage - Rated  900VAC, 1250VDC  Current Rating  -	Series	Military, MIL-DTL-22992
Shell Size - Insert 24-22 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Conductive Cadmium Plated Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Connector Type	Receptacle, Female Sockets
Shell Size, MIL  Mounting Type Panel Mount, Bulkhead - Front Side Nut  Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Conductive Cadmium Plated Contact Finish Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Number of Positions	4
Mounting Type Panel Mount, Bulkhead - Front Side Nut  Termination Solder Cup  Fastening Type Threaded  Orientation N (Normal)  Ingress Protection Waterproof  Shell Material, Finish Aluminum, Conductive Cadmium Plated  Contact Finish Silver  Features -  Voltage - Rated 900VAC, 1250VDC  Current Rating -	Shell Size - Insert	24-22
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Conductive Cadmium Plated Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Shell Size, MIL	-
Fastening Type  Orientation  N (Normal)  Ingress Protection  Waterproof  Shell Material, Finish  Contact Finish  Silver  Features  -  Voltage - Rated  900VAC, 1250VDC  Current Rating  Threaded  N (Normal)  N (Normal)  Aluminum, Conductive Cadmium Plated  Silver  -  -  -  -  -  -  -  -  -  -  -  -  -	Mounting Type	Panel Mount, Bulkhead - Front Side Nut
Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Conductive Cadmium Plated Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Termination	Solder Cup
Ingress Protection  Waterproof  Shell Material, Finish  Aluminum, Conductive Cadmium Plated  Contact Finish  Silver  Features  -  Voltage - Rated  900VAC, 1250VDC  Current Rating  -	Fastening Type	Threaded
Shell Material, Finish  Contact Finish  Silver  Features  - Voltage - Rated  Current Rating  Aluminum, Conductive Cadmium Plated  Silver  -  -  -  -  -  -  -  -  -  -  -  -  -	Orientation	N (Normal)
Contact Finish  Features  - Voltage - Rated  Current Rating  Silver  -  -  -  -  -  -  -  -  -  -  -  -  -	Ingress Protection	Waterproof
Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Shell Material, Finish	Aluminum, Conductive Cadmium Plated
Voltage - Rated 900VAC, 1250VDC Current Rating -	Contact Finish	Silver
Current Rating -	Features	-
	Voltage - Rated	900VAC, 1250VDC
	Current Rating	-
Report errors?		Report errors?

#### MS17347R24C22S Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

#### MS17347R24C22S Payment Methods





















### MS17347R24C22S Shipping Methods













If you have any question about MS17347R24C22S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com