



#### MS17347R24N22S Information

Heisener.com

Part Number MS17347R24N22S

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

Circular Connectors

**Description** CONN RCPT 4POS JAM NUT SKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## MS17347R24N22S Specifications

Manufacturer Part Number     MS 17347R24N22S       Manufacturer     Amphenol Industrial Operations       Category     Connectors, Interconnects       Package     -       Series     Military, MIL-DTL-22992       Connector Type     Receptacle, Female Sockets       Number of Positions     4       Shell Size - Insert     24-22       Shell Size, MIL     -       Mounting Type     Panel Mount, Bulkhead - Front Side Nut       Termination     Solder Cup       Fastening Type     Threaded       Orientation     N (Normal)       Ingress Protection     Waterproof       Shell Material, Finish     Aluminum, Anodic Coating (Alumilite)       Contact Finish     Silver       Features     -       Voltage - Rated     900VAC, 1250VDC       Current Rating     -       Report errors?		
CategoryConnectors, InterconnectsPackage-SeriesMilitary, MIL-DTL-22992Connector TypeReceptacle, Female SocketsNumber of Positions4Shell Size - Insert24-22Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Manufacturer Part Number	MS17347R24N22S
Package-SeriesMilitary, MIL-DTL-22992Connector TypeReceptacle, Female SocketsNumber of Positions4Shell Size - Insert24-22Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Manufacturer	Amphenol Industrial Operations
Package - Series Military, MIL-DTL-22992 Connector Type Receptacle, Female Sockets Number of Positions 4 Shell Size - Insert 24-22 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating	Category	Connectors, Interconnects
Series Military, MIL-DTL-22992 Connector Type Receptacle, Female Sockets Number of Positions 4 Shell Size - Insert 24-22 Shell Size, MIL		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions4Shell Size - Insert24-22Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Package	-
Number of Positions4Shell Size - Insert24-22Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Series	Military, MIL-DTL-22992
Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Connector Type	Receptacle, Female Sockets
Shell Size, MIL  Mounting Type Panel Mount, Bulkhead - Front Side Nut  Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Number of Positions	4
Mounting Type Panel Mount, Bulkhead - Front Side Nut  Termination Solder Cup  Fastening Type Threaded  Orientation N (Normal)  Ingress Protection Waterproof  Shell Material, Finish Aluminum, Anodic Coating (Alumilite)  Contact Finish Silver  Features -  Voltage - Rated 900VAC, 1250VDC  Current Rating -	Shell Size - Insert	24-22
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Shell Size, MIL	-
Fastening Type  Orientation  N (Normal)  Ingress Protection  Waterproof  Shell Material, Finish  Contact Finish  Silver  Features  -  Voltage - Rated  900VAC, 1250VDC  Current Rating  Threaded  N (Normal)  Aluminum, Anodic Coating (Alumilite)  Silver  -  -  -  -  -  -  -  -  -  -  -  -  -	Mounting Type	Panel Mount, Bulkhead - Front Side Nut
Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Termination	Solder Cup
Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Fastening Type	Threaded
Shell Material, Finish  Contact Finish  Silver  Features  - Voltage - Rated  Current Rating  Aluminum, Anodic Coating (Alumilite)  -  -  -  -  -  -  -  -  -  -  -  -  -	Orientation	N (Normal)
Contact Finish  Features  - Voltage - Rated  Current Rating  Silver  -  900VAC, 1250VDC  -	Ingress Protection	Waterproof
Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Shell Material, Finish	Aluminum, Anodic Coating (Alumilite)
Voltage - Rated 900VAC, 1250VDC Current Rating -	Contact Finish	Silver
Current Rating -	Features	-
	Voltage - Rated	900VAC, 1250VDC
Report errors?	Current Rating	-
		Report errors?

#### MS17347R24N22S Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### MS17347R24N22S Payment Methods



















# MS17347R24N22S Shipping Methods













If you have any question about MS17347R24N22S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com