



MS17348R24C11S Information

Heisener.com

Part Number MS17348R24C11S

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects **Circular Connectors**

Description CONN RCPT 9POS JAM NUT SKT

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MS17348R24C11S Specifications

| Manufacturer Part Number MS17348R24C11S Manufacturer Amphenol Industrial Operations Category Connectors, Interconnects Circular Connectors Package - Series Military, MIL-DTL-22992 Connector Type Receptacle, Female Sockets Number of Positions 9 Shell Size - Insert 24-11 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Conductive Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating - Report errors? | | |
|---|--------------------------|--|
| CategoryConnectors, InterconnectsPackage-SeriesMilitary, MIL-DTL-22992Connector TypeReceptacle, Female SocketsNumber of Positions9Shell Size - Insert24-11Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Conductive Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating- | Manufacturer Part Number | MS17348R24C11S |
| Package-SeriesMilitary, MIL-DTL-22992Connector TypeReceptacle, Female SocketsNumber of Positions9Shell Size - Insert24-11Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Conductive Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating- | Manufacturer | Amphenol Industrial Operations |
| Package - Military, MIL-DTL-22992 Connector Type Receptacle, Female Sockets Number of Positions 9 Shell Size - Insert 24-11 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Conductive Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating | Category | Connectors, Interconnects |
| Series Military, MIL-DTL-22992 Connector Type Receptacle, Female Sockets Number of Positions 9 Shell Size - Insert 24-11 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Conductive Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating - | | Circular Connectors |
| Connector TypeReceptacle, Female SocketsNumber of Positions9Shell Size - Insert24-11Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Conductive Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating- | Package | - |
| Number of Positions9Shell Size - Insert24-11Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Conductive Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating- | Series | Military, MIL-DTL-22992 |
| Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Conductive Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating - | Connector Type | Receptacle, Female Sockets |
| Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Conductive Cadmium Plated Contact Finish Features - Voltage - Rated 500VAC, 700VDC Current Rating - | Number of Positions | 9 |
| Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Conductive Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating - | Shell Size - Insert | 24-11 |
| Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Conductive Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating - | Shell Size, MIL | - |
| Fastening Type Orientation N (Normal) Ingress Protection Shell Material, Finish Contact Finish Silver Features - Voltage - Rated Current Rating Threaded N (Normal) N (Normal) Aluminum, Conductive Cadmium Plated Silver - - - - - - - - - - - - - | Mounting Type | Panel Mount, Bulkhead - Front Side Nut |
| Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Conductive Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating - | Termination | Solder Cup |
| Ingress Protection Shell Material, Finish Contact Finish Silver Features - Voltage - Rated Current Rating Waterproof Aluminum, Conductive Cadmium Plated Silver | Fastening Type | Threaded |
| Shell Material, Finish Contact Finish Silver Features - Voltage - Rated Current Rating Aluminum, Conductive Cadmium Plated Silver - - - - - - - - - - - - - | Orientation | N (Normal) |
| Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating - | Ingress Protection | Waterproof |
| Features - Voltage - Rated 500VAC, 700VDC Current Rating - | Shell Material, Finish | Aluminum, Conductive Cadmium Plated |
| Voltage - Rated 500VAC, 700VDC Current Rating - | Contact Finish | Silver |
| Current Rating - | Features | - |
| | Voltage - Rated | 500VAC, 700VDC |
| Report errors? | Current Rating | - |
| | | Report errors? |

MS17348R24C11S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MS17348R24C11S Payment Methods





















MS17348R24C11S Shipping Methods













If you have any question about MS17348R24C11S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com