



MS17348R28C12S Information

Heisener.com

Part Number MS17348R28C12S

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 26POS JAM NUT W/SCKT

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MS17348R28C12S Specifications

Manufacturer Part Number MS17348R28C12S Manufacturer Amphenol Aerospace Operations Category Connectors, Interconnects Circular Connectors Package - Series Military, MIL-DTL-22992 Connector Type Receptacle, Female Sockets Number of Positions 26 Shell Size - Insert 28-12 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Conductive Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating - Report errors?		
Category Connectors, Interconnects Circular Connectors Package - Series Military, MIL-DTL-22992 Connector Type Receptacle, Female Sockets Number of Positions 26 Shell Size - Insert 28-12 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Conductive Cadmium Plated Contact Finish Features - Voltage - Rated Convert Rating Connectors, Interconnects Circular Connectors Military, MIL-DTL-22992 Receptacle, Female Sockets Military, MIL-DTL-22992 Receptacle, Female Sockets Military, MIL-DTL-22992 Receptacle, Female Sockets Nometacle, Female Sockets Number of Position Solder Cup Panel Mount, Bulkhead - Front Side Nut Solder Cup Solder	Manufacturer Part Number	MS17348R28C12S
Package-SeriesMilitary, MIL-DTL-22992Connector TypeReceptacle, Female SocketsNumber of Positions26Shell Size - Insert28-12Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Conductive Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating-	Manufacturer	Amphenol Aerospace Operations
Package - Military, MIL-DTL-22992 Connector Type Receptacle, Female Sockets Number of Positions 26 Shell Size - Insert 28-12 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Conductive Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating	Category	Connectors, Interconnects
Series Military, MIL-DTL-22992 Connector Type Receptacle, Female Sockets Number of Positions 26 Shell Size - Insert 28-12 Shell Size, MIL		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions26Shell Size - Insert28-12Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Conductive Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating-	Package	-
Number of Positions26Shell Size - Insert28-12Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Conductive Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating-	Series	Military, MIL-DTL-22992
Shell Size - Insert 28-12 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Conductive Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Conductive Cadmium Plated Contact Finish Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Number of Positions	26
Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Conductive Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Shell Size - Insert	28-12
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Conductive Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Shell Size, MIL	-
Fastening Type Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Contact Finish Silver Features - Voltage - Rated Current Rating Threaded N (Normal) Waterproof Aluminum, Conductive Cadmium Plated Silver - - - Voltage - Rated Current Rating	Mounting Type	Panel Mount, Bulkhead - Front Side Nut
Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Conductive Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Termination	Solder Cup
Ingress Protection Shell Material, Finish Contact Finish Silver Features - Voltage - Rated Current Rating Waterproof Aluminum, Conductive Cadmium Plated Silver	Fastening Type	Threaded
Shell Material, Finish Contact Finish Silver Features - Voltage - Rated Current Rating Aluminum, Conductive Cadmium Plated Silver - - - - - - - - - - - - -	Orientation	N (Normal)
Contact Finish Features - Voltage - Rated Current Rating Silver - - - - - - - - - - - - -	Ingress Protection	Waterproof
Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Shell Material, Finish	Aluminum, Conductive Cadmium Plated
Voltage - Rated 500VAC, 700VDC Current Rating -	Contact Finish	Silver
Current Rating -	Features	-
	Voltage - Rated	500VAC, 700VDC
Report errors?	Current Rating	-
		Report errors?

MS17348R28C12S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MS17348R28C12S Payment Methods

































If you have any question about MS17348R28C12S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com