



MS25183-20-18P Information

Heisener.com

Part Number MS25183-20-18P **Manufacturer** ITT Cannon, LLC

Category Connectors, Interconnects Circular Connectors

Description CONN PLUG 9 POS STRAIGHT W/PINS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MS25183-20-18P Specifications

Manufacturer Part Number MS25183-20-18P Manufacturer ITT Cannon, LLC Category Connectors, Interconnects Package - Series Military, MIL-DTL-5015, MS Connector Type Plug, Male Pins Number of Positions 9 Shell Size - Insert 20-18 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shielded Voltage - Rated 500VAC, 700VDC		
Category Circular Connectors Package Package Package Plug, Male Pins Plug, Male Pins Pumber of Positions Package Shell Size - Insert Shell Size, MIL Free Hanging (In-Line) Fastening Type Free Hanging (In-Line) Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Shielded Voltage - Rated Sover, 2004 Contact Finish Siever Fastening Fastening Sover, 700VDC	Manufacturer Part Number	MS25183-20-18P
Circular Connectors Package - Series Military, MIL-DTL-5015, MS Connector Type Plug, Male Pins Number of Positions 9 Shell Size - Insert 20-18 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Shielded Voltage - Rated Convertified Contact Finish Silver Features Shielded Voltage - Rated	Manufacturer	ITT Cannon, LLC
Package - Military, MIL-DTL-5015, MS Connector Type Plug, Male Pins Number of Positions 9 Shell Size - Insert 20-18 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shielded Voltage - Rated 500VAC, 700VDC	Category	Connectors, Interconnects
Series Military, MIL-DTL-5015, MS Connector Type Plug, Male Pins Number of Positions 9 Shell Size - Insert 20-18 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shielded Voltage - Rated 500VAC, 700VDC		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions9Shell Size - Insert20-18Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesShieldedVoltage - Rated500VAC, 700VDC	Package	-
Number of Positions Shell Size - Insert 20-18 Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shielded Voltage - Rated 500VAC, 700VDC	Series	Military, MIL-DTL-5015, MS
Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Shielded Voltage - Rated 20-18 Free Hanging (In-Line) Solder Cup Threaded Aluminum Alloy Sliver Freatures Shielded Voltage - Rated	Connector Type	Plug, Male Pins
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Shielded Voltage - Rated Solvac, 700VDC	Number of Positions	9
Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesShieldedVoltage - Rated500VAC, 700VDC	Shell Size - Insert	20-18
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shielded Voltage - Rated 500VAC, 700VDC	Shell Size, MIL	-
Fastening Type Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shielded Voltage - Rated Threaded N (Normal) Environment Resistant Aluminum Alloy, Olive Drab Cadmium Plated Silver Footure Shielded Solver Shovac, 700VDC	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shielded Voltage - Rated 500VAC, 700VDC	Termination	Solder Cup
Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shielded Voltage - Rated 500VAC, 700VDC	Fastening Type	Threaded
Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shielded Voltage - Rated 500VAC, 700VDC	Orientation	N (Normal)
Contact Finish Silver Features Shielded Voltage - Rated 500VAC, 700VDC	Ingress Protection	Environment Resistant
Features Shielded Voltage - Rated 500VAC, 700VDC	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 500VAC, 700VDC	Contact Finish	Silver
-	Features	Shielded
0.00	Voltage - Rated	500VAC, 700VDC
Current Rating 22A, 41A	Current Rating	22A, 41A
Report errors?		Report errors?

MS25183-20-18P Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MS25183-20-18P Payment Methods



















MS25183-20-18P Shipping Methods













If you have any question about MS25183-20-18P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com