



### MS2518314S-1S Information

Heisener.com

**Part Number** MS2518314S-1S **Manufacturer** ITT Cannon, LLC

Category Connectors, Interconnects Circular Connectors

**Description** CONN PLUG 3 POS STRAIGHT W/SCKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **MS2518314S-1S Specifications**

Manufacturer Part Number       MS2518314S-1S         Manufacturer       ITT Cannon, LLC         Category       Connectors, Interconnects         Package       -         Series       Military, MIL-DTL-5015, MS         Connector Type       Plug, Female Sockets         Number of Positions       3         Shell Size - Insert       14S-1         Shell Size, MIL       -         Mounting Type       Free Hanging (In-Line)         Termination       Solder Cup         Fastening Type       Threaded         Orientation       N (Normal)         Ingress Protection       Environment Resistant         Shell Material, Finish       Aluminum Alloy, Olive Drab Cadmium Plated         Contact Finish       Silver         Features       Shielded         Voltage - Rated       500VAC, 700VDC         Current Rating       22A	•	
CategoryConnectors, InterconnectsPackage-SeriesMilitary, MIL-DTL-5015, MSConnector TypePlug, Female SocketsNumber of Positions3Shell Size - Insert14S-1Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesShieldedVoltage - Rated500VAC, 700VDCCurrent Rating22A	Manufacturer Part Number	MS2518314S-1S
Package-SeriesMilitary, MIL-DTL-5015, MSConnector TypePlug, Female SocketsNumber of Positions3Shell Size - Insert14S-1Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesShieldedVoltage - Rated500VAC, 700VDCCurrent Rating22A	Manufacturer	ITT Cannon, LLC
Package-SeriesMilitary, MIL-DTL-5015, MSConnector TypePlug, Female SocketsNumber of Positions3Shell Size - Insert14S-1Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesShieldedVoltage - Rated500VAC, 700VDCCurrent Rating22A	Category	Connectors, Interconnects
Series Military, MIL-DTL-5015, MS  Connector Type Plug, Female Sockets  Number of Positions 3  Shell Size - Insert 14S-1  Shell Size, MIL -  Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Threaded  Orientation N (Normal)  Ingress Protection Environment Resistant  Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Silver  Features Shielded  Voltage - Rated 500VAC, 700VDC  Current Rating 22A		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions3Shell Size - Insert14S-1Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesShieldedVoltage - Rated500VAC, 700VDCCurrent Rating22A	Package	-
Number of Positions3Shell Size - Insert14S-1Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesShieldedVoltage - Rated500VAC, 700VDCCurrent Rating22A	Series	Military, MIL-DTL-5015, MS
Shell Size - Insert Shell Size, MIL	Connector Type	Plug, Female Sockets
Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shielded Voltage - Rated 500VAC, 700VDC Current Rating 22A	Number of Positions	3
Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Threaded  Orientation N (Normal)  Ingress Protection Environment Resistant  Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Silver  Features Shielded  Voltage - Rated 500VAC, 700VDC  Current Rating 22A	Shell Size - Insert	14S-1
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shielded Voltage - Rated 500VAC, 700VDC Current Rating 22A	Shell Size, MIL	-
Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shielded Voltage - Rated 500VAC, 700VDC Current Rating 22A	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shielded Voltage - Rated 500VAC, 700VDC Current Rating 22A	Termination	Solder Cup
Ingress Protection Environment Resistant  Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Silver  Features Shielded  Voltage - Rated 500VAC, 700VDC  Current Rating 22A	Fastening Type	Threaded
Shell Material, Finish Contact Finish Silver Shielded Voltage - Rated Current Rating Aluminum Alloy, Olive Drab Cadmium Plated Silver Shielded 22A	Orientation	N (Normal)
Contact Finish Silver  Features Shielded Voltage - Rated Current Rating 22A	Ingress Protection	Environment Resistant
Features Shielded  Voltage - Rated 500VAC, 700VDC  Current Rating 22A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 500VAC, 700VDC Current Rating 22A	Contact Finish	Silver
Current Rating 22A	Features	Shielded
-	Voltage - Rated	500VAC, 700VDC
Report errors?	Current Rating	22A
		Report errors?

#### MS2518314S-1S Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# MS2518314S-1S Payment Methods





















### MS2518314S-1S Shipping Methods













If you have any question about MS2518314S-1S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com