



## MS27466E11A35P Information

Heisener.com

Part Number MS27466E11A35P

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN RCPT 13POS WALL MNT W/PINS

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# MS27466E11A35P Specifications

Manufacturer Part Number     MS27466E11A35P       Manufacturer     Amphenol Aerospace Operations       Category     Connectors, Interconnects       Package     -       Series     Military, MIL-DTL-38999 Series I       Connector Type     Receptacle, Male Pins       Number of Positions     13       Shell Size - Insert     11-35       Shell Size, MIL     -       Mounting Type     Panel Mount, Flange       Termination     Crimp       Fastening Type     Bayonet Lock       Orientation     N (Normal)       Ingress Protection     Environment Resistant       Shell Material, Finish     Aluminum, Cadmium over Nickel Plated       Contact Finish     Gold       Features     -       Voltage - Rated     400VAC, 500VDC       Current Rating     5A		
Category Connectors, Interconnects Circular Connectors  Package - Series Military, MIL-DTL-38999 Series I Connector Type Receptacle, Male Pins Number of Positions 13 Shell Size - Insert 11-35 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating  Fascening Series I Connectors, Interconnects Circular Connectors  Military, MIL-DTL-38999 Series I Circular Connectors Ingress I Series	Manufacturer Part Number	MS27466E11A35P
Package-SeriesMilitary, MIL-DTL-38999 Series IConnector TypeReceptacle, Male PinsNumber of Positions13Shell Size - Insert11-35Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeatures-Voltage - Rated400VAC, 500VDCCurrent Rating5A	Manufacturer	Amphenol Aerospace Operations
Package - Military, MIL-DTL-38999 Series I Connector Type Receptacle, Male Pins Number of Positions 13 Shell Size - Insert 11-35 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Woltage - Rated 400VAC, 500VDC Current Rating 5	Category	Connectors, Interconnects
Series Military, MIL-DTL-38999 Series I  Connector Type Receptacle, Male Pins  Number of Positions 13  Shell Size - Insert 11-35  Shell Size, MIL		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions13Shell Size - Insert11-35Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeatures-Voltage - Rated400VAC, 500VDCCurrent Rating5A	Package	-
Number of Positions13Shell Size - Insert11-35Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeatures-Voltage - Rated400VAC, 500VDCCurrent Rating5A	Series	Military, MIL-DTL-38999 Series I
Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A	Connector Type	Receptacle, Male Pins
Shell Size, MIL  Mounting Type Panel Mount, Flange  Termination Crimp  Fastening Type Bayonet Lock Orientation N (Normal)  Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated  Contact Finish Features - Voltage - Rated 400VAC, 500VDC  Current Rating  -	Number of Positions	13
Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeatures-Voltage - Rated400VAC, 500VDCCurrent Rating5A	Shell Size - Insert	11-35
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A	Shell Size, MIL	-
Fastening Type  Bayonet Lock Orientation  N (Normal)  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum, Cadmium over Nickel Plated  Contact Finish  Gold  Features  -  Voltage - Rated  400VAC, 500VDC  Current Rating  5A	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A	Termination	Crimp
Ingress Protection Environment Resistant  Shell Material, Finish Aluminum, Cadmium over Nickel Plated  Contact Finish Gold  Features -  Voltage - Rated 400VAC, 500VDC  Current Rating 5A	Fastening Type	Bayonet Lock
Shell Material, Finish  Contact Finish  Gold  Features  - Voltage - Rated  Current Rating  Aluminum, Cadmium over Nickel Plated  Gold  - 5A	Orientation	N (Normal)
Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A	Ingress Protection	Environment Resistant
Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A	Shell Material, Finish	Aluminum, Cadmium over Nickel Plated
Voltage - Rated 400VAC, 500VDC Current Rating 5A	Contact Finish	Gold
Current Rating 5A	Features	-
	Voltage - Rated	400VAC, 500VDC
Report errors?	Current Rating	5A
		Report errors?

### MS27466E11A35P Guarantees



## **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# MS27466E11A35P Payment Methods



















# MS27466E11A35P Shipping Methods













If you have any question about MS27466E11A35P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com