



### MS27467E17F26SC Information

Heisener.com

Part Number MS27467E17F26SC

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN PLUG 26POS STRAIGHT W/SCKT

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## MS27467E17F26SC Specifications

Manufacturer Part Number       MS27467E17F26SC         Manufacturer       Amphenol Aerospace Operations         Category       Connectors, Interconnects         Package       -         Series       Military, MIL-DTL-38999 Series I         Connector Type       Plug, Female Sockets         Number of Positions       26         Shell Size - Insert       17-26         Shell Size, MIL       -         Mounting Type       Free Hanging (In-Line)         Termination       Crimp         Fastening Type       Bayonet Lock         Orientation       C         Ingress Protection       Environment Resistant         Shell Material, Finish       Aluminum, Nickel Plated, Electroless         Contact Finish       Gold         Features       Shielded         Voltage - Rated       600VAC, 850VDC         Current Rating       7.5A		
Category Connectors, Interconnects Circular Connectors  Package - Series Military, MIL-DTL-38999 Series I Connector Type Plug, Female Sockets Number of Positions 26 Shell Size - Insert 17-26 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Crimp Fastening Type Bayonet Lock Orientation C Ingress Protection Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 600VAC, 850VDC Current Rating 7.5A	Manufacturer Part Number	MS27467E17F26SC
Circular Connectors  Package Series Military, MIL-DTL-38999 Series I Connector Type Plug, Female Sockets Number of Positions 26 Shell Size - Insert 17-26 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Crimp Fastening Type Bayonet Lock Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7.5A	Manufacturer	Amphenol Aerospace Operations
Package - Military, MIL-DTL-38999 Series I Connector Type Plug, Female Sockets Number of Positions 26 Shell Size - Insert 17-26 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 600VAC, 850VDC Current Rating 7.5A	Category	Connectors, Interconnects
Series Military, MIL-DTL-38999 Series I  Connector Type Plug, Female Sockets  Number of Positions 26  Shell Size - Insert 17-26  Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Crimp  Fastening Type Bayonet Lock  Orientation C  Ingress Protection Environment Resistant  Shell Material, Finish Aluminum, Nickel Plated, Electroless  Contact Finish Gold  Features Shielded  Voltage - Rated 600VAC, 850VDC  Current Rating 7.5A		Circular Connectors
Connector Type Plug, Female Sockets  Number of Positions 26  Shell Size - Insert 17-26  Shell Size, MIL -  Mounting Type Free Hanging (In-Line)  Termination Crimp  Fastening Type Bayonet Lock  Orientation C  Ingress Protection Environment Resistant  Shell Material, Finish Aluminum, Nickel Plated, Electroless  Contact Finish Gold  Features Shielded  Voltage - Rated 600VAC, 850VDC  Current Rating 7.5A	Package	-
Number of Positions Shell Size - Insert 17-26 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Features Shielded Voltage - Rated OOVAC, 850VDC Current Rating 7.5A	Series	Military, MIL-DTL-38999 Series I
Shell Size - Insert  Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Crimp Fastening Type Bayonet Lock Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Features Shielded Voltage - Rated OOVAC, 850VDC Current Rating  7.5A	Connector Type	Plug, Female Sockets
Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Crimp  Fastening Type Bayonet Lock Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated O0VAC, 850VDC Current Rating 7.5A	Number of Positions	26
Mounting Type Free Hanging (In-Line)  Crimp  Bayonet Lock Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 600VAC, 850VDC Current Rating 7.5A	Shell Size - Insert	17-26
Termination Crimp Fastening Type Bayonet Lock Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 600VAC, 850VDC Current Rating 7.5A	Shell Size, MIL	-
Fastening Type  Orientation  C  Ingress Protection  Shell Material, Finish  Contact Finish  Gold  Features  Voltage - Rated  Current Rating  Bayonet Lock  C  C  Current Rating  Bayonet Lock  C  Current Rating  Bayonet Lock  C  Contact Finish  Contact Finish  Aluminum, Nickel Plated, Electroless  Sold  Food  Gold  Food  Food  T.5A	Mounting Type	Free Hanging (In-Line)
Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 600VAC, 850VDC Current Rating 7.5A	Termination	Crimp
Ingress Protection  Environment Resistant  Aluminum, Nickel Plated, Electroless  Contact Finish  Gold  Features  Shielded  Voltage - Rated  600VAC, 850VDC  Current Rating  7.5A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features Shielded Voltage - Rated Current Rating Aluminum, Nickel Plated, Electroless Gold Food Food Food Food Food Food Food F	Orientation	С
Contact Finish Gold Features Shielded  Voltage - Rated 600VAC, 850VDC  Current Rating 7.5A	Ingress Protection	Environment Resistant
Features Shielded  Voltage - Rated 600VAC, 850VDC  Current Rating 7.5A	Shell Material, Finish	Aluminum, Nickel Plated, Electroless
Voltage - Rated 600VAC, 850VDC Current Rating 7.5A	Contact Finish	Gold
Current Rating 7.5A	Features	Shielded
-	Voltage - Rated	600VAC, 850VDC
Report errors?	Current Rating	7.5A
		Report errors?

#### MS27467E17F26SC Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## MS27467E17F26SC Payment Methods



















# MS27467E17F26SC Shipping Methods













If you have any question about MS27467E17F26SC, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com