



MS27467E25A19SA Information

Heisener.com

Part Number MS27467E25A19SA

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 19POS STRAIGHT W/SCKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MS27467E25A19SA Specifications

Manufacturer Part Number MS27467E25A19SA Manufacturer Amphenol Aerospace Operations Category Connectors, Interconnects Package - Series Military, MIL-DTL-38999 Series I Connector Type Plug, Female Sockets Number of Positions 19 Shell Size - Insert 25-19 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation A Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 600VAC, 850VDC Current Rating 23A		
Category Connectors, Interconnects Circular Connectors Package - Series Military, MIL-DTL-38999 Series I Connector Type Plug, Female Sockets Number of Positions 19 Shell Size - Insert 25-19 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation A Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated Courrent Rating 23A	Manufacturer Part Number	MS27467E25A19SA
Circular Connectors Package - Series Military, MIL-DTL-38999 Series I Connector Type Plug, Female Sockets Number of Positions 19 Shell Size - Insert 25-19 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation A Ingress Protection Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated Courrent Rating 2- Circular Connectors Military, MIL-DTL-38999 Series I Military, MIL Military, MIL Military, MIL-DTL-38999 Series I Military, MIL-DTL-38999 Series I Military, MIL-DTL-38999 Series I Military, MIL-DTL-38999 Series I Military, MIL Military,	Manufacturer	Amphenol Aerospace Operations
Package - Series Military, MIL-DTL-38999 Series I Connector Type Plug, Female Sockets Number of Positions 19 Shell Size - Insert 25-19 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation A Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 600VAC, 850VDC Current Rating 223A	Category	Connectors, Interconnects
Series Military, MIL-DTL-38999 Series I Connector Type Plug, Female Sockets Number of Positions 19 Shell Size - Insert 25-19 Shell Size, MIL		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions19Shell Size - Insert25-19Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationAIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated600VAC, 850VDCCurrent Rating23A	Package	-
Number of Positions19Shell Size - Insert25-19Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationAIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated600VAC, 850VDCCurrent Rating23A	Series	Military, MIL-DTL-38999 Series I
Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line) Crimp Fastening Type Bayonet Lock Orientation A Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 600VAC, 850VDC Current Rating	Connector Type	Plug, Female Sockets
Shell Size, MIL Mounting Type Free Hanging (In-Line) Crimp Fastening Type Bayonet Lock Orientation A Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Features Shielded Voltage - Rated Current Rating 23A	Number of Positions	19
Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation A Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 600VAC, 850VDC Current Rating 23A	Shell Size - Insert	25-19
Termination Crimp Fastening Type Bayonet Lock Orientation A Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 600VAC, 850VDC Current Rating 23A	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation A Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 600VAC, 850VDC Current Rating 23A	Mounting Type	Free Hanging (In-Line)
Orientation A Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 600VAC, 850VDC Current Rating 23A	Termination	Crimp
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 600VAC, 850VDC Current Rating 23A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features Shielded Voltage - Rated Current Rating Aluminum, Cadmium over Nickel Plated Gold Shielded 23A	Orientation	A
Contact Finish Gold Features Shielded Voltage - Rated 600VAC, 850VDC Current Rating 23A	Ingress Protection	Environment Resistant
Features Shielded Voltage - Rated 600VAC, 850VDC Current Rating 23A	Shell Material, Finish	Aluminum, Cadmium over Nickel Plated
Voltage - Rated 600VAC, 850VDC Current Rating 23A	Contact Finish	Gold
Current Rating 23A	Features	Shielded
	Voltage - Rated	600VAC, 850VDC
Report errors?	Current Rating	23A
		Report errors?

MS27467E25A19SA Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MS27467E25A19SA Payment Methods



















MS27467E25A19SA Shipping Methods













If you have any question about MS27467E25A19SA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com