



### MS27467P23B53P Information

Heisener.com

Part Number MS27467P23B53P

Manufacturer Amphenol Aerospace Operations

**Category** Connectors, Interconnects

**Circular Connectors** 

**Description** CONN PLUG 53POS STRAIGHT W/PINS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# MS27467P23B53P Specifications

Manufacturer Part Number       MS27467P23B53P         Manufacturer       Amphenol Aerospace Operations         Category       Connectors, Interconnects         Package       -         Series       Military, MIL-DTL-38999 Series I         Connector Type       Plug, Male Pins         Number of Positions       53         Shell Size - Insert       23-53         Shell Size, MIL       -         Mounting Type       Free Hanging (In-Line)         Termination       Crimp         Fastening Type       Bayonet Lock         Orientation       N (Normal)         Ingress Protection       Environment Resistant         Shell Material, Finish       Aluminum, Olive Drab Cadmium Plated         Contact Finish       Gold         Features       Potted, Shielded         Voltage - Rated       600VAC, 850VDC         Current Rating       7.5A		
Category Connectors, Interconnects Circular Connectors  Package - Series Military, MIL-DTL-38999 Series I  Connector Type Plug, Male Pins  Number of Positions 53 Shell Size - Insert 23-53 Shell Size, MIL - Mounting Type Free Hanging (In-Line)  Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Potted, Shielded Voltage - Rated Convert Rating 7,5A	Manufacturer Part Number	MS27467P23B53P
Circular Connectors  Package - Series Military, MIL-DTL-38999 Series I  Connector Type Plug, Male Pins  Number of Positions 53 Shell Size - Insert 23-53 Shell Size, MIL - Mounting Type Free Hanging (In-Line)  Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Features Potted, Shielded Voltage - Rated Onotact Fating Onotact Finish Fore Military, MIL-DTL-38999 Series I Piug Military,	Manufacturer	Amphenol Aerospace Operations
Package - Series Military, MIL-DTL-38999 Series I Connector Type Plug, Male Pins Number of Positions 53 Shell Size - Insert 23-53 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Potted, Shielded Voltage - Rated 600VAC, 850VDC Current Rating 75	Category	Connectors, Interconnects
Series Military, MIL-DTL-38999 Series I  Connector Type Plug, Male Pins  Number of Positions 53  Shell Size - Insert 23-53  Shell Size, MIL		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions53Shell Size - Insert23-53Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesPotted, ShieldedVoltage - Rated600VAC, 850VDCCurrent Rating7.5A	Package	-
Number of Positions53Shell Size - Insert23-53Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesPotted, ShieldedVoltage - Rated600VAC, 850VDCCurrent Rating7.5A	Series	Military, MIL-DTL-38999 Series I
Shell Size - Insert 23-53 Shell Size, MIL - Mounting Type Free Hanging (In-Line)  Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Potted, Shielded  Voltage - Rated 600VAC, 850VDC Current Rating 7.5A	Connector Type	Plug, Male Pins
Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Crimp Fastening Type Bayonet Lock Orientation N (Normal)  Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated  Contact Finish Features Potted, Shielded  Voltage - Rated 600VAC, 850VDC Current Rating 7.5A	Number of Positions	53
Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesPotted, ShieldedVoltage - Rated600VAC, 850VDCCurrent Rating7.5A	Shell Size - Insert	23-53
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Potted, Shielded Voltage - Rated 600VAC, 850VDC Current Rating 7.5A	Shell Size, MIL	-
Fastening Type  Bayonet Lock  Orientation  N (Normal)  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum, Olive Drab Cadmium Plated  Contact Finish  Gold  Features  Potted, Shielded  Voltage - Rated  600VAC, 850VDC  Current Rating  7.5A	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Potted, Shielded Voltage - Rated 600VAC, 850VDC Current Rating 7.5A	Termination	Crimp
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Potted, Shielded Voltage - Rated 600VAC, 850VDC Current Rating 7.5A	Fastening Type	Bayonet Lock
Shell Material, Finish  Contact Finish  Gold  Features  Potted, Shielded  Voltage - Rated  600VAC, 850VDC  Current Rating  7.5A	Orientation	N (Normal)
Contact Finish Gold Features Potted, Shielded Voltage - Rated 600VAC, 850VDC Current Rating 7.5A	Ingress Protection	Environment Resistant
Features Potted, Shielded  Voltage - Rated 600VAC, 850VDC  Current Rating 7.5A	Shell Material, Finish	Aluminum, Olive Drab Cadmium Plated
Voltage - Rated 600VAC, 850VDC Current Rating 7.5A	Contact Finish	Gold
Current Rating 7.5A	Features	Potted, Shielded
	Voltage - Rated	600VAC, 850VDC
Report errors?	Current Rating	7.5A
		Report errors?

#### MS27467P23B53P Guarantees



## **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# MS27467P23B53P Payment Methods

































If you have any question about MS27467P23B53P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com