



MS27467P25F35S Information

Heisener.com

Part Number MS27467P25F35S

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 128POS STRAIGHT W/SCKT

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MS27467P25F35S Specifications

Manufacturer Part NumberM827467P25F35SManufacturerAmphenol Aerospace OperationsCategoryConnectors, InterconnectsPackage-SeriesMilitary, MIL-DTL-38999 Series IConnector TypePlug, Female SocketsNumber of Positions128Shell Size - Insert25-35Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeaturesPotted, ShieldedVoltage - Rated400VAC, 500VDCCurrent Rating5A		
Category Connectors, Interconnects Circular Connectors Package - Series Military, MIL-DTL-38999 Series I Connector Type Plug, Female Sockets Number of Positions 128 Shell Size - Insert 25-35 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Potted, Shielded Voltage - Rated 400VAC, 500VDC Current Rating 5A	Manufacturer Part Number	MS27467P25F35S
Package-SeriesMilitary, MIL-DTL-38999 Series IConnector TypePlug, Female SocketsNumber of Positions128Shell Size - Insert25-35Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeaturesPotted, ShieldedVoltage - Rated400VAC, 500VDCCurrent Rating5A	Manufacturer	Amphenol Aerospace Operations
Package - Military, MIL-DTL-38999 Series I Connector Type Plug, Female Sockets Number of Positions 128 Shell Size - Insert 25-35 Shell Size, MIL - Community Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Potted, Shielded Voltage - Rated 400VAC, 500VDC Current Rating Series I	Category	Connectors, Interconnects
SeriesMilitary, MIL-DTL-38999 Series IConnector TypePlug, Female SocketsNumber of Positions128Shell Size - Insert25-35Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeaturesPotted, ShieldedVoltage - Rated400VAC, 500VDCCurrent Rating5A		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions128Shell Size - Insert25-35Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeaturesPotted, ShieldedVoltage - Rated400VAC, 500VDCCurrent Rating5A	Package	-
Number of Positions128Shell Size - Insert25-35Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeaturesPotted, ShieldedVoltage - Rated400VAC, 500VDCCurrent Rating5A	Series	Military, MIL-DTL-38999 Series I
Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line) Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Features Potted, Shielded Voltage - Rated 400VAC, 500VDC Current Rating	Connector Type	Plug, Female Sockets
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Features Potted, Shielded Voltage - Rated 400VAC, 500VDC Current Rating Free Hanging (In-Line) Free Hanging (In-Line	Number of Positions	128
Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Potted, Shielded Voltage - Rated 400VAC, 500VDC Current Rating 5A	Shell Size - Insert	25-35
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Potted, Shielded Voltage - Rated 400VAC, 500VDC Current Rating 5A	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Potted, Shielded Voltage - Rated 400VAC, 500VDC Current Rating 5A	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Potted, Shielded Voltage - Rated 400VAC, 500VDC Current Rating 5A	Termination	Crimp
Ingress Protection - Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Potted, Shielded Voltage - Rated 400VAC, 500VDC Current Rating 5A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features Potted, Shielded Voltage - Rated 400VAC, 500VDC Current Rating 5A	Orientation	N (Normal)
Contact Finish Gold Features Potted, Shielded Voltage - Rated 400VAC, 500VDC Current Rating 5A	Ingress Protection	-
Features Potted, Shielded Voltage - Rated 400VAC, 500VDC Current Rating 5A	Shell Material, Finish	Aluminum, Nickel Plated, Electroless
Voltage - Rated 400VAC, 500VDC Current Rating 5A	Contact Finish	Gold
Current Rating 5A	Features	Potted, Shielded
	Voltage - Rated	400VAC, 500VDC
Report errors?	Current Rating	5A
		Report errors?

MS27467P25F35S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MS27467P25F35S Payment Methods



















MS27467P25F35S Shipping Methods













If you have any question about MS27467P25F35S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com