



MS27467T11A35SB Information

Heisener.com

Part Number MS27467T11A35SB

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 13POS STRAIGHT W/SCKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MS27467T11A35SB Specifications

| Manufacturer Part Number MS27467T11A35SB Manufacturer Amphenol Aerospace Operations Category Connectors, Interconnects Package - Series Military, MIL-DTL-38999 Series I Connector Type Plug, Female Sockets Number of Positions 13 Shell Size - Insert 11-35 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation B Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 400 VAC, 500 VDC Current Rating 5A | | |
|--|--------------------------|--------------------------------------|
| Category Circular Connectors Package - Series Military, MIL-DTL-38999 Series I Connector Type Plug, Female Sockets Number of Positions 13 Shell Size - Insert 11-35 Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation B Ingress Protection Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 500VDC Current Rating 5 A | Manufacturer Part Number | MS27467T11A35SB |
| Circular Connectors Package - Series Military, MIL-DTL-38999 Series I Connector Type Plug, Female Sockets Number of Positions 13 Shell Size - Insert 11-35 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation B Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 500VDC Current Rating 54 | Manufacturer | Amphenol Aerospace Operations |
| Package - Series Military, MIL-DTL-38999 Series I Connector Type Plug, Female Sockets Number of Positions 13 Shell Size - Insert 11-35 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation B Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 500VDC Current Rating 5A | Category | Connectors, Interconnects |
| Series Military, MIL-DTL-38999 Series I Connector Type Plug, Female Sockets Number of Positions 13 Shell Size - Insert 11-35 Shell Size, MIL | | Circular Connectors |
| Connector Type Plug, Female Sockets Number of Positions 13 Shell Size - Insert 11-35 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation B Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 500VDC Current Rating 5A | Package | - |
| Number of Positions13Shell Size - Insert11-35Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationBIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated400VAC, 500VDCCurrent Rating5A | Series | Military, MIL-DTL-38999 Series I |
| Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation B Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 500VDC Current Rating 5A | Connector Type | Plug, Female Sockets |
| Shell Size, MIL Mounting Type Free Hanging (In-Line) Crimp Fastening Type Bayonet Lock Orientation B Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 500VDC Current Rating 5A | Number of Positions | 13 |
| Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation B Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 500VDC Current Rating 5A | Shell Size - Insert | 11-35 |
| Termination Crimp Fastening Type Bayonet Lock Orientation B Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 500VDC Current Rating 5A | Shell Size, MIL | - |
| Fastening Type Bayonet Lock Orientation B Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 500VDC Current Rating 5A | Mounting Type | Free Hanging (In-Line) |
| Orientation B Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 500VDC Current Rating 5A | Termination | Crimp |
| Ingress Protection Environment Resistant Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 500VDC Current Rating 5A | Fastening Type | Bayonet Lock |
| Shell Material, Finish Contact Finish Gold Features Shielded Voltage - Rated Current Rating Aluminum, Cadmium over Nickel Plated Gold Shielded 400VAC, 500VDC 5A | Orientation | В |
| Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 500VDC Current Rating 5A | Ingress Protection | Environment Resistant |
| Features Shielded Voltage - Rated 400VAC, 500VDC Current Rating 5A | Shell Material, Finish | Aluminum, Cadmium over Nickel Plated |
| Voltage - Rated 400VAC, 500VDC Current Rating 5A | Contact Finish | Gold |
| Current Rating 5A | Features | Shielded |
| - | Voltage - Rated | 400VAC, 500VDC |
| Report errors? | Current Rating | 5A |
| | | Report errors? |

MS27467T11A35SB Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MS27467T11A35SB Payment Methods



















MS27467T11A35SB Shipping Methods













If you have any question about MS27467T11A35SB, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com