



MS27467T11B35PD Information

Heisener.com

Part Number MS27467T11B35PD

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects **Circular Connectors**

Description CONN PLUG 13POS STRAIGHT W/PINS

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MS27467T11B35PD Specifications

Manufacturer Part Number MS27467T11B35PD Manufacturer Amphenol Aerospace Operations Category Connectors, Interconnects Package - Series Military, MIL-DTL-38999 Series I Connector Type Plug, Male Pins Number of Positions 13 Shell Size - Insert 11-35 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation D Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 500VDC Current Rating 5A		
Category Connectors, Interconnects Circular Connectors Package - Series Military, MIL-DTL-38999 Series I Connector Type Plug, Male Pins Number of Positions 13 Shell Size - Insert 11-35 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation D Ingress Protection Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Voltage - Rated 400VAC, 500VDC Current Rating Series Circular Connectors Military, MIL-DTL-38999 Series I Circular Connectors Military, MIL-DTL-38999 Series I Fully Aluminum, Olive Drab Cadmium Plated Gold Gold Gold Series Shielded Voltage - Rated 400VAC, 500VDC Current Rating	Manufacturer Part Number	MS27467T11B35PD
Package-SeriesMilitary, MIL-DTL-38999 Series IConnector TypePlug, Male PinsNumber of Positions13Shell Size - Insert11-35Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationDIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShieldedVoltage - Rated400VAC, 500VDCCurrent Rating5A	Manufacturer	Amphenol Aerospace Operations
Package-SeriesMilitary, MIL-DTL-38999 Series IConnector TypePlug, Male PinsNumber of Positions13Shell Size - Insert11-35Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationDIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShieldedVoltage - Rated400VAC, 500VDCCurrent Rating5A	Category	Connectors, Interconnects
Series Military, MIL-DTL-38999 Series I Connector Type Plug, Male Pins Number of Positions 13 Shell Size - Insert 11-35 Shell Size, MIL		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions13Shell Size - Insert11-35Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationDIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShieldedVoltage - Rated400VAC, 500VDCCurrent Rating5A	Package	-
Number of Positions13Shell Size - Insert11-35Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationDIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShieldedVoltage - Rated400VAC, 500VDCCurrent Rating5A	Series	Military, MIL-DTL-38999 Series I
Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line) Crimp Fastening Type Bayonet Lock Orientation D Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Features Shielded Voltage - Rated Voltage - Rated Current Rating Shell Size - Insert Sree Hanging (In-Line) Free Hanging (In-Line) Free Hanging (In-Line) Crimp Factors Show Hanging S	Connector Type	Plug, Male Pins
Shell Size, MIL Mounting Type Free Hanging (In-Line) Crimp Fastening Type Bayonet Lock Orientation D Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Features Shielded Voltage - Rated 400VAC, 500VDC Current Rating Free Hanging (In-Line) Crimp Bayonet Lock D Aluminum Dlated Contact Finish Aluminum, Olive Drab Cadmium Plated Shielded Voltage - Rated 400VAC, 500VDC	Number of Positions	13
Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationDIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShieldedVoltage - Rated400VAC, 500VDCCurrent Rating5A	Shell Size - Insert	11-35
Termination Crimp Fastening Type Bayonet Lock Orientation D Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 500VDC Current Rating 5A	Shell Size, MIL	-
Fastening Type Orientation D Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 500VDC Current Rating 5A	Mounting Type	Free Hanging (In-Line)
Orientation D Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 500VDC Current Rating 5A	Termination	Crimp
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 500VDC Current Rating 5A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features Shielded Voltage - Rated Current Rating Aluminum, Olive Drab Cadmium Plated Gold Contact Finish Gold Shielded 5A	Orientation	D
Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 500VDC Current Rating 5A	Ingress Protection	Environment Resistant
Features Shielded Voltage - Rated 400VAC, 500VDC Current Rating 5A	Shell Material, Finish	Aluminum, Olive Drab Cadmium Plated
Voltage - Rated 400VAC, 500VDC Current Rating 5A	Contact Finish	Gold
Current Rating 5A	Features	Shielded
	Voltage - Rated	400VAC, 500VDC
	Current Rating	5A
Report errors?		Report errors?

MS27467T11B35PD Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MS27467T11B35PD Payment Methods



















MS27467T11B35PD Shipping Methods













If you have any question about MS27467T11B35PD, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com