



MS27467T17A6S Information

Heisener.com

Part Number MS27467T17A6S

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 6POS STRAIGHT W/SCKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MS27467T17A6S Specifications

Manufacturer Part NumberMS27467T17A6SManufacturerAmphenol Aerospace OperationsCategoryConnectors, InterconnectsPackage-SeriesMilitary, MIL-DTL-38999 Series IConnector TypePlug, Female SocketsNumber of Positions6Shell Size - Insert17-6Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated600VAC, 850VDCCurrent Rating23A		
Category Connectors, Interconnects Circular Connectors Package - Series Military, MIL-DTL-38999 Series I Connector Type Plug, Female Sockets Number of Positions 6 Shell Size - Insert 17-6 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Voltage - Rated Converted Shell Advance Science Circular Connectors Military, MIL-DTL-38999 Series I Aluminary, MIL-DTL-38999 Series I Fremise I Aluminary Sockets Nell Size, MIL Alumination Science Circular Connectors Aluminum, Cadmium over Nickel Plated Contact Finish Gold Voltage - Rated	Manufacturer Part Number	MS27467T17A6S
Package-SeriesMilitary, MIL-DTL-38999 Series IConnector TypePlug, Female SocketsNumber of Positions6Shell Size - Insert17-6Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated600VAC, 850VDC	Manufacturer	Amphenol Aerospace Operations
Package - Series Military, MIL-DTL-38999 Series I Connector Type Plug, Female Sockets Number of Positions 6 Shell Size - Insert 17-6 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Voltage - Rated 600VAC, 850VDC	Category	Connectors, Interconnects
Series Military, MIL-DTL-38999 Series I Connector Type Plug, Female Sockets Number of Positions 6 Shell Size - Insert 17-6 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 600VAC, 850VDC		Circular Connectors
Connector Type Plug, Female Sockets Number of Positions 6 Shell Size - Insert 17-6 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 600VAC, 850VDC	Package	-
Number of Positions Shell Size - Insert 17-6 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Voltage - Rated 600VAC, 850VDC	Series	Military, MIL-DTL-38999 Series I
Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Features Shielded Voltage - Rated 600VAC, 850VDC	Connector Type	Plug, Female Sockets
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 600VAC, 850VDC	Number of Positions	6
Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated600VAC, 850VDC	Shell Size - Insert	17-6
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 600VAC, 850VDC	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 600VAC, 850VDC	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 600VAC, 850VDC	Termination	Crimp
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 600VAC, 850VDC	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features Shielded Voltage - Rated Aluminum, Cadmium over Nickel Plated Gold Gold 600VAC, 850VDC	Orientation	N (Normal)
Contact Finish Gold Features Shielded Voltage - Rated 600VAC, 850VDC	Ingress Protection	Environment Resistant
Features Shielded Voltage - Rated 600VAC, 850VDC	Shell Material, Finish	Aluminum, Cadmium over Nickel Plated
Voltage - Rated 600VAC, 850VDC	Contact Finish	Gold
	Features	Shielded
Current Rating 23A	Voltage - Rated	600VAC, 850VDC
	Current Rating	23A
Report errors?		Report errors?

MS27467T17A6S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MS27467T17A6S Payment Methods



















MS27467T17A6S Shipping Methods













If you have any question about MS27467T17A6S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com