



MS27468E13B98S Information

Heisener.com

Part Number MS27468E13B98S

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 10POS JAM NUT W/SCKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MS27468E13B98S Specifications

Manufacturer Part Number MS27468E13B98S Manufacturer Amphenol Aerospace Operations Category Connectors, Interconnects Circular Connectors Package - Series Military, MIL-DTL-38999 Series I Connector Type Receptacle, Female Sockets Number of Positions 10 Shell Size - Insert 13-98 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating 7.5A		
Category Connectors, Interconnects Circular Connectors Package - Series Military, MIL-DTL-38999 Series I Connector Type Receptacle, Female Sockets Number of Positions 10 Shell Size - Insert 13-98 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating 7,5A	Manufacturer Part Number	MS27468E13B98S
Circular Connectors Package - Series Military, MIL-DTL-38999 Series I Connector Type Receptacle, Female Sockets Number of Positions 10 Shell Size - Insert 13-98 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating 7.5A	Manufacturer	Amphenol Aerospace Operations
Package-SeriesMilitary, MIL-DTL-38999 Series IConnector TypeReceptacle, Female SocketsNumber of Positions10Shell Size - Insert13-98Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated600VAC, 850VDCCurrent Rating7.5A	Category	Connectors, Interconnects
Series Military, MIL-DTL-38999 Series I Connector Type Receptacle, Female Sockets Number of Positions 10 Shell Size - Insert 13-98 Shell Size, MIL		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions10Shell Size - Insert13-98Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated600VAC, 850VDCCurrent Rating7.5A	Package	-
Number of Positions10Shell Size - Insert13-98Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated600VAC, 850VDCCurrent Rating7.5A	Series	Military, MIL-DTL-38999 Series I
Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating 7.5A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated 600VAC, 850VDC Current Rating 7.5A	Number of Positions	10
Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated600VAC, 850VDCCurrent Rating7.5A	Shell Size - Insert	13-98
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating 7.5A	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating 7.5A	Mounting Type	Panel Mount, Bulkhead - Front Side Nut
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating 7.5A	Termination	Crimp
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating 7.5A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Current Rating Aluminum, Olive Drab Cadmium Plated Gold 600VAC, 850VDC 7.5A	Orientation	N (Normal)
Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating 7.5A	Ingress Protection	Environment Resistant
Features - Voltage - Rated 600VAC, 850VDC Current Rating 7.5A	Shell Material, Finish	Aluminum, Olive Drab Cadmium Plated
Voltage - Rated 600VAC, 850VDC Current Rating 7.5A	Contact Finish	Gold
Current Rating 7.5A	Features	-
	Voltage - Rated	600VAC, 850VDC
Report errors?	Current Rating	7.5A
		Report errors?

MS27468E13B98S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MS27468E13B98S Payment Methods



















MS27468E13B98S Shipping Methods













If you have any question about MS27468E13B98S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com