



MS27468E21A35PB Information

Heisener.com

Part Number MS27468E21A35PB

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 79POS JAM NUT W/PINS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MS27468E21A35PB Specifications

Manufacturer Part Number MS27468E21A35PB Manufacturer Amphenol Aerospace Operations Category Connectors, Interconnects Circular Connectors Package - Series Military, MIL-DTL-38999 Series I Connector Type Receptacle, Male Pins Number of Positions 79 Shell Size - Insert 21-35 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation B Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A		
Category Connectors, Interconnects Circular Connectors Package - Series Military, MIL-DTL-38999 Series I Connector Type Receptacle, Male Pins Number of Positions 79 Shell Size - Insert 21-35 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation B Ingress Protection Be Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating Series - Circular Connectors Military, MIL-DTL-38999 Series I Receptacle, Male Pins Pasens Ingress I Receptacle, Male Pins Pasens Ingress Protection Bayonet Lock Orientation B Ingress Protection Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Features - Voltage - Rated 400VAC, 500VDC Current Rating	Manufacturer Part Number	MS27468E21A35PB
Package-SeriesMilitary, MIL-DTL-38999 Series IConnector TypeReceptacle, Male PinsNumber of Positions79Shell Size - Insert21-35Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeBayonet LockOrientationBIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeatures-Voltage - Rated400VAC, 500VDCCurrent Rating5A	Manufacturer	Amphenol Aerospace Operations
Package-SeriesMilitary, MIL-DTL-38999 Series IConnector TypeReceptacle, Male PinsNumber of Positions79Shell Size - Insert21-35Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeBayonet LockOrientationBIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeatures-Voltage - Rated400VAC, 500VDCCurrent Rating5A	Category	Connectors, Interconnects
Series Military, MIL-DTL-38999 Series I Connector Type Receptacle, Male Pins Number of Positions 79 Shell Size - Insert 21-35 Shell Size, MIL		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions79Shell Size - Insert21-35Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeBayonet LockOrientationBIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeatures-Voltage - Rated400VAC, 500VDCCurrent Rating5A	Package	-
Number of Positions79Shell Size - Insert21-35Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeBayonet LockOrientationBIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeatures-Voltage - Rated400VAC, 500VDCCurrent Rating5A	Series	Military, MIL-DTL-38999 Series I
Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation B Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Voltage - Rated 400VAC, 500VDC Current Rating 5A	Connector Type	Receptacle, Male Pins
Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation B Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Features Voltage - Rated 400VAC, 500VDC Current Rating 5A	Number of Positions	79
Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation B Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A	Shell Size - Insert	21-35
Termination Crimp Fastening Type Bayonet Lock Orientation B Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation B Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A	Mounting Type	Panel Mount, Bulkhead - Front Side Nut
Orientation B Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A	Termination	Crimp
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features Voltage - Rated Current Rating Aluminum, Cadmium over Nickel Plated Gold 400VAC, 500VDC 5A	Orientation	В
Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A	Ingress Protection	Environment Resistant
Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A	Shell Material, Finish	Aluminum, Cadmium over Nickel Plated
Voltage - Rated 400VAC, 500VDC Current Rating 5A	Contact Finish	Gold
Current Rating 5A	Features	-
	Voltage - Rated	400VAC, 500VDC
Report errors?	Current Rating	5A
		Report errors?

MS27468E21A35PB Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MS27468E21A35PB Payment Methods



















MS27468E21A35PB Shipping Methods













If you have any question about MS27468E21A35PB, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com