



### MS27468E25F35SC Information

Heisener.com

Part Number MS27468E25F35SC

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects

Circular Connectors

**Description** CONN RCPT 128POS JAM NUT W/SCKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## MS27468E25F35SC Specifications

| Manufacturer Part Number       MS27468E25F35SC         Manufacturer       Amphenol Aerospace Operations         Category       Connectors, Interconnects         Package       -         Series       Military, MIL-DTL-38999 Series I         Connector Type       Receptacle, Female Sockets         Number of Positions       128         Shell Size - Insert       25-35         Shell Size, MIL       -         Mounting Type       Panel Mount, Bulkhead - Front Side Nut         Termination       Crimp         Fastening Type       Bayonet Lock         Orientation       C         Ingress Protection       Environment Resistant         Shell Material, Finish       Aluminum, Nickel Plated, Electroless         Contact Finish       Gold         Features       -         Voltage - Rated       400VAC, 500VDC         Current Rating       5A    Report errors? |                          |  |
|--|--------------------------|--|
| Category Connectors, Interconnects Circular Connectors  Package - Series Military, MIL-DTL-38999 Series I Connector Type Receptacle, Female Sockets Number of Positions 128 Shell Size - Insert 25-35 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation C Ingress Protection Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating  5A   | Manufacturer Part Number | MS27468E25F35SC                        |
| Circular Connectors  Package - Series Military, MIL-DTL-38999 Series I  Connector Type Receptacle, Female Sockets  Number of Positions 128  Shell Size - Insert 25-35  Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut  Termination Crimp Fastening Type Bayonet Lock Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating  5A   | Manufacturer             | Amphenol Aerospace Operations          |
| Package-SeriesMilitary, MIL-DTL-38999 Series IConnector TypeReceptacle, Female SocketsNumber of Positions128Shell Size - Insert25-35Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeBayonet LockOrientationCIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated400VAC, 500VDCCurrent Rating5A   | Category                 | Connectors, Interconnects              |
| Series Military, MIL-DTL-38999 Series I  Connector Type Receptacle, Female Sockets  Number of Positions 128  Shell Size - Insert 25-35  Shell Size, MIL  |                          | Circular Connectors                    |
| Connector TypeReceptacle, Female SocketsNumber of Positions128Shell Size - Insert25-35Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeBayonet LockOrientationCIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated400VAC, 500VDCCurrent Rating5A   | Package                  | -                                      |
| Number of Positions128Shell Size - Insert25-35Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeBayonet LockOrientationCIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated400VAC, 500VDCCurrent Rating5A   | Series                   | Military, MIL-DTL-38999 Series I       |
| Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A  | Connector Type           | Receptacle, Female Sockets             |
| Shell Size, MIL  Mounting Type Panel Mount, Bulkhead - Front Side Nut  Crimp Fastening Type Bayonet Lock Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Features - Voltage - Rated 400VAC, 500VDC Current Rating  5A  | Number of Positions      | 128                                    |
| Mounting Type Panel Mount, Bulkhead - Front Side Nut  Termination Crimp  Fastening Type Bayonet Lock  Orientation C  Ingress Protection Environment Resistant  Shell Material, Finish Aluminum, Nickel Plated, Electroless  Contact Finish Gold  Features -  Voltage - Rated 400VAC, 500VDC  Current Rating 5A   | Shell Size - Insert      | 25-35                                  |
| Termination Crimp Fastening Type Bayonet Lock Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A   | Shell Size, MIL          | -                                      |
| Fastening Type  Orientation  C  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum, Nickel Plated, Electroless  Contact Finish  Gold  Features  -  Voltage - Rated  400VAC, 500VDC  Current Rating  5A  | Mounting Type            | Panel Mount, Bulkhead - Front Side Nut |
| Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A   | Termination              | Crimp                                  |
| Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A   | Fastening Type           | Bayonet Lock                           |
| Shell Material, Finish  Contact Finish  Gold  Features  - Voltage - Rated  Current Rating  Aluminum, Nickel Plated, Electroless  Gold  - 5A  | Orientation              | C                                      |
| Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A  | Ingress Protection       | Environment Resistant                  |
| Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A  | Shell Material, Finish   | Aluminum, Nickel Plated, Electroless   |
| Voltage - Rated 400VAC, 500VDC Current Rating 5A   | Contact Finish           | Gold                                   |
| Current Rating 5A  | Features                 | -                                      |
|  | Voltage - Rated          | 400VAC, 500VDC                         |
| Report errors?   | Current Rating           | 5A                                     |
|  |                          | Report errors?                         |

#### MS27468E25F35SC Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## MS27468E25F35SC Payment Methods



















# MS27468E25F35SC Shipping Methods













If you have any question about MS27468E25F35SC, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com