



MS27468P19F35SA Information

Heisener.com

Part Number MS27468P19F35SA

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 66POS JAM NUT W/SCKT

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MS27468P19F35SA Specifications

Manufacturer Part Number MS27468P19F35SA Manufacturer Amphenol Aerospace Operations Category Connectors, Interconnects Package - Series Military, MIL-DTL-38999 Series I Connector Type Receptacle, Female Sockets Number of Positions 66 Shell Size - Insert 19-35 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation A Ingress Protection - Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Potted Voltage - Rated 400VAC, 500VDC Current Rating 5A		
Category Connectors, Interconnects Circular Connectors Package - Series Military, MIL-DTL-38999 Series I Connector Type Receptacle, Female Sockets Number of Positions 66 Shell Size - Insert 19-35 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation A Ingress Protection Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Potted Voltage - Rated 400VAC, 500VDC Current Rating 5 Connectors, Interconnects Circular Connectors Military, MIL-DTL-38999 Series I Activation Facecptacle, Female Sockets Military, MIL-DTL-38999 Series I Activation Facecptacle, Female Sockets Military, MIL-DTL-38999 Series I Activation Facecptacle Female Sockets Military, MIL-DTL-38999 Series I Activation Facecptacle Female Sockets Activation Fe	Manufacturer Part Number	MS27468P19F35SA
Package-SeriesMilitary, MIL-DTL-38999 Series IConnector TypeReceptacle, Female SocketsNumber of Positions66Shell Size - Insert19-35Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeBayonet LockOrientationAIngress Protection-Shell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeaturesPottedVoltage - Rated400VAC, 500VDCCurrent Rating5A	Manufacturer	Amphenol Aerospace Operations
Package-SeriesMilitary, MIL-DTL-38999 Series IConnector TypeReceptacle, Female SocketsNumber of Positions66Shell Size - Insert19-35Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeBayonet LockOrientationAIngress Protection-Shell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeaturesPottedVoltage - Rated400VAC, 500VDCCurrent Rating5A	Category	Connectors, Interconnects
Series Military, MIL-DTL-38999 Series I Connector Type Receptacle, Female Sockets Number of Positions 66 Shell Size - Insert 19-35 Shell Size, MIL		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions66Shell Size - Insert19-35Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeBayonet LockOrientationAIngress Protection-Shell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeaturesPottedVoltage - Rated400VAC, 500VDCCurrent Rating5A	Package	-
Number of Positions66Shell Size - Insert19-35Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeBayonet LockOrientationAIngress Protection-Shell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeaturesPottedVoltage - Rated400VAC, 500VDCCurrent Rating5A	Series	Military, MIL-DTL-38999 Series I
Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation A Ingress Protection - Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Potted Voltage - Rated 400VAC, 500VDC Current Rating 5A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Crimp Fastening Type Bayonet Lock Orientation A Ingress Protection - Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Features Potted Voltage - Rated 400VAC, 500VDC Current Rating - Carrent Rating	Number of Positions	66
Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeBayonet LockOrientationAIngress Protection-Shell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeaturesPottedVoltage - Rated400VAC, 500VDCCurrent Rating5A	Shell Size - Insert	19-35
Termination Crimp Fastening Type Bayonet Lock Orientation A Ingress Protection - Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Potted Voltage - Rated 400VAC, 500VDC Current Rating 5A	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation A Ingress Protection - Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Potted Voltage - Rated 400VAC, 500VDC Current Rating 5A	Mounting Type	Panel Mount, Bulkhead - Front Side Nut
Orientation A Ingress Protection - Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Potted Voltage - Rated 400VAC, 500VDC Current Rating 5A	Termination	Crimp
Ingress Protection - Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Potted Voltage - Rated 400VAC, 500VDC Current Rating 5A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features Potted Voltage - Rated Current Rating Aluminum, Nickel Plated, Electroless Gold Potted 5A	Orientation	A
Contact Finish Gold Features Potted Voltage - Rated 400VAC, 500VDC Current Rating 5A	Ingress Protection	-
Features Potted Voltage - Rated 400VAC, 500VDC Current Rating 5A	Shell Material, Finish	Aluminum, Nickel Plated, Electroless
Voltage - Rated 400VAC, 500VDC Current Rating 5A	Contact Finish	Gold
Current Rating 5A	Features	Potted
	Voltage - Rated	400VAC, 500VDC
Report errors?	Current Rating	5A
		Report errors?

MS27468P19F35SA Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MS27468P19F35SA Payment Methods



















MS27468P19F35SA Shipping Methods













If you have any question about MS27468P19F35SA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com